

Shafts

Type WRA

Stainless steel shafts WRA

- **WRA** Full stainless steel shafts, induction hardened, HRC 52 - 56, ground, chemicals resistant, material X-90CrMoV18 (1.4112)

Shaft diameter d (mm)	Weight of 1 m (kg)	Description	Max. production length (mm)	Thickness of hardened layer (mm)	Standard tolerance ISO h6 (µm)
5	0,154	WRA05	6000	0,7	0/-8
6	0,222	WRA06	6000	0,7	0/-8
8	0,395	WRA08	6000	0,9	0/-9
10	0,617	WRA10	6000	1,1	0/-9
12	0,888	WRA12	6000	1,3	0/-11
14	1,208	WRA14	6000	1,5	0/-11
15	1,387	WRA15	6000	1,6	0/-11
16	1,578	WRA16	6000	1,6	0/-11
20	2,466	WRA20	6000	1,8	0/-13
25	3,853	WRA25	6000	2,0	0/-13
30	5,549	WRA30	6000	2,4	0/-13
40	9,865	WRA40	6000	2,6	0/-16

HIWIN s.r.o

MEDKOVA 888/11

627 00 BRNO

CZECH REPUBLIC

TEL: +420 548 528 233

FAX: +420 548 220 223

EMAIL: INFO@HIWIN.CZ

WWW.HIWIN.CZ