

Shafts

Type WRB

Stainless steel shafts WRB

- **WRB** Full stainless steel shafts, induction hardened, HRC 51 - 55, ground, material X-46Cr13 (1.4043)

Shaft diameter d (mm)	Weight of 1 m (kg)	Description	Max. production length (mm)	Thickness of hardened layer (mm)	Standard tolerance ISO h6 (µm)
5	0,154	WRB05	1000	0,7	0/-8
6	0,222	WRB06	3900	0,7	0/-8
8	0,395	WRB08	3900	0,9	0/-9
10	0,617	WRB10	3900	1,1	0/-9
12	0,888	WRB12	4900	1,3	0/-11
14	1,208	WRB14	4900	1,5	0/-11
15	1,387	WRB15	4900	1,6	0/-11
16	1,578	WRB16	4900	1,6	0/-11
20	2,466	WRB20	4900	1,8	0/-13
25	3,853	WRB25	4900	2,0	0/-13
30	5,549	WRB30	4900	2,4	0/-13
40	9,865	WRB40	4900	2,6	0/-16
50	15,410	WRB50	4900	2,9	0/-16
60	22,200	WRB60	4900	3,0	0/-19

HIWIN s.r.o

MEDKOVÁ 888/11

627 00 BRNO

CZECH REPUBLIC

TEL : +420 548 528 238

FAX : +420 548 220 223

EMAIL : INFO@HIWIN.CZ

WWW.HIWIN.CZ