

Shafts

Type WV

Hardened chrome plated shafts WV

- **WV** Full shafts, induction hardened, chrome plated, layer 7-10 µm, HV 900-1100, ground, material Cf53 Cr (1.1213)

Shaft diameter d (mm)	Weight of 1 m (kg)	Description	Max. production length (mm)	Thickness of hardened layer (mm)	Standard tolerance ISO h7 (µm)
5	0,154	WV05	6000	0,8	0/-12
6	0,222	WV06	6000	0,8	0/-12
8	0,395	WV08	6000	1,0	0/-15
10	0,617	WV10	6000	1,0	0/-15
12	0,888	WV12	6000	1,3	0/-18
14	1,208	WV14	6000	1,3	0/-18
15	1,387	WV15	6000	1,3	0/-18
16	1,578	WV16	6000	1,6	0/-18
20	2,466	WV20	6000	1,6	0/-21
25	3,853	WV25	6000	1,8	0/-21
30	5,549	WV30	6000	2,0	0/-21
35	7,553	WV35	6000	2,5	0/-25
40	9,865	WV40	6000	2,5	0/-25
50	15,410	WV50	6000	3,0	0/-25
60	22,200	WV60	6000	3,0	0/-30

HIWIN s.r.o
 MEDKOVA 888/11
 627 00 BRNO
 CZECH REPUBLIC
 TEL.: +420 548 528 238
 FAX: +420 548 220 223
 EMAIL: INFO@HIWIN.CZ
WWW.HIWIN.CZ