

Rotary Tables

Motors, Drives & Accessories

Rotary Tables

Directly-driven rotary tables from HIWIN have a backlash-free and very rigid design, making them highly versatile. The compact design makes the tables easy to integrate and allows for a space-saving setup. Various diameters and heights simplify the process of selecting the right rotary table. On request, the rotary tables are also supplied as a complete system with drive.

Rotary Tables

Contents

Contents

| | | |
|----------|--|-----------|
| 1 | Product overview | 7 |
| 2 | Sample applications | 8 |
| 2.1 | HIWIN rotary tables optimise transport processes | 8 |
| 2.2 | HIWIN rotary table in glass plate handling | 8 |
| 3 | HIWIN rotary tables TMS | 9 |
| 3.1 | Characteristics of the TMS rotary tables | 9 |
| 3.2 | Order code for TMS rotary tables | 9 |
| 3.3 | Technical data for TMS | 10 |
| 3.3.1 | Technical data for TMS0 | 10 |
| 3.3.2 | Technical data for TMS1 | 12 |
| 3.3.3 | Technical data for TMS3 | 14 |
| 3.3.4 | Technical data for TMS7 | 18 |
| 4 | HIWIN rotary tables TMB | 22 |
| 4.1 | Characteristics of the TMB rotary tables | 22 |
| 4.2 | Order code for TMB rotary tables | 22 |
| 4.3 | Technical data for TMBO | 23 |
| 5 | HIWIN rotary tables TMN | 25 |
| 5.1 | Characteristics of the TMN rotary tables | 25 |
| 5.2 | Order code for TMN rotary tables | 25 |
| 5.3 | Technical data for TMN | 26 |
| 5.3.1 | Technical data for TMN42 | 26 |
| 5.3.2 | Technical data for TMN71 | 28 |
| 5.3.3 | Technical data for TMN93 | 30 |
| 6 | HIWIN rotary tables TMA | 32 |
| 6.1 | Characteristics of the TMA rotary tables | 32 |
| 6.2 | Order code for TMA rotary tables | 32 |
| 6.3 | Technical data for TMA32 | 32 |

Rotary Tables

Product overview

1. Product overview



HIWIN rotary tables TMS

[Page 9](#)

- Standard series
- Torques up to 450 Nm
- Integrated rotary encoder
- Outer diameter 110 – 300 mm
- With pneumatic clamping as an option



HIWIN rotary tables TMB

[Page 22](#)

- Compact design
- Torques up to 6.4 Nm
- Outer diameter 65 mm
- Integrated rotary encoder



HIWIN rotary tables TMN

[Page 25](#)

- Extremely flat design
- Torques up to 39.6 Nm
- Outer diameter 118 – 230 mm
- Integrated rotary encoder



HIWIN rotary tables TMA

[Page 32](#)

- Air bearings
- Highest accuracy and synchronism
- Integrated rotary encoder

Rotary Tables


Sample applications, HIWIN rotary tables TMS

2. Sample applications

2.1 HIWIN rotary tables optimise transport processes

The specification

- Rapid positioning when transporting the work-pieces between the interlinked system parts on a vertical circular path = special requirements apply to acceleration and braking due to the short distances travelled
- Flexible solution, allowing changes or additions to be made during commissioning
- It should be possible for the system to be stopped in any position in order to inspect the parts



Our solution

- Swivel drive minimises the cycle times = saves time and money
- Centrifugal forces are reduced = transport components swiftly and gently to the next station with the gripper arm
- Precision bearing and optical positioning measurement system = maximum reproducibility
- Design with hollow shaft = pass cables or mechanisms through with ease
- Direct drive = no gearbox backlash or gearbox mechanisms prone to wear

2.2 HIWIN rotary table in glass plate handling

The specification

- Lay-up station in which the finished strings are drawn in with special vacuum suckers after welding. The strings are then swivelled and deposited either in string boxes or on glass plates
- The current method of holding the Z-axis for the cross bar above toothed belt and servo motor is to be replaced because it takes up too much room and is too heavy
- A high level of torque and a compact design are needed due to the long swivel arm and high inherent weight of the arm
- High speed is needed because of the short cycle times required



Our solution

- Rotary indexing table = high torque and compact design = high throughput, space and cost savings
- Design with hollow shaft = pneumatic hoses and cables can pass through
- Direct drive = no gearbox clearance or gearbox mechanisms prone to wear
- Adaptation to existing control

3. HIWIN rotary tables TMS

3.1 Characteristics of the TMS rotary tables

TMS rotary tables are directly driven rotary tables and do not therefore have a gearbox. The extremely rigid connection between the motor and load, coupled with a high-quality servo drive controller, ensures outstanding acceleration capabilities and movement with good uniformity. Due to the hollow shaft design, TMS rotary tables are especially well suited to automation tasks. Media, cable systems or mechanisms can pass through with ease.

Key features:

- Backlash-free and extremely dynamic
- Brush-less and high-torque
- Integrated optical rotary encoder
- With pneumatic clamping as an option
- IP65 as an option
- Flange version as an option
- Absolute positioning measurement system as an option (EnDat 2.2, Siemens DRIVE-CLiQ, Sick HIPERFACE, Fanuc or Mitsubishi interface)



Typical applications:

- Automation technology
- Pick-and-place machines

3.2 Order code for TMS rotary tables

| TM | S | 3 | 4 | L | D | 0 | 0 | F | C |
|--|---|---|---|---|---|---|---|---|------------------------------------|
| Torque motor | | | | | | | | | Special equipment: |
| Type: | | | | | | | | | O: None C: Customer specific |
| S: Rotary table complete with crossed roller bearing | | | | | | | | | F: Flange version ¹⁾ |
| Outer diameter [mm]: | | | | | | | | | Protection class ¹⁾ : |
| 0: 110 | | | | | | | | | O: IP40 |
| 1: 150 | | | | | | | | | 1: IP65 |
| 3: 200 | | | | | | | | | Clamping element ¹⁾ : |
| 7: 300 | | | | | | | | | O: None P: Pneumatic |
| Rotor height [mm]: | | | | | | | | | Positioning measurement system: |
| 2: 20 | | | | | | | | | C: Optical, absolute (EnDat) |
| 3: 30 | | | | | | | | | D: Optical, incremental (TMS0/1/3) |
| 4: 40 | | | | | | | | | A: Optical, incremental (TMS7) |
| 6: 60 | | | | | | | | | Winding variant ¹⁾ : |
| 7: 70 | | | | | | | | | None: standard winding |
| 8: 80 | | | | | | | | | L: For high rotary speed |
| C: 120 | | | | | | | | | |

¹⁾ Options depend on the series; see technical data

Rotary Tables

HIWIN rotary tables TMS

3.3 Technical data for TMS

3.3.1 Technical data for TMS0

Torque-speed curves (DC bus voltage: 560 VDC)




Table 3.1 Technical data for TMS0 HIWIN rotary tables

| | Symbol | Unit | TMS03 | TMS07 |
|---|-----------------|---------------------------------|-----------------------|-------|
| Technical data of rotary table | | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 9.3 | 18.6 |
| Continuous torque | T_c | Nm | 3.1 | 6.2 |
| Stall torque | T_s | Nm | 2.17 | 4.34 |
| Inertia of rotating parts | J | kgm^2 | 0.003 | 0.006 |
| Weight | M_m | kg | 4 | 7 |
| Max. axial load | F_a | N | 3,700 | |
| Max. radial load | F_r | N | 820 | |
| Max. moment of tilt | M_k | Nm | 40 | |
| Nominal speed (at 400 VAC, 30 % duty cycle) | n | 1/min | 700 | |
| Position accuracy | | arc sec | $\pm 45/\pm 10^{21}$ | |
| Repeating accuracy | | arc sec | ± 3 | |
| Radial run-out | | mm | 0.03 (optional 0.015) | |
| Axial run-out | | mm | 0.03 (optional 0.005) | |
| Height | H | mm | 117.5 | 150 |
| Protection class | | | IP40 | |
| Technical data of motor | | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 6.0 | |
| Continuous current | I_c | A_{eff} | 2.0 | |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 0.5 | 0.8 |
| Resistance ¹⁾ | R_{25} | Ω | 7.1 | 11.1 |
| Inductance ¹⁾ | L | mH | 15.2 | 22.2 |
| Electrical time constant | T_e | ms | 2.1 | 2.0 |
| Torque constant | K_t | Nm/A_{eff} | 1.55 | 3.10 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 0.82 | 1.70 |
| Number of poles | 2p | | 10 | |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 1.76 | 1.13 |
| Thermal time constant | T_{th} | s | 1,930 | 1,980 |
| Thermal sensor | | | PTC SNM 100 | |
| Max. DC Bus | | V | 600 | |




All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature

¹⁾ Line-to-line

²⁾ With error mapping

Encoder type D specifications (optical, incremental)

- 5,026 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{pp}

Dimensions of the TMS0 HIWIN rotary table(For values, see [Table 3.1](#))

X View

Rotary Tables

HIWIN rotary tables TMS

3.3.2 Technical data for TMS1

Torque-speed curves (DC bus voltage: 560 VDC)




Table 3.2 Technical data for TMS1 HIWIN rotary tables

| | Symbol | Unit | TMS12 | TMS14 | TMS16 | TMS18 |
|---|----------|---------------------------------|-----------------------|--------|-------|--------|
| Technical data of rotary table | | | | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 15 | 30 | 45 | 60 |
| Continuous torque | T_c | Nm | 5 | 10 | 15 | 20 |
| Stall torque | T_s | Nm | 3.5 | 7 | 10.5 | 14 |
| Inertia of rotating parts | J | kgm^2 | 0.006 | 0.0065 | 0.007 | 0.0075 |
| Weight | M_m | kg | 5.7 | 7 | 8.3 | 9.5 |
| Max. axial load | F_a | N | 3,700 | | | |
| Max. radial load | F_r | N | 1,700 | | | |
| Max. moment of tilt | M_k | Nm | 60 | | | |
| Nominal speed (at 400 VAC, 30 % duty cycle) | n | 1/min | 600 | | 500 | |
| Position accuracy | | arc sec | $\pm 45/\pm 10^{2j}$ | | | |
| Repeating accuracy | | arc sec | ± 3 | | | |
| Radial run-out | | mm | 0.03 (optional 0.015) | | | |
| Axial run-out | | mm | 0.03 (optional 0.005) | | | |
| Height | H | mm | 100 | 120 | 140 | 160 |
| Protection class | | | IP40 | | | |
| Technical data of motor | | | | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 12 | | | |
| Continuous current | I_c | A_{eff} | 4 | | | |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 0.6 | 1.0 | 1.3 | 1.6 |
| Resistance ¹⁾ | R_{25} | Ω | 2.6 | 3.9 | 5.2 | 6.5 |
| Inductance ¹⁾ | L | mH | 8.2 | 14.0 | 20.0 | 26.0 |
| Electrical time constant | T_e | ms | 3.2 | 3.6 | 3.8 | 4.0 |
| Torque constant | K_t | Nm/A_{eff} | 1.25 | 2.50 | 3.75 | 5.00 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 0.6 | 1.2 | 1.8 | 2.4 |
| Number of poles | $2p$ | | 22 | | | |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 1.76 | 0.80 | 0.60 | 0.48 |
| Thermal time constant | T_{th} | s | 2,210 | 2,290 | 2,460 | 2,520 |
| Thermal sensor | | | PTC SNM 100 | | | |
| Max. DC Bus | | V | 600 | | | |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature


¹⁾ Line-to-line

²⁾ With error mapping

Encoder type D specifications (optical, incremental)

- 7,226 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{pp}

Dimensions of the TMS1 HIWIN rotary table

 (For values, see [Table 3.2](#))


Rotary Tables

HIWIN rotary tables TMS

3.3.3 Technical data for TMS3

Torque-speed curves (DC bus voltage: 560 VDC)




Table 3.3 Technical data for HIWIN rotary tables TMS3

| | Symbol | Unit | TMS32 | TMS34 | TMS34L | TMS38 | TMS38L | TMS3C | TMS3CL | |
|---|----------|---------------------------------|----------------------|----------------------|--------|-------|--------|-------|--------|--|
| Technical data of rotary table | | | | | | | | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 30 | 60 | | 120 | | 180 | | |
| Continuous torque | T_c | Nm | 10 | 20 | | 40 | | 60 | | |
| Stall torque | T_s | Nm | 7 | 14 | | 28 | | 42 | | |
| Inertia of rotating parts | J | kgm^2 | 0.014 | 0.020 | | 0.026 | | 0.035 | | |
| Weight | M_m | kg | 15 | 21 | | 26 | | 32 | | |
| Max. axial load | F_a | N | 8,000 | | | | | | | |
| Max. radial load | F_r | N | 6,500 | | | | | | | |
| Max. moment of tilt | M_k | Nm | 240 | | | | | | | |
| Nominal speed (at 400 VAC, 30 % duty cycle) | n | 1/min | 700 | 700 | 700 | 450 | 700 | 300 | 600 | |
| Position accuracy | | arc sec | $\pm 25/\pm 10^{2)}$ | | | | | | | |
| Repeating accuracy | | arc sec | ± 2.5 | | | | | | | |
| Radial run-out | | mm | 0.05 | | | | | | | |
| Axial run-out | | mm | 0.05 (optional 0,01) | | | | | | | |
| Height | H | mm | 130 | 150 | | 190 | | 230 | | |
| Protection class | | | IP40 | IP40 (optional IP65) | | | | | | |
| Technical data of motor | | | | | | | | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 10.2 | 10.2 | 20.4 | 10.2 | 20.4 | 10.2 | 20.4 | |
| Continuous current | I_c | A_{eff} | 3.4 | 3.4 | 6.8 | 3.4 | 6.8 | 3.4 | 6.8 | |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 1.1 | 1.8 | | 2.8 | | 3.6 | 3.5 | |
| Resistance ¹⁾ | R_{25} | Ω | 5 | 7.5 | 1.9 | 12 | 3 | 17.1 | 4.3 | |
| Inductance ¹⁾ | L | mH | 20.6 | 34.60 | 8.7 | 53.6 | 16.3 | 84.4 | 25.3 | |
| Electrical time constant | T_e | ms | 4.1 | 4.6 | 4.6 | 4.5 | 5.4 | 4.9 | 5.9 | |
| Torque constant | K_t | Nm/A_{eff} | 3 | 6 | 3 | 12 | 6 | 18 | 9 | |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 1.5 | 3 | 1.5 | 6 | 3 | 9 | 4.5 | |
| Number of poles | $2p$ | | 22 | | | | | | | |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 1.1 | 0.73 | | 0.46 | | 0.32 | | |
| Thermal time constant | T_{th} | s | 1,980 | 2,020 | | 2,130 | | 2,170 | | |
| Thermal sensor | | | PTC SNM 120 | | | | | | | |
| Max. DC Bus | | V | 600 | | | | | | | |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature

¹⁾ Line-to-line

²⁾ With error mapping

Encoder specifications

Type D: optical, incremental (standard)

- 7,226 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{PP}

Type C: optical, absolute (optional)

- EnDat
- Motor hollow shaft diameter: 40 mm

Specifications for pneumatic clamping element (optional)

- Clamping torque 110 Nm at 6 bar
- Clamping torque with additional air: 200 Nm at 6 bar
- Suitable for emergency stop due to spring preload

Options


- Clamping element
- Flange version
- IP65 (except for TMS32)
- Absolute positioning measurement system (except for TMS32)

Rotary Tables

HIWIN rotary tables TMS


Dimensions of the TMS3 HIWIN rotary table

(For values, see [Table 3.3](#))



Dimensions of the TMS3 HIWIN rotary table (version with clamping element)

(For values, see [Table 3.3](#))



Rotary Tables

HIWIN rotary tables TMS

3.3.4 Technical data for TMS7

Torque-speed curves (DC bus voltage: 560 VDC)




Table 3.4 Technical data for TMS7 HIWIN rotary tables

| | Symbol | Unit | TMS74 | TMS74L | TMS76 | TMS76L | TMS7C | TMS7CL | | | | |
|---|----------|---------------------------------|----------------------|--------|-------|--------|-------|--------|--|--|--|--|
| Technical data of rotary table | | | | | | | | | | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 150 | | 225 | | 450 | | | | | |
| Continuous torque | T_c | Nm | 50 | | 75 | | 150 | | | | | |
| Stall torque | T_s | Nm | 35 | | 52.5 | | 105 | | | | | |
| Inertia of rotating parts | J | kgm^2 | 0.152 | | 0.174 | | 0.241 | | | | | |
| Weight | M_m | kg | 39 | | 44.5 | | 61.5 | | | | | |
| Max. axial load | F_a | N | 8,000 | | | | | | | | | |
| Max. radial load | F_r | N | 6,500 | | | | | | | | | |
| Max. moment of tilt | M_k | Nm | 360 | | | | | | | | | |
| Nominal speed (at 400 VAC, 30 % duty cycle) | n | 1/min | 290 | 500 | 190 | 400 | 80 | 190 | | | | |
| Position accuracy | | arc sec | $\pm 25/\pm 10^{2)}$ | | | | | | | | | |
| Repeating accuracy | | arc sec | ± 2.5 | | | | | | | | | |
| Radial run-out | | mm | 0.05 | | | | | | | | | |
| Axial run-out | | mm | 0.05 (optional 0.01) | | | | | | | | | |
| Height | H | mm | 160 | | 180 | | 240 | | | | | |
| Protection class | | | IP40 (optional IP65) | | | | | | | | | |
| Technical data of motor | | | | | | | | | | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 10.2 | 20.4 | 10.2 | 20.4 | 10.2 | 20.4 | | | | |
| Continuous current | I_c | A_{eff} | 3.4 | 6.8 | 3.4 | 6.8 | 3.4 | 6.8 | | | | |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 3.9 | 3.9 | 5.1 | 5.0 | 7.7 | 7.7 | | | | |
| Resistance ¹⁾ | R_{25} | Ω | 12.9 | 3.2 | 17 | 4.3 | 29 | 7.3 | | | | |
| Inductance ¹⁾ | L | mH | 55 | 13.8 | 76 | 19 | 145 | 36.3 | | | | |
| Electrical time constant | T_e | ms | 4.3 | 4.3 | 4.5 | 4.4 | 5.0 | 5.0 | | | | |
| Torque constant | K_t | Nm/A_{eff} | 17 | 8.5 | 25.6 | 12.8 | 51.1 | 25.5 | | | | |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 9.8 | 4.9 | 14.8 | 7.4 | 29.5 | 14.8 | | | | |
| Number of poles | $2p$ | | 44 | | | | | | | | | |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 0.42 | | 0.32 | | 0.19 | | | | | |
| Thermal time constant | T_{th} | s | 2,230 | | 2,330 | | 2,350 | | | | | |
| Thermal sensor | | | PTC SNM 120 | | | | | | | | | |
| Max. DC Bus | | V | 600 | | | | | | | | | |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature

¹⁾ Line-to-line

²⁾ With error mapping

Encoder specifications

Type A: optical, incremental (standard)

- 5,400 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{pp}

Type C: optical, absolute (optional)

- EnDat
- Motor hollow shaft diameter: 40 mm

Specifications for pneumatic clamping element (optional)

- Clamping torque 330 Nm at 6 bar
- Clamping torque with additional air: 580 Nm at 6 bar
- Suitable for emergency stop due to spring preload

Options


- Clamping element
- Flange version
- IP65
- Absolute positioning measurement system

Rotary Tables


HIWIN rotary tables TMS

Dimensions of the TMS7 HIWIN rotary table

(For values, see [Table 3.4](#))



Dimensions of the TMS7 HIWIN rotary table (version with clamping element)

(For values, see [Table 3.4](#))

Rotary Tables

HIWIN rotary tables TMB

4. HIWIN rotary tables TMB

4.1 Characteristics of the TMB rotary tables

Thanks to the compact design and low weight, the TMB rotary tables can be used as rotary axes in many different ways and with little construction work.

Two heights provide the optimum solution for torques of between 4.2 and 6.4 Nm.

Since no gearbox is needed, there is virtually no noise during operation and no backlash.

The cable connections are integrated in the housing to save space. The hollow shaft allows cables and other media to pass through with ease.




Key features:

- Backlash-free and extremely dynamic
- Compact design
- Hollow shaft, 12 mm in diameter
- 65 mm outer diameter
- Integrated optical rotary encoder
- Very low running noise

Typical applications:

- Automation technology
- Pick-and-place machines

4.2 Order code for TMB rotary tables



4.3 Technical data for TMB0

Torque-speed curves (DC bus voltage: TMB02N: 48 VDC; TMB02H: 320 VDC; TMB06H: 320 VDC)




Table 4.1 Technical data for TMB0 HIWIN rotary tables

| | Symbol | Unit | TMB02N-A00 | TMB02H-A00 | TMB06H-A00 |
|---------------------------------------|-----------------|---------------------------------|----------------------|------------|----------------------|
| Technical data of rotary table | | | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 3.0 | 2.56 | 6.4 |
| Continuous torque | T_c | Nm | 0.9 | 0.59 | 1.4 |
| Stall torque | T_s | Nm | 0.5 | 0.42 | 1 |
| Inertia of rotating parts | J | kgm^2 | 3.5×10^{-5} | | 9.5×10^{-5} |
| Weight | M_m | g | 650 | 960 | 1,270 |
| Max. axial load | F_a | N | 150 | | |
| Max. radial load | F_r | N | 150 | | |
| Max. moment of tilt | M_k | Nm | 4 | | |
| Nominal speed (30 % duty cycle) | n | 1/min | 650 | 450 | 420 |
| Position accuracy | | arc sec | 150 | | |
| Repeating accuracy | | arc sec | 6 | | |
| Radial run-out | | mm | 0.05 | | |
| Axial run-out | | mm | 0.05 | | |
| Height | H | mm | 72.6 | | 115 |
| Protection class | | | IP40 | | |
| Technical data of motor | | | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 23.1 | 5.5 | 9.7 |
| Continuous current | I_c | A_{eff} | 6.9 | 1.26 | 2.0 |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 0.11 | 0.10 | 0.2 |
| Resistance ¹⁾ | R_{25} | Ω | 1.4 | 20.1 | 10.6 |
| Inductance ¹⁾ | L | mH | 0.88 | 11.3 | 9.9 |
| Electrical time constant | T_e | ms | 0.63 | 0.56 | 0.93 |
| Torque constant | K_t | Nm/A_{eff} | 0.13 | 0.46 | 0.66 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 0.13 | 0.46 | 0.66 |
| Number of poles | $2p$ | | 12 | | |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 3.3 | | 2.5 |
| Thermal sensor | | | PTC SNM 125 | | |
| Max. DC Bus | | V | 48 | 340 | |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25 °C ambient temperature

¹⁾ Line-to-line

Encoder specifications type A (optical, incremental)


- 2,048 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{PP}

Rotary Tables

HIWIN rotary tables TMB, HIWIN rotary tables TMN

Dimensions of the TMB0 HIWIN rotary table

(For values, see [Table 4.1](#))



X View

5. HIWIN rotary tables TMN

5.1 Characteristics of the TMN rotary tables

The particularly flat and light precision rotary tables of the TMN series are suited to all applications in which high rigidity and accuracy are needed along with the smallest dimensions possible. Typical areas of use include the manufacture of LEDs, solar cells and semiconductors. The zero-maintenance TMN rotary tables use precision bearings and optical encoders to achieve very high positioning and repeat accuracy.




Key features:

- Backlash-free and extremely dynamic
- Extremely flat design
- Integrated rotary encoder

Typical applications:

- LED manufacture and testing
- Production of solar cells
- Manufacture of semiconductor components

5.2 Order code for TMN rotary tables



Rotary Tables

HIWIN rotary tables TMN

5.3 Technical data for TMN

5.3.1 Technical data for TMN42

Torque-speed curves (DC bus voltage: 320/560 VDC)




Table 5.1 Technical data for TMN42 HIWIN rotary tables

| | Symbol | Unit | TMN42 |
|---------------------------------------|-----------------|---------------------------------|-------------|
| Technical data of rotary table | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 4.2 |
| Continuous torque | T_c | Nm | 1.4 |
| Stall torque | T_s | Nm | 0.98 |
| Inertia of rotating parts | J | kgm^2 | 0.003 |
| Weight | M_m | kg | 2 |
| Max. axial load | F_a | N | 600 |
| Max. radial load | F_r | N | 600 |
| Max. moment of tilt | M_k | Nm | 30 |
| Nominal speed (at 400 VAC) | n | 1/min | 700 |
| Position accuracy | | arc sec | ± 45 |
| Repeating accuracy | | arc sec | ± 2.5 |
| Radial run-out | | mm | 0.03 |
| Axial run-out | | mm | 0.03 |
| Height | H | mm | 45 |
| Protection class | | | IP40 |
| Technical data of motor | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 4.5 |
| Continuous current | I_c | A_{eff} | 1.5 |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 0.4 |
| Resistance ¹⁾ | R_{25} | Ω | 4.59 |
| Inductance ¹⁾ | L | mH | 8.18 |
| Electrical time constant | T_e | ms | 1.78 |
| Torque constant | K_t | Nm/A_{eff} | 0.97 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 0.56 |
| Number of poles | 2p | | 16 |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 4.84 |
| Thermal time constant | T_{th} | s | 1,170 |
| Thermal sensor | | | PTC SNM 100 |
| Max. DC Bus | | V | 600 |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature



¹⁾ Line-to-line

Encoder specifications (optical, incremental)

- 2,048 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{pp}

Dimensions of the TMN42 HIWIN rotary table

(For values, see [Table 5.1](#))



Rotary Tables

HIWIN rotary tables TMN

5.3.2 Technical data for TMN71

Torque-speed curves (DC bus voltage: 320/560 VDC)




Table 5.2 Technical data for TMN71 HIWIN rotary tables

| | Symbol | Unit | TMN71 |
|---------------------------------------|-----------------|---------------------------------|-------------|
| Technical data of rotary table | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 11.1 |
| Continuous torque | T_c | Nm | 3.7 |
| Stall torque | T_s | Nm | 2.59 |
| Inertia of rotating parts | J | kgm^2 | 0.008 |
| Weight | M_m | kg | 3.5 |
| Max. axial load | F_a | N | 1,000 |
| Max. radial load | F_r | N | 1,000 |
| Max. moment of tilt | M_k | Nm | 50 |
| Nominal speed (at 400 VAC) | n | 1/min | 600 |
| Position accuracy | | arc sec | ± 45 |
| Repeating accuracy | | arc sec | ± 2.5 |
| Radial run-out | | mm | 0.03 |
| Axial run-out | | mm | 0.03 |
| Height | H | mm | 50 |
| Protection class | | | IP40 |
| Technical data of motor | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 10.2 |
| Continuous current | I_c | A_{eff} | 3.4 |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 0.6 |
| Resistance ¹⁾ | R_{25} | Ω | 2.22 |
| Inductance ¹⁾ | L | mH | 9.02 |
| Electrical time constant | T_e | ms | 4.1 |
| Torque constant | K_t | Nm/A_{eff} | 1.09 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 0.63 |
| Number of poles | $2p$ | | 16 |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 1.95 |
| Thermal time constant | T_{th} | s | 1,420 |
| Thermal sensor | | | PTC SNM 100 |
| Max. DC Bus | | V | 600 |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature


¹⁾ Line-to-line

Encoder specifications (optical, incremental)

- 2,048 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{PP}

Dimensions of the TMN71 HIWIN rotary table

(For values, see [Table 5.2](#))



Rotary Tables

HIWIN rotary tables TMN

5.3.3 Technical data for TMN93

Torque-speed curves (DC bus voltage: 320/560 VDC)




Table 5.3 Technical data for TMN93 HIWIN rotary tables

| | Symbol | Unit | TMN93 |
|---------------------------------------|-----------------|---------------------------------|-------------|
| Technical data of rotary table | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 39.6 |
| Continuous torque | T_c | Nm | 13.2 |
| Stall torque | T_s | Nm | 9.24 |
| Inertia of rotating parts | J | kgm^2 | 0.012 |
| Weight | M_m | kg | 7.5 |
| Max. axial load | F_a | N | 1,000 |
| Max. radial load | F_r | N | 1,000 |
| Max. moment of tilt | M_k | Nm | 50 |
| Nominal speed (at 400 VAC) | n | 1/min | 500 |
| Position accuracy | | arc sec | ± 45 |
| Repeating accuracy | | arc sec | ± 2.5 |
| Radial run-out | | mm | 0.03 |
| Axial run-out | | mm | 0.03 |
| Height | H | mm | 55 |
| Protection class | | | IP40 |
| Technical data of motor | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 10.2 |
| Continuous current | I_c | A_{eff} | 3.4 |
| Motor constant | K_m | $\text{Nm}/\sqrt{\text{W}}$ | 1.5 |
| Resistance ¹⁾ | R_{25} | Ω | 4.3 |
| Inductance ¹⁾ | L | mH | 23.2 |
| Electrical time constant | T_e | ms | 5.4 |
| Torque constant | K_t | Nm/A_{eff} | 3.9 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 2.25 |
| Number of poles | $2p$ | | 22 |
| Thermal resistance | R_{th} | $^{\circ}\text{C}/\text{W}$ | 1.01 |
| Thermal time constant | T_{th} | s | 1,780 |
| Thermal sensor | | | PTC SNM 100 |
| Max. DC Bus | | V | 600 |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature


¹⁾ Line-to-line

Encoder specifications (optical, incremental)

- 3,600 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{PP}

Dimensions of the TMN93 HIWIN rotary table

(For values, see [Table 5.3](#))



Rotary Tables

HIWIN rotary tables TMA

6. HIWIN rotary tables TMA

6.1 Characteristics of the TMA rotary tables

The rotary tables of the TMA series with air bearings were developed especially for applications with high synchronism and precision. The running tolerances have been reduced to a minimum.

The rotary table thereby achieves a positioning accuracy of 20 arcsec and a repeat accuracy of 2 arcsec.




Key features:

- Backlash-free and extremely dynamic
- Air bearings
- High accuracy and high synchronism
- Integrated optical rotary encoder

Typical applications:

- Measuring technology
- Test machines

6.2 Order code for TMA rotary tables



6.3 Technical data for TMA32

Torque-speed curve (DC bus voltage: 560 VDC)




Table 6.1 Technical data for TMA32 HIWIN rotary tables

| | Symbol | Unit | TMA32 |
|---------------------------------------|-----------------|---------------------------------|-------------|
| Technical data of rotary table | | | |
| Peak torque (for 1 sec.) | T_p | Nm | 27 |
| Continuous torque | T_c | Nm | 11 |
| Stall torque | T_s | Nm | 8 |
| Inertia of rotating parts | J | kgm^2 | 0.019 |
| Weight | M_m | kg | 16 |
| Max. axial load | F_a | N | 2,500 |
| Max. radial load | F_r | N | 2,500 |
| Max. moment of tilt | M_k | Nm | 70 |
| Rigidity of axial bearing | | N/ μm | 350 |
| Rigidity of radial bearing | | N/ μm | 125 |
| Resistance to tilting | | Nm/ μrad | 0.58 |
| Nominal speed (at 400 VAC) | n | 1/min | 1,000 |
| Position accuracy | | arc sec | ± 20 |
| Repeating accuracy | | arc sec | ± 2 |
| Radial run-out | | mm | 0.002 |
| Axial run-out | | mm | 0.002 |
| Operating pressure | | bar | 5 |
| Air consumption | v_n | Nl/min | 18 |
| Height | H | mm | 140 |
| Protection class | | | IP40 |
| Technical data of motor | | | |
| Peak current (for 1 sec.) | I_p | A_{eff} | 8 |
| Continuous current | I_c | A_{eff} | 3.0 |
| Motor constant | K_m | Nm/ $\sqrt{\text{W}}$ | 1.0 |
| Resistance ¹⁾ | R_{25} | Ω | 2.9 |
| Inductance ¹⁾ | L | mH | 10.0 |
| Electrical time constant | T_e | ms | 3.9 |
| Torque constant | K_t | Nm/ A_{eff} | 3.5 |
| Back emf constant | K_u | $V_{\text{eff}}/(\text{rad/s})$ | 1.6 |
| Number of poles | $2p$ | | 22 |
| Thermal resistance | R_{th} | $^{\circ}\text{C/W}$ | 0.7 |
| Thermal sensor | | | PTC SNM 100 |
| Max. DC Bus | | V | 600 |

All the specifications in the table (except dimensions) are in $\pm 10\%$ of tolerance at 25°C ambient temperature

¹⁾ Line-to-line

Encoder specifications (optical, incremental)


- 9,000 lines/cycle
- Index mark
- Signal output sin/cos 1 V_{pp}

Rotary Tables

HIWIN rotary tables TMA

Dimensions of the TMA32 HIWIN rotary table

(For values, see [Table 6.1](#))





Linear Guideways



Ballscrews



Linear Motor Systems



Linear Axes



Linear Actuators



Robots



Linear Motor Components



Rotary Tables



Drives & Servo Motors

Germany
HIWIN GmbH
Brücklesbünd 2
D-77654 Offenburg
Phone +49 (0) 7 81 9 32 78-0
Fax +49 (0) 7 81 9 32 78-90
info@hiwin.de
www.hiwin.de

Taiwan
Headquarters
HIWIN Technologies Corp.
No. 7, Jingke Road
Taichung Precision Machinery Park
Taichung 40852, Taiwan
Phone +886-4-2359-4510
Fax +886-4-2359-4420
business@hiwin.tw
www.hiwin.tw

Taiwan
Headquarters
HIWIN Mikrosystem Corp.
No. 6, Jingke Central Road
Taichung Precision Machinery Park
Taichung 40852, Taiwan
Phone +886-4-2355-0110
Fax +886-4-2355-0123
business@hiwinmikro.tw
www.hiwinmikro.tw

France
HIWIN France s.a.r.l.
20 Rue du Vieux Bourg
F-61370 Echauffour
Phone +33 (2) 33 34 11 15
Fax +33 (2) 33 34 73 79
info@hiwin.fr
www.hiwin.fr

Italy
HIWIN Srl
Via Pitagora 4
I-20861 Brugherio (MB)
Phone +39 039 287 61 68
Fax +39 039 287 43 73
info@hiwin.it
www.hiwin.it

Poland
HIWIN GmbH
ul. Putawska 405a
PL-02-801 Warszawa
Phone +48 22 544 07 07
Fax +48 22 544 07 08
info@hiwin.pl
www.hiwin.pl

Switzerland
HIWIN Schweiz GmbH
Eichwiesstrasse 20
CH-8645 Jona
Phone +41 (0) 55 225 00 25
Fax +41 (0) 55 225 00 20
info@hiwin.ch
www.hiwin.ch

Slovakia
HIWIN s.r.o., o.z.z.o.
Mládežnická 2101
SK-01701 Považská Bystrica
Phone +421 424 43 47 77
Fax +421 424 26 23 06
info@hiwin.sk
www.hiwin.sk

Czech Republic
HIWIN s.r.o.
Medkova 88/11
CZ-62700 BRNO
Phone +42 05 48 528 238
Fax +42 05 48 220 223
info@hiwin.cz
www.hiwin.cz

Netherlands
HIWIN GmbH
info@hiwin.nl
www.hiwin.nl

Austria
HIWIN GmbH
info@hiwin.at
www.hiwin.at

Slovenia
HIWIN GmbH
info@hiwin.si
www.hiwin.si

Hungary
HIWIN GmbH
info@hiwin.hu
www.hiwin.hu

China
HIWIN Corp.
www.hiwin.cn

Japan
HIWIN Corp.
mail@hiwin.co.jp
www.hiwin.co.jp

USA
HIWIN Corp.
info@hiwin.com
www.hiwin.com

Korea
HIWIN Corp.
www.hiwin.kr

Singapore
HIWIN Corp.
www.hiwin.sg