


INTELLIGENCE IN MOTION

LINEAR GUIDEWAYS

HIWIN[®]
Motion Control & Systems



01

WWW.HIWIN.CZ

LINEAR GUIDEWAYS

Product overview

4/5

General information

6/24

HG/QH series

25/43

EG/QE series

44/59

CG series

60/73

WE/QW series

74/86

MG series

87/99

RG/QR series

100/117

PG series

118/125

Accessories

126/131

01


Contents

- 1. Product overview
- 2. General information
 - 2.1 Properties and advantages
 - 2.2 Selection principles
 - 2.3 Load ratings
 - 2.4 Lifetime calculation
 - 2.5 Operating load
 - 2.6 Friction and lubrication
 - 2.7 Mounting position
 - 2.8 Assembly
 - 2.9 Sealing systems
 - 2.10 SynchMotion™ technology
 - 2.11 HIWIN coating
- 3. Linear guideway
 - 3.1 Series HG and QH
 - 3.2 Series EG and QE
 - 3.3 Series CG
 - 3.4 Series WE and QW
 - 3.5 Series MG
 - 3.6 Series RG and QR
 - 3.7 Series PG
- 4. Accessories
 - 4.1 Lubrication adapters
 - 4.2 HIWIN grease guns and lubricants

Linear Guideways

Product overview


1. Product overview



Linear guideway, series HG and QH

[Chapter 3.1](#)


- 4-row recirculation ball bearing guide
- 45° contact angle
- High loading capacity in all mounting positions
- High rigidity
- Block with SynchMotion™ technology (QH series)



Linear guideway, series EG and QE

[Chapter 3.2](#)


- 4-row recirculation ball bearing guide
- 45° contact angle
- High loading capacity in all mounting positions
- Low installation height
- Block with SynchMotion™ technology (QE series)



Linear guideway, series CG

[Chapter 3.3](#)


- 4-row recirculation ball bearing guide
- 0-arrangement with 45° contact angle
- High torque loading capacity, especially rolling moment capacity
- Optional: rail with cover strip



Linear guideway, series WE and QW

[Chapter 3.4](#)

- 4-row recirculating ball bearing guide
- 45° contact angle
- High torque loading capacity
- Low installation height
- Block with SynchMotion™ technology (QW series)




Linear guideway, series MG

[Chapter 3.5](#)

- 2-row recirculating ball bearing guide
- 45° contact angle
- Compact construction
- Narrow and wide designs

Linear Guideways


Product overview



Linear guideway, series RG and QR

[Chapter 3.6](#)

- 4-row recirculation ball bearing guide
- 45° contact angle
- Roller guide
- Very high loading capacity
- Very high rigidity
- Block with SynchMotion™ technology (QR series)



Linear guideway, series PG

[Chapter 3.7](#)

- HG series with integrated positioning measurement system
- Zero contact distance measurement
- Simple attachment and assembly
- Signal output in real time

Accessories

[Chapter 4](#)

- Grease nipple
- Lubrication adapter
- Push-in fittings

Linear Guideways

General information

2. General information

2.1 Properties and advantages

1. High positioning accuracy

A carriage mounted with a linear guideway only has to overcome rolling friction. The difference between the static and dynamic rolling friction is very small so the break-away force is only slightly greater than the motion force. Stick-slip effects are not experienced.

2. Long lifetime and highly precise movement

With a sliding guide, the different thicknesses of lubrication film may result in accuracy errors. The sliding friction and the fact that lubrication is often insufficient cause a lot of wear and therefore decreasing accuracy. Contrasted with this, the linear guideway has very low rolling friction, coupled with extremely low wear. Guidance accuracy remains virtually constant over the entire lifetime.

3. High speed and low driving force

The low friction coefficients mean that only low driving forces are needed. The required power also remains low when reversing.

4. Same high load capacity in all directions

Thanks to the enforced guidance inherent in its design, a linear guideway can absorb forces in a vertical and horizontal direction.

5. Simple installation and interchangeability

Assembling a linear guideway is a simple process. A high level of accuracy is achieved with a milled or ground mounting surface if the assembly instructions are followed. Standard sliding guides require considerably more effort to assemble as the sliding surfaces have to be scraped. Individual components cannot be interchanged without scraping. Linear guideways can however be interchanged with very little effort.

6. Simple lubrication

Insufficient lubrication on sliding guides destroys the sliding surfaces. Lubricant must be used at a large number of points on the sliding surfaces. The linear guideway only requires minimal lubrication which is provided by a simple supply line to the block. HIWIN can also supply blocks with an integrated oil lubrication unit and interchangeable oil tank for long-term lubrication.

7. Corrosion protection

To achieve optimum corrosion protection, blocks and rails can be supplied with different coatings. The individual procedures selected depend on the application. Data relating to the ambient conditions and corrosive substances is needed for an optimum choice of coating. The miniature linear guideways MG and PM are produced in stainless steel.

Linear Guideways

General information

2.2 Selection principles

Establish the selection conditions

- Machine base
- Max. installation space
- Desired accuracy
- Rigidity required
- Type of loading
- Travel distance
- Speed of travel, acceleration
- Frequency of use
- Lifetime
- Ambient conditions

Select the series

- HG and CG series – Grinding, milling and drilling machines, lathes, machining centres, woodworking
- EG series – Automation technology, high-speed transport, semiconductor equipment, precision measuring equipment
- WE series – Single axes with high torque loads M_x
- MG series – Miniature technology, semiconductor equipment, medical technology
- RG series – Machining centres, injection moulding machines, machines and systems with high rigidity

Select the accuracy class

- Classes C, H, P, SP, UP depending on the accuracy required

Define the size and number of blocks

- Depending on empirical values
- Depending on type of loading
- If a ballscrew is used, the nominal size of the linear guideways and the ballscrew should be roughly the same, e.g. 32 ballscrew and 35 rail

Calculate the maximum load of the blocks

- Calculate the maximum load using the sample calculations (see Section 2.5). Ensure that the static structural safety of the selected linear guideway is higher than the corresponding value in the table on static structural safety.

Determine the preload

- The preload depends on the rigidity requirements and the accuracy of the mounting surface.

Determine the rigidity

- Use the rigidity table to calculate the deformation (δ) the rigidity increases with preload and as the guide increases in size.

Calculate the lifetime

- Establish the lifetime needed taking account of the speed and frequency of travel; base work on sample calculations (see Section 2.4).

Select the type of lubrication

- Grease via grease nipple
- Oil via connection line

Selection complete

Linear Guideways

General information

2.3 Load ratings


2.3.1 Static load rating C_0

If a linear guideway is subject to disproportionately high loads or impact during movement or when stationary, local permanent deformation occurs between the block and balls. Once this permanent deformation exceeds a particular level, it impacts on how easily the guide moves. By definition, the static load rating corresponds to a static

load which causes a permanent deformation of $0.0001 \times$ ball diameter at the point of contact subject to the most loading. The values are stated in the tables for each linear guideway. These tables can be used to select a suitable linear guideway. The maximum static load to which a linear guideway is subjected must not exceed the static load rating.

2.3.2 Permissible static moment M_0

The permissible static moment is the moment that corresponds to the greatest possible loading of moving parts by the static load rating in a defined direction and magnitude. The permissible static moment is defined in three directions (MX, MY and MZ) for linear movement systems.



2.3.3 Static structural safety

Static structural safety, which depends on the ambient and operating conditions, must be taken into account for rail systems at rest or moving slowly. A higher level of structural safety is especially important for guides subject to impact loads, see [Table 2.1](#). The static structural safety can be calculated using [F 2.1](#).

F 2.1

$$f_{SL} = \frac{C_0}{P} ; f_{SM} = \frac{M_0}{M}$$

f_{SL}	Static structural safety
f_{SM}	Static safety factor for torque loading
C_0	Static load rating [N]
M_0	Permissible static moment [Nm]
P	Equivalent static working load [N]
M	Equivalent static moment [Nm]

Please note: The load-bearing capacity of the linear guideway is often limited not by its load-bearing strength, but the screw connection. We therefore recommend checking the maximum permitted load-bearing capacity of the screw connection in accordance with VDI 2230.

Table 2.1 Static structural safety

Loading	f_{SL}, f_{SM} [min.]
Normal loading	1.25 – 3.00
With impact and vibration	3.00 – 5.00

2.3.4 Dynamic load rating C_{dyn}

The dynamic load rating is the defined loading (in direction and magnitude) at which a linear guideway achieves a nominal lifetime of 50 km¹⁾ travel distance (HG, QH, EG, QE, CG, WE, QW, MG) or 100 km¹⁾ (RG). The dynamic load rating is stated for each guide in the dimension charts. This can be used to calculate the lifetime of one particular guide.

¹⁾ Note

The dynamic load rating of linear guideways is stated for a lifetime of 50 or 100 km travel distance depending on the manufacturer. The following factors can be used to convert the dynamic load rating.

$$C_{dyn} 50 \text{ km} = 1.26 \times C_{dyn} 100 \text{ km (series HG, QH, EG, QE, CG, WE, QW, MG)}$$

$$C_{dyn} 50 \text{ km} = 1.23 \times C_{dyn} 100 \text{ km (series RG)}$$

Linear Guideways

General information

2.4 Lifetime calculation

2.4.1 Definition of lifetime

Continual and repeat loading of the tracks and balls on a linear guideway causes signs of fatigue on the track surface. Ultimately this results in what is known as pitting. The lifetime of a linear guideway is defined as the total travel distance covered until pitting starts to form on the surface of the track or balls.

2.4.2 Nominal lifetime (L)

The lifetime may vary significantly even if the linear guideways are produced in the same way and used under the same movement conditions. The nominal lifetime should therefore be viewed as a rough estimate of the lifetime of a linear guideway. The nominal lifetime corresponds to the total travel distance which 90 % of a group of identical linear guideways reach under the same conditions without failure.

2.4.2.2 Nominal lifetime calculation

The actual loading affects the nominal lifetime of a linear guideway. The nominal lifetime can be calculated with Formulas [F 2.2](#) and [F 2.3](#) using the selected dynamic load rating and equivalent dynamic loading.

Formulas for calculating nominal lifetime (L)

Series HG, QH, EG, QE, WE, MG:

$$F 2.2 \quad L = \left(\frac{C_{dyn}}{P} \right)^3 \times 50 \text{ km}$$

Series RG, QR:

$$F 2.3 \quad L = \left(\frac{C_{dyn}}{P} \right)^{10/3} \times 100 \text{ km}$$


L Nominal lifetime [km]
 C_{dyn} Dynamic load rating [N]
 P Equivalent dynamic loading [N]

2.4.2.1 Factors affecting nominal lifetime

The type of loading, hardness of the track and temperature of the guide have a considerable impact on the nominal lifetime. Formulas [F 2.4](#) and [F 2.5](#) show the relationship between these factors.


Hardness factor (f_h)

The tracks of the linear guideways have a hardness of 58 HRC. A hardness factor of 1.0 applies. If the hardness differs from this, the hardness factor shown on the right should be used. If the stated hardness is not reached, the permissible loading is reduced. If this happens, the dynamic and static load ratings must be multiplied by the hardness factor.



Temperature factor (f_t)

Standard rails can be used in an ambient temperature range of -10 to 80 °C. At ambient temperatures up to 150 °C, linear guideways with a metallic end cap must be used (identified in the type code by the addition "/SE"). Intermittent ambient temperatures of up to 180 °C are possible. However, we do recommend contacting our technical support team to be sure. If the temperature of a linear guideway exceeds 100 °C, the permissible load and lifetime are reduced. The dynamic and static load ratings must therefore be multiplied by the temperature factor.



Linear Guideways

General information

Load factor (f_w)

The equivalent dynamic load is multiplied by the load factor according to [Table 2.2](#).

This takes into account the external effects on the rail's service life that are not entered directly in the calculations (e.g. vibrations, impacts, and high speed).

Table 2.2 Load factor

Type of loading	Speed of travel	f_w
No impact and vibration	up to 15 m/min	1.0 – 1.2
Normal load	15 m/min to 60 m/min	1.2 – 1.5
Little impact	60 m/min to 120 m/min	1.5 – 2.0
With impact and vibration	greater than 120 m/min	2.0 – 3.5

Formula for calculating nominal lifetime (taking factors into account)

Series HG, QH, EG, QE, CG, WE, QW, MG:

F 2.4

$$L = \left(\frac{f_h \times f_t \times C_{dyn}}{f_w \times P} \right)^3 \times 50 \text{ km}$$

L Nominal lifetime [km]
 f_h Hardness factor
 C_{dyn} Dynamic load rating [N]
 f_t Temperature factor
P Equivalent dynamic loading [N]
 f_w Load factor

Series RG, QR:

F 2.5

$$L = \left(\frac{f_h \times f_t \times C_{dyn}}{f_w \times P} \right)^{10/3} \times 100 \text{ km}$$

2.4.3 Lifetime calculation (L_h)

The speed of travel and frequency of movement are used to calculate the lifetime in hours from the nominal lifetime.

Formula for calculating lifetime (L_h)

Series HG, QH, EG, QE, CG, WE, QW, MG:

F 2.6

$$L_h = \frac{L}{v \times 60} = \frac{\left(\frac{C_{dyn}}{P} \right)^3 \times 50,000}{v \times 60}$$

L_h Lifetime [h]
L Nominal lifetime [m]
v Speed [m/min]
 C_{dyn}/P Ratio between load rating and load

Series RG, QR:

F 2.7

$$L_h = \frac{L}{v \times 60} = \frac{\left(\frac{C_{dyn}}{P} \right)^{10/3} \times 100,000}{v \times 60}$$

Linear Guideways

General information

2.5 Operating load

2.5.1 Operating load

When calculating the loads acting on a linear guideway, various factors must be taken into account, e.g. the focal point of the load, the motion force's point of entry and the mass inertia at the start and end of movement. To obtain a correct value, each parameter must be taken into account.

Load on a block

Table 2.3 Load on a block (examples of calculating load on a block)

Typical examples	Distribution of load	Load on a block
		$P_1 = \frac{W}{4} + \frac{F}{4} + \frac{F \times a}{2c} + \frac{F \times b}{2d}$ $P_2 = \frac{W}{4} + \frac{F}{4} + \frac{F \times a}{2c} + \frac{F \times b}{2d}$ $P_3 = \frac{W}{4} + \frac{F}{4} + \frac{F \times a}{2c} + \frac{F \times b}{2d}$ $P_4 = \frac{W}{4} + \frac{F}{4} + \frac{F \times a}{2c} + \frac{F \times b}{2d}$
		$P_1 = P_3 = \frac{W}{4} - \frac{F \times l}{2d}$ $P_2 = P_4 = \frac{W}{4} + \frac{F \times l}{2d}$
		$P_1 = P_2 = P_3 = P_4 = -\frac{W \times h}{2d} + \frac{F \times l}{2d}$
		$P_1 \dots P_4 = \frac{W \times h}{2c} + \frac{F \times l}{2c}$ $P_{t1} = P_{t3} = \frac{W}{4} + \frac{F}{4} + \frac{F \times k}{2d}$ $P_{t2} = P_{t4} = \frac{W}{4} + \frac{F}{4} + \frac{F \times k}{2d}$

$P_1 \dots P_4$ Load on the individual block

W Weight of load

F Motion force; other force arising

F_A Reaction force

l Distance from external force to carriage

c Rail spacing

d Block spacing

a, b, k Distance from external force to geometric center


h Distance from center of gravity to driver

Linear Guideways

General information

Load and mass inertia

Table 2.4 Load and mass inertia (examples of calculating load and mass inertia)

Consideration of acceleration and deceleration	Load on one block
	<p>○ Constant velocity</p> $P_1 \dots P_4 = \frac{W}{4}$ <p>○ Acceleration</p> $P_1 = P_3 = \frac{W}{4} + \frac{1}{2} \times \frac{W}{g} \times \frac{v_c}{t_1} \times \frac{l}{d}$ $P_2 = P_4 = \frac{W}{4} - \frac{1}{2} \times \frac{W}{g} \times \frac{v_c}{t_1} \times \frac{l}{d}$ <p>○ Deceleration</p> $P_1 = P_3 = \frac{W}{4} - \frac{1}{2} \times \frac{W}{g} \times \frac{v_c}{t_3} \times \frac{l}{d}$ $P_2 = P_4 = \frac{W}{4} + \frac{1}{2} \times \frac{W}{g} \times \frac{v_c}{t_3} \times \frac{l}{d}$

$P_1 \dots P_4$ Load on the individual block

W Weight of load

F Motion force

F_A Reaction force

g Gravitational acceleration [m/s²]

v_c Velocity [m/s]

t_1 Acceleration time [s]

t_2 Constant speed time [s]

t_3 Deceleration time [s]

c Rail spacing [m]




d Block spacing [m]

l Distance from center of gravity to carriage [m]

2.5.2 Calculation of equivalent load during changing loads

If loading of a linear guideway fluctuates greatly, an equivalent load must be used in the lifetime calculation. The equivalent load is defined as the load which causes the same wear on the bearings as the changing loads. It can be calculated using [Table 2.5](#).

Table 2.5 Examples of calculating equivalent load (P_m)

Gradual change	Steady change	Sinusoidal change
		
$P_m = \sqrt[3]{\frac{1}{L} (P_1^3 \times L_1 + P_2^3 \times L_2 + \dots + P_n^3 \times L_n)}$	$P_m = \frac{1}{3} (P_{min} + 2 \times P_{max})$	$P_m = 0.65 \times P_{max}$

P_m Equivalent load

P_n Changing load

P_{min} Minimum load

P_{max} Maximum load

L Total travel distance

L_n Travel distance under load P_n

Linear Guideways

General information

2.6 Friction and lubrication

2.6.1 Frictional resistance

Using rolling elements in the linear guideway mainly reduces friction on the roll friction of the rolling elements. This makes the friction coefficient of linear guideways very low, up to one fiftieth of that of traditional sliding guides. Generally, the friction

coefficient is around 0.004 depending on the series. If the loading is only 10 % or less of the dynamic load rating, most of the frictional resistance is caused by the wiper and grease and friction between the rolling elements. If the operating load is more than 10 % of the dynamic load rating, the load provides the majority of the frictional resistance.

F 2.8

$$F = \mu \times W + S$$

F	Frictional force [N]
S	Frictional resistance [N]
μ	Friction coefficient
W	Load [N]

2.6.2 Lubrication

Like any other roller bearing, linear guideways need a sufficient supply of lubricant. In principle, both oil and grease can be used for lubrication. The lubricant is a design element and should be taken into account when designing a machine.

Lubricants reduce wear, protect against contamination, reduce corrosion and their properties extend the service life. Dirt may build up on unprotected rails. This dirt must be removed on a regular basis.

HIWIN provides greases for various requirements:

- HIWIN G01: heavy-duty applications
- HIWIN G02: clean room and vacuum applications
- HIWIN G03: high-speed clean room and vacuum applications
- HIWIN G04: high-speed applications
- HIWIN G05: standard applications

You will find information about the HIWIN lubricants in the accessories [chapter 4](#).


You will also find details about the HIWIN lubricants and lubrication of the linear guideways in the “**HIWIN assembly instructions for linear guideways**” available from www.hiwin.cz.

2.6.3 Oil lubrication unit E2

The oil lubrication unit E2 consists of a lubricating unit between the deflection system and the end seal, and an interchangeable oil tank. The block does not need to be disassembled in order to interchange the oil tank. Lubrication passes from the oil tank via the connector to the lubricating unit which then lubricates the track of the rail.

Due to the specific design of the oil tank, the block can be assembled in any position without influencing the lubrication effect. The oil lubrication unit E2 can be used at an ambient temperature of -10°C to $+60^{\circ}\text{C}$. The replacement intervals depend greatly on the loads and the environmental conditions. Environmental influences such as high loads, vibrations and dirt shorten the replacement intervals.

The oil lubrication unit E2 is available for the HG, EG and RG series. You will find the corresponding dimensions, lubricant volumes and intervals in the chapters for the corresponding series.



- [1] Oil tank
- [2] Connector
- [3] Lubrication unit
- [4] Deflection system
- [5] End seal
- [6] Screw
- [7] Seal plug

Applications

- Machine tools
- Production machines, injection moulding machines, paper industry, textile machines, foodstuffs industry, woodworking machines
- Electronics industry, semiconductor industry, robot technology, cross tables, measurement and test machines
- Other areas, medical equipment, automation, industrial handling

Linear Guideways

General information


2.7 Mounting position

2.7.1 Examples of typical mounting positions

A linear guideway can absorb loads from above/below and right/left. The mounting position depends on the requirements of the machine and the loading direction. The precision of the rail is defined by the straightness and evenness of the installation surfaces, since the rail is attached to these while the screws are being tightened.


A profile bar on a reference edge:

The reference edge is identified by arrows on the top of the rail. For very short rails, identification is on the front side of the rail.




Profile rails that are not attached to an installation surface may have larger tolerances in terms of straightness. Below you will find typical mounting situations: Details of the assembly tolerances can be found in the chapters for the individual series.


Two rails with mobile block:




Two rails with permanently installed block:




Two external blocks:




Two internal blocks:



Setup with permanently installed surface:



HGW..C block with different mounting directions:



D Spacer

Linear Guideways


General information

2.8 Assembly

Depending on the accuracy required and the linear guideway's impact and vibration loading, the following three types of assembly are recommended.

2.8.1 Assembly of rails with reference edge and clamp

If the machine is subject to severe vibration, impact or lateral force, guides and blocks may move. To avoid this problem and achieve a high level of rigidity and guidance accuracy, we would recommend assembling the linear guideway with reference edges and clamps on both sides.




- [1] Following side
- [2] Guide clamping screw
- [3] Carriage
- [4] Block clamping screw
- [5] Reference side
- [6] Machine bed


2.8.1.1 Types of attachment

The following four types of attachment are recommended.


Attachment with a clamping plate:




Attachment with clamping screws:



Attachment with clamping strips:



Attachment with needle rollers:




Linear Guideways


General information

2.8.1.2 Assembly of the rails


- 1) Before beginning, remove all dirt from the surface of the machine




- 2) Place the rail carefully on the bed and align it with the reference edge




- 3) When aligning the rail on the bed, ensure that the thread engages with the screws used




- 4) Tighten clamping screws one after another in order to ensure good contact between the rail and the reference edge



- 5) Tighten rail mounting bolts in three stages using a torque wrench until the specified torque is reached




- 4) Assemble the second rail in the same way as the first



2.8.1.3 Assembly of the blocks

- Carefully place carriage on block. Then provisionally tighten carriage mounting bolts.
- Press block against carriage's reference edge and align carriage by tightening clamping screws.
- To assemble carriage evenly, tighten mounting bolts on reference side and following side in turn four times.




Linear Guideways

General information

2.8.2 Assembly of rails with reference edge without clamp


To ensure that the reference and following rails are parallel when not using clamping screws, we would recommend the following methods of assembly. The block is installed as described above.



- [1] Following rail
- [2] Carriage
- [3] Block clamping screw
- [4] Reference rail
- [5] Machine bed

2.8.2.1 Assembly of rail on the reference side


Place the guide on the machine bed's mounting surface. Tighten the mounting bolts slightly and then use a vice to press the guide against the reference edge of the machine bed. Then tighten the mounting bolts in turn to the specified torque.



2.8.2.2 Assembly of rail on the following side


Aligning to a straight edge:

Place the straight edge between the guides and align it parallel to the reference edge on the reference side using a dial gauge. Once the guide on the following side is aligned parallel to the reference side, tighten the mounting bolts in turn working from one end of the guide to the other.



Using a plate:

Install a plate on two blocks on the reference rail. On the following rail, loosely secure a block on the plate. Then fit a dial gauge on the plate and bring the gauge into contact with the side of the following rail's block. Then move the plate from one end to the other and align the following rail parallel to the reference rail. Tighten the mounting bolts in turn.




- [1] Reference rail
- [2] Following rail

Linear Guideways

General information


Aligning to a reference rail:

When the reference rail is correctly installed, securely fit a plate on two blocks on the reference rail and one of the two blocks on the following rail. Then move the plate from one end of the rails to the other, while tightening the mounting bolts of the following rail.



Using a gauge:


Use a special gauge to establish the position of the following rail and tighten the mounting bolts to the specified torque.



- [1] Reference rail
- [2] Following rail

2.8.3 Assembly of rails without reference edge and without clamp

To ensure that the reference and following rails are parallel even if there is no reference edge on the reference side, we would recommend the following type of assembly. The blocks are installed as described above.




- [1] Following rail
- [2] Carriage
- [3] Block clamping screw
- [4] Following rail
- [5] Machine bed

2.8.3.1 Assembly of rail on the reference side

Aligning to a temporary reference edge:


Closely connect two blocks with a plate. Use an edge on the machine bed to align the rail from one end to the other. To check, move the block and tighten the mounting bolts in turn to the specified torque.



Aligning to a straight edge:

Use a dial gauge on a straight edge to align the rail from one end to the other. Be sure to tighten the mounting bolts in turn.

The following rail is assembled as described under [2.8.2.2 „Assembly of rail on the following side“](#).



Linear Guideways

General information

2.8.4 Joint rails

Joint (multi-part) rails must be assembled according to the markings on them. The joints of each section are identified in consecutive alphabetical order as well as by the rail/pair number so that each rail section can be clearly assigned.

Each joint is printed on the top of the rail. This assists with initial assembly and can be removed at any time using a suitable cleaning agent (e.g. methylated spirit). For paired multi-part rails, the word "Paar" must also be stated in addition to the rail number.


Paar = pair

Schiene = rail

	Section 1	Joint a	Section 2	Joint b	Section 3
Rail 1	Schiene 1a		Schiene 1a Schiene 1b		Schiene 1b
Rail 2	Schiene 2a		Schiene 2a Schiene 2b		Schiene 2b

	Section 1	Joint a	Section 2	Joint b	Section 3
Pair 1 Rail 1	Paar 1 1a		Paar 1 1a Paar 1 1b		Paar 1 1b
Pair 1 Rail 2	Paar 1 2a		Paar 1 2a Paar 1 2b		Paar 1 2b
Pair 2 Rail 1	Paar 2 1a		Paar 2 1a Paar 2 1b		Paar 2 1b
Pair 2 Rail 2	Paar 2 2a		Paar 2 2a Paar 2 2b		Paar 2 2b

For paired multi-part rails, the butt joints should be staggered.



2.8.5 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.

Table 2.6 Tightening torques of the mounting bolts according to ISO 4762-12.9

Screw size	Torque [Nm]	Screw size	Torque [Nm]
M2	0.6	M8	30
M3	2	M10	70
M4	4	M12	120
M5	9	M14	160
M6	13	M16	200

Linear Guideways

General information

2.9 Sealing systems

2.9.1 Sealing systems SS, ZZ, DD, KK

The HIWIN end seals firstly prevent the ingress of foreign substances such as dust particles, chips or liquid into the block's ball tracks and secondly reduce the amount of lubricant lost. HIWIN provides various sealing systems for the various ambient conditions of your application. The effectiveness of the end seal impacts directly on the lifetime of the linear guideway and should therefore be taken into account at the design stage and selected to suit the ambient conditions of your application.

SS (standard):

End seal with bottom seal

- For applications with little dirt and dust
- Only minimal increase in displacement forces

ZZ:

Only minimal increase in displacement forces

- For applications associated with hot chips or sharp-edged particles of dirt
- The scraper protects the end seal and prevents it from being damaged

DD:


Double end seal with bottom seal

- For applications associated with a lot of dirt and dust
- The double end seal effectively prevents the ingress of dirt into the block

KK:

Double end seal with bottom seal and scraper

- For applications associated with a lot of dirt and dust and hot chips or sharp-edged particles of dirt
- The scraper protects the end seals and prevents them from being damaged



Availability of sealing systems SS, ZZ, DD and KK:

Sealing systems SS, ZZ, DD and KK are available for all series and sizes.

The exception is the MG series, for which only the standard sealing system SS is available.

Linear Guideways

General information

2.9.2 Sealing systems SW and ZWX for optimum dust protection

Sealing systems SW and ZWX allow HIWIN linear guideways to also be used in areas with very high levels of dirt. The sealing systems offer optimum protection against the ingress of dirt, dust and liquid. The end seal is resistant to oils and greases and very resistant to wear.

Properties:

- End seal with double sealing lip
- Optimized bottom seal
- Additional top seal
- Optimized stainless steel scraper

Advantages:

- Optimum dust protection
- Lifetime extended ten-fold
- Longer lubrication intervals
- Lower maintenance costs

SW:


End seal with double sealing lip, optimized bottom seal and additional top seal

- Optimum dust protection
- The additional top seal prevents the ingress of dirt via the top of the rail
- The optimized bottom seal protects against the ingress of dirt on the rail flank

ZWX:

End seal with double sealing lip, optimized bottom seal, additional top seal and optimized scraper

- Optimum dust protection
- The additional top seal prevents the ingress of dirt via the top of the rail
- The optimized bottom seal protects against the ingress of dirt on the rail flank
- The optimized scraper also protects against dirt particles > 0,2 mm in diameter and prevents damage to the end seal.



Dust test for sealing systems SW and ZWX

Thorough dust tests have shown that the lifetime with sealing systems SW and ZWX is ten times longer than that with a standard seal in cases of high dust levels.

Test conditions:

- Sealed room in which MDF dust is swirled about
- $v = 1,3 \text{ m/s}$
- Grease lubrication




Table 2.7 Availability of sealing systems SW and ZWX

Series	Sizes							
	15	20	25	30	35	45	55	65
HG	○	● ■	● ■	● ■	● ■	● ■	○ □	○ □
CG	○	○	○	○	○	○		
RG	—	—	—	—	—	○ □	○ □	○ □

- Sealing system SW
- Sealing system ZWX

- Sealing system SW (without top seal and optimized bottom seal)
- Sealing system ZWX (without top seal and optimized bottom seal)

Linear Guideways


General information

2.10 SynchMotion™ technology

The innovative SynchMotion™ technology reduces contact between the rolling elements and with the block. Like the ball cage of a standard ball bearing, the rolling elements are kept a defined distance from one another using SynchMotion™ technology. Reciprocal friction, as is produced in standard linear guideways, is therefore prevented and synchronous fluctuations are greatly reduced. No uncontrolled ball movements occur, even at high speeds. SynchMotion™ technology also improves the transport of lubricant within the block and the storage of lubricant.

Advantages:

- Improved synchronous performance
- Optimised for high travel speeds
- Improved lubrication properties
- Less running noise
- Higher dynamic load capacities



QH series

QE series

QR series

Table 2.8 Availability of SynchMotion™ technology for HIWIN linear guideways

Series	Sizes									
	15	20	21	25	27	30	35	45	55	65
QH	●	●	—	●	—	●	●	●	—	—
QE	●	●	—	●	—	●	●	—	—	—
QW	—	—	●	—	●	—	●	—	—	—
QR	—	—	—	●	—	●	●	●	—	—

Carriages with SynchMotion™ technology come in identical sizes, are compatible with the HG, EG, WE and RG blocks, are fitted on the standard rail and are very easy to interchange.

Linear Guideways

General information

2.11 HIWIN coating

2.11.1 HIWIN Coating HICOAT CZS

Characteristics

HICOAT CZS is a very thin zinc coating that offers a very good corrosion protection, even on radii and chamfers. Smaller bare parts stay protected by the cathodic corrosion protection. Compared with uncoated pieces this leads to significantly higher periods of use. The CZS coating is available for the HG, EG and WE series.

Specific features:


- Very good corrosion protection
- Free of Cr(VI)
- A possible interaction between coating, ambient medium and lubricant should be tested in each individual case

Technical data:

Salt spray test DIN EN ISO 9227 [h] ¹⁾	300
Maximum rail length (single-piece) [m]	4,0

¹⁾ Unloaded rail

Model number for coatings:



Corrosion test of mounting rails with CZS coating compared with uncoated rail



Fig. 1: New rail with CZS coating



Fig. 2: Rail with CZS coating – after 6 months of outdoor storage



Fig. 3: Rail with CZS coating – after 99 hours of salt spray test (acc. to DIN EN ISO 9227)



Fig. 4: Uncoated rail – after 4 hours of salt spray test

Table 2.9 HICOAT CZS characteristics

Layer	Zinc
Thickness [μm]	4 - 6
Hardness [HV]	300
Colour	silver glittering
Primary function	corrosion protection
Corrosion protection acc. DIN EN ISO 9227 [h]	***** 50 - 300
Max. coating length [mm]	4000
Attributes	cathodic protection
Suitable for use in food stuffs	no
Price level	low

Linear Guideways

General information

2.11.2 HIWIN Coating HICOAT CTS

Characteristics

HICOAT CTS is a thin layer chrome coating that offers good corrosion protection and a very high wear protection. The high wear protection results from the extraordinary hardness of the coating. The CTS coating is free of Cr(VI) and suitable for use in food stuffs. It is available for the HG, EG and WE series.

Specific features:

- Very good wear protection
- Good corrosion protection
- Free of Cr(VI)
- Suitable for use in food stuffs


Technical data:

Salt spray test DIN EN ISO 9227 [h] ¹⁾	96
Maximum rail length (single-piece) [m]	4,0

¹⁾ Unloaded rail

²⁾ Also available in black (longer delivery time),
not suitable for use in food stuffs, as containing Cr(VI)

Model number for coatings:



Corrosion test of mounting rails with CTS coating compared with uncoated rail



Fig. 1: New rail with CTS coating



Fig. 2: Rail with CTS coating –
after one month of outdoor storage



Fig. 3: Rail with CTS coating –
after 22 hours of salt spray test (acc.
to DIN EN ISO 9227)



Fig. 4: Uncoated rail –
after 4 hours of salt spray test

Table 2.10 HICOAT CTS characteristics

Layer	Chrome
Thickness [μm]	2 - 4
Hardness [HV]	900 - 1300
Colour	silver grey matt
Primary function	wear protection
Corrosion protection acc. DIN EN ISO 9227 [h]	** 22 - 96
Max. coating length [mm]	4000
Attributes	very hard layer
Suitable for use in food stuffs	yes
Price level	high

Table 2.11 HICOAT CTB characteristics

Layer	Chrome + Cr(VI)
Thickness [μm]	4 - 6
Hardness [HV]	800
Colour	black
Primary function	corrosion and wear protection
Corrosion protection acc. DIN EN ISO 9227 [h]	*** 22 - 200
Max. coating length [mm]	4000
Attributes	very hard layer
Suitable for use in food stuffs	no
Price level	high

HG/QH series

The HG (standard) and QH (with Synch-Motion™ technology) series with four ball tracks are designed for high loads and rigidities.

01

Linear Guideways

HG/QH series

3. Linear guideways

3.1 HG and QH series


3.1.1 Properties of the linear guideways, series HG and QH

The HIWIN linear guideways of the HG series with four ball tracks are designed for high loads and rigidities. Due to the 45° arrangement of the ball tracks the HG series can equally take loads from all directions. Low displacement forces and a high efficiency are further features of the HG series. The ball retainers prevent the balls from falling out when the block is pulled off the rail during assembly.


The models of the QH series with SynchMotion™ technology offer all the advantages of the standard series HG. Controlled movement of the balls at a defined distance also results in improved synchronous performance, higher reliable travel speeds, extended lubrication intervals and less running noise. Since the installation dimensions of the QH blocks are identical to those of the HG blocks, they are also fitted on the HGR standard rail and can therefore be interchanged with ease.

3.1.2 Structure of the HG/QH series

- 4-row recirculation ball bearing guide
- 45° contact angle of ball tracks
- Ball retainers prevent the balls from falling out when the block is removed
- Various sealing variants depending on the field of application
- 6 options for connecting grease nipple or lubrication adapter
- SynchMotion™ technology (QH series)



Structure of the HG series



Structure of the QH series

Advantages:

- Zero play
- Interchangeable
- High accuracy
- High loading capacity in all loading directions
- Low friction losses even with preload thanks to optimized ball tracks and 2-point contact

Additional advantages of QH series:

- Improved synchronous performance
- Optimized for higher travel speeds
- Extended lubrication intervals
- Less running noise
- Higher dynamic load capacities

3.1.3 Order codes for the HG/QH series

For HG/QH linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. Block and rail can be ordered separately and fitted by the customer. Their accuracy extends to class P.


Given their stringent dimensional accuracy check, the interchangeable models are a good choice for customers who do not use rails in pairs on one axis. Non-interchangeable linear guideways are always supplied preassembled. The order codes of the series include the dimensions, model, accuracy class, preload etc.

Linear Guideways

HG/QH series


Non-interchangeable models (custom-assembled)

○ Order code for the fully assembled linear guideway




Interchangeable models

○ Order code for HG/QH block



○ Order code for HG rail



Note:

¹⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails.

By default multi-part rails are delivered with staggered butt joints.

²⁾ You will find an overview of the individual sealing systems in [chapter 2.9](#)

³⁾ Only available for HG




Linear Guideways

HG/QH series

3.1.4 Block types

HIWIN provides square and flange blocks for its linear guideways. Given their low height and larger mounting surface, flange blocks are better suited to large loads.

Table 3.1 Block types

Type	Series/ size	Structure	Hight [mm]	Rail length [mm]	Typical application
High square type	HGH-CA HGH-HA		28 – 90	100 – 4,000	<ul style="list-style-type: none"> ○ Machining centers ○ NC lathes ○ Grinding machines ○ Precision milling machines ○ High-performance cutting machines ○ Automation technology ○ Transport technology ○ Measuring technology ○ Machines and equipment requiring high positioning accuracy
Low square type	HGL-CA HGL-HA		24 – 70		
Flange type	HGW-CC HGW-HC		24 – 90		

3.1.5 Rail types

In addition to rails with standard fastening from above, HIWIN also provides rails for fastening from below.

Table 3.2 Rail types

Fastening from above	Fastening from below
	
HGR_R	HGR_T


Linear Guideways

HG/QH series

3.1.6 Preload

Definition

Every rail type can be preloaded based on the size of the balls. The curve shows that the rigidity doubles at higher preload. The HG/QH series offers three standard preload classes for various applications and conditions.



Preload ID

Table 3.3 Preload ID

ID	Preload		Application	Sample applications
Z0	Light preload	$0 - 0.02 C_{dyn}$	Constant load direction, little vibration, lower accuracy needed	<ul style="list-style-type: none"> Transport technology Automatic packaging machines X-Y axis in industrial machines Welding machines
ZA	Medium preload	$0.05 - 0.07 C_{dyn}$	High accuracy needed	<ul style="list-style-type: none"> Machining centres Z axes for industrial machines Eroding machines NC lathes Precision X-Y tables Measuring technology
ZB	High preload	above $0.1 C_{dyn}$	High rigidity needed, vibration and impact	<ul style="list-style-type: none"> Machining centres Grinding machines NC lathes Horizontal and vertical milling machines Z axis of machine tools High-performance cutting machines

Linear Guideways

HG/QH series

3.1.7 Load ratings and torques




Table 3.4 Load ratings and torques for series HG/QH

Series/size	Dynamic load rating C_{dyn} [N] ¹⁾	Static load rating C_0 [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M_x	M_y	M_z	M_{0x}	M_{0y}	M_{0z}
HG_15C	11,380	16,970	76	67	67	120	100	100
QH_15C	13,880	14,360	90	84	84	100	80	80
HG_20S	12,190	16,110	99	61	61	130	80	80
HG_20C	17,750	27,760	178	126	126	270	200	200
QH_20C	23,080	25,630	231	171	171	260	190	190
HG_20H	21,180	35,900	208	203	203	350	350	350
QH_20H	27,530	31,670	268	230	230	310	270	270
HG_25C	26,480	36,490	301	240	240	420	330	330
QH_25C	31,780	33,680	361	294	294	390	310	310
HG_25H	32,750	49,440	374	379	379	560	570	570
QH_25H	39,300	43,620	451	410	410	500	450	450
HG_30C	38,740	52,190	494	396	396	660	530	530
QH_30C	46,490	48,170	588	491	491	600	500	500
HG_30H	47,270	69,160	600	630	630	880	920	920
QH_30H	56,720	65,090	722	623	623	830	890	890
HG_35C	49,520	69,160	832	577	577	1,160	810	810
QH_35C	60,520	63,840	1,019	720	720	1,070	760	760
HG_35H	60,210	91,630	1,011	918	918	1,540	1,400	1,400
QH_35H	73,590	86,240	1,233	1,135	1,135	1,450	1,330	1,330
HG_45C	77,570	102,710	1,497	1,169	1,169	1,980	1,550	1,550
QH_45C	89,210	94,810	1,723	1,295	1,295	1,830	1,380	1,380
HG_45H	94,540	136,460	1,825	1,857	1,857	2,630	2,680	2,680
QH_45H	108,720	128,430	2,097	2,041	2,041	2,470	2,410	2,410
HG_55C	114,440	148,330	2,843	2,039	2,039	3,690	2,640	2,640
HG_55H	139,350	196,200	3,464	3,242	3,242	4,880	4,570	4,570
HG_65C	163,630	215,330	5,049	3,245	3,245	6,650	4,270	4,270
HG_65H	208,360	303,130	6,449	5,068	5,068	9,380	7,380	7,380

¹⁾ Dynamic load rating for travel distance of 50,000 m

Linear Guideways

HG/QH series

3.1.8 Rigidity

Rigidity depends on preload. Formula F 3.1 can be used to determine deformation depending on rigidity.

F 3.1

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/ μm]

Table 3.5 Radial rigidity for series HG/QH

Load class	Series/ size	Rigidity depending on preload		
		Z0	ZA	ZB
Average load	HG_20S	130	170	190
Heavy load	HG_15C	200	260	290
	QH_15C	180	230	260
	HG_20C	250	320	360
	QH_20C	230	290	320
	HG_25C	300	390	440
	QH_25C	270	350	400
	HG_30C	370	480	550
	QH_30C	330	430	500
	HG_35C	410	530	610
	QH_35C	370	480	550
	HG_45C	510	660	750
	QH_45C	460	590	680
	HG_55C	620	800	910
	HG_65C	760	980	1,120
Super heavy load	HG_20H	310	400	460
	QH_20H	280	360	410
	HG_25H	390	510	580
	QH_25H	350	460	520
	HG_30H	480	620	710
	QH_30H	430	560	640
	HG_35H	530	690	790
	QH_35H	480	620	710
	HG_45H	650	850	970
	QH_45H	590	770	870
	HG_55H	790	1,030	1,180
	HG_65H	1,030	1,330	1,520

Unit: N/ μm

Linear Guideways

HG/QH series

3.1.9 Dimensions of the HG/QH blocks

3.1.9.1 HGH/QHH





Table 3.6 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]														Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M × l	T	H ₂	H ₃	C _{dyn}	C ₀		
HGH15CA	28	4.3	9.5	34	26	4.0	26	39.4	61.4	10.00	4.85	5.3	M4 × 5	6.0	7.95	7.7	11,380	16,970	0.18	
QHH15CA	28	4.0	9.5	34	26	4.0	26	39.4	61.4	10.00	5.00	5.3	M4 × 5	6.0	7.95	8.2	13,880	14,360	0.18	
HGH20CA	30	4.6	12.0	44	32	6.0	36	50.5	77.5	12.25	6.00	12.0	M5 × 6	8.0	6.00	6.0	17,750	27,760	0.30	
HGH20HA							50	65.2	92.2	12.60							21,180	35,900	0.39	
QHH20CA	30	4.6	12.0	44	32	6.0	36	50.5	76.7	11.75	6.00	12.0	M5 × 6	8.0	6.00	6.0	23,080	25,630	0.29	
QHH20HA							50	65.2	91.4	12.10							27,530	31,670	0.38	
HGH25CA	40	5.5	12.5	48	35	6.5	35	58.0	84.0	15.70	6.00	12.0	M6 × 8	8.0	10.00	9.0	26,480	36,490	0.51	
HGH25HA							50	78.6	104.6	18.50							32,750	49,440	0.69	
QHH25CA	40	5.5	12.5	48	35	6.5	35	58.0	83.4	15.70	6.00	12.0	M6 × 8	8.0	10.00	9.0	31,780	33,680	0.50	
QHH25HA							50	78.6	104.0	18.50							39,300	43,620	0.68	
HGH30CA	45	6.0	16.0	60	40	10.0	40	70.0	97.4	20.25	6.00	12.0	M8 × 10	8.5	9.50	13.8	38,740	52,190	0.88	
HGH30HA							60	93.0	120.4	21.75							47,270	69,160	1.16	
QHH30CA	45	6.0	16.0	60	40	10.0	40	70.0	97.4	19.50	6.25	12.0	M8 × 10	8.5	9.50	9.0	46,490	48,170	0.87	
QHH30HA							60	93.0	120.4	21.75							56,720	65,090	1.15	
HGH35CA	55	7.5	18.0	70	50	10.0	50	80.0	112.4	20.60	7.00	12.0	M8 × 12	10.2	16.00	19.6	49,520	69,160	1.45	
HGH35HA							72	105.8	138.2	22.50							60,210	91,630	1.92	
QHH35CA	55	7.5	18.0	70	50	10.0	50	80.0	113.6	19.00	7.50	12.0	M8 × 12	10.2	15.50	13.5	60,520	63,840	1.44	
QHH35HA							72	105.8	139.4	20.90							73,590	86,240	1.90	
HGH45CA	70	9.5	20.5	86	60	13.0	60	97.0	139.4	23.00	10.00	12.9	M10 × 17	16.0	18.50	30.5	77,570	102,710	2.73	
HGH45HA							80	128.8	171.2	28.90							94,540	136,460	3.61	
QHH45CA	70	9.2	20.5	86	60	13.0	60	97.0	139.4	23.00	10.00	12.9	M10 × 17	16.0	18.50	20.0	89,210	94,810	2.72	
QHH45HA							80	128.8	171.2	29.09							108,720	128,430	3.59	
HGH55CA	80	13.0	23.5	100	75	12.5	75	117.7	166.7	27.35	11.00	12.9	M12 × 18	17.5	22.00	29.0	114,440	148,330	4.17	
HGH55HA							95	155.8	204.8	36.40							139,350	196,200	5.49	
HGH65CA	90	15.0	31.5	126	76	25.0	70	144.2	200.2	43.10	14.00	12.9	M16 × 20	25.0	15.00	15.0	163,630	215,330	7.00	
HGH65HA							120	203.6	259.6	47.80							208,360	303,130	9.82	

For dimensions of the rail see [chapter 3.1.10](#), for standard and optional lubrication adapters see [chapter 4.1](#).

Linear Guideways

HG/QH series

3.1.9.2 HGL




Table 3.7 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]														Load ratings [N]		Weigh [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M × l	T	H ₂	H ₃	C _{dyn}	C ₀		
HGL15CA	24	4.3	9.5	34	26	4.0	26	39.4	61.4	10.00	4.85	5.3	M4 × 4	6.0	3.95	3.7	11,380	16,970	0.14	
HGL25SA	36	5.5	12.5	48	35	6.5	—	38.2	64.2	23.20	6.00	12.0	M6 × 6	8.0	6.00	5.0	18,650	24,290	0.32	
HGL25CA							35	58.0	84.0	15.70							26,480	36,490	0.42	
HGL25HA							50	78.6	104.6	18.50							32,750	49,440	0.57	
HGL30CA	42	6.0	16.0	60	40	10.0	40	70.0	97.4	20.25	6.00	12.0	M8 × 10	8.5	6.50	10.8	38,740	52,190	0.78	
HGL30HA						60	93.0	120.4	21.75	47,270							69,160	1.03		
HGL35CA	48	7.5	18.0	70	50	10.0	50	80.0	112.4	20.60	7.00	12.0	M8 × 12	10.2	9.00	12.6	49,520	69,160	1.14	
HGL35HA						72	105.8	138.2	22.50	60,210							91,630	1.52		
HGL45CA	60	9.5	20.5	86	60	13.0	60	97.0	139.4	23.00	10.00	12.9	M10 × 17	16.0	8.50	20.5	77,570	102,710	2.08	
HGL45HA						80	128.8	171.2	28.90	94,540							136,460	2.75		
HGL55CA	70	13.0	23.5	100	75	12.5	75	117.7	166.7	27.35	11.00	12.9	M12 × 18	17.5	12.00	19.0	114,440	148,330	3.25	
HGL55HA						95	155.8	204.8	36.40	139,350							196,200	4.27		

For dimensions of the rail see [chapter 3.1.10](#), for standard and optional lubrication adapters see [chapter 4.1](#).

Linear Guideways

HG/QH series

3.1.9.3 HGW/QHW




Table 3.8 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]																Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	M	G	T	T ₁	T ₂	H ₂	H ₃	C _{dyn}	C ₀		
HGW15CC	24	4.3	16.0	47	38	4.5	30	39.4	61.4	8.00	4.85	M5	5.3	6.0	8.9	7.0	3.95	3.7	11,380	16,970	0.17	
QHW15CC	24	4.0	16.0	47	38	4.5	30	39.4	61.4	8.00	5.00	M5	5.3	6.0	8.9	7.0	3.95	4.2	13,880	14,360	0.17	
HGW20SC	30	4.6	21.5	63	53	5.0	—	29.5	54.3	19.65	6.00	M6	12.0	8.0	10.0	9.5	6.00	6.0	12,190	16,110	0.28	
40							50.5	77.5	10.25	17,750									27,760	0.40		
65.2							92.2	17.60	21,180	35,900									0.52			
HGW20HC	30	4.6	21.5	63	53	5.0	40	50.5	76.7	9.75	6.00	M6	12.0	8.0	10.0	9.5	6.00	6.0	23,080	25,630	0.40	
65.2							91.4	17.10	27,530	31,670									0.52			
HGW25SC	36	5.5	23.5	70	57	6.5	—	38.2	64.2	23.20	6.00	M8	12.0	8.0	14.0	10.0	6.00	5.0	18,650	24,290	0.42	
45							58.0	84.0	10.70	26,480									36,490	0.59		
78.6							104.6	21.00	32,750	49,440									0.80			
QHW25CC	36	5.5	23.5	70	57	6.5	45	58.0	83.4	10.70	6.00	M8	12.0	8.0	14.0	10.0	6.00	5.0	31,780	33,680	0.59	
78.6							104.0	21.00	39,300	43,620									0.80			
HGW30CC	42	6.0	31.0	90	72	9.0	52	70.0	97.4	14.25	6.00	M10	12.0	8.5	16.0	10.0	6.50	10.8	38,740	52,190	1.09	
HGW30HC								93.0	120.4	25.75									47,270	69,160	1.44	
QHW30CC	42	6.0	31.0	90	72	9.0	52	70.0	97.4	13.50	6.25	M10	12.0	8.5	16.0	10.0	6.50	6.0	46,490	48,170	1.09	
QHW30HC								93.0	120.4	25.75									56,720	65,090	1.44	
HGW35CC	48	7.5	33.0	100	82	9.0	62	80.0	112.4	14.60	7.00	M10	12.0	10.1	18.0	13.0	9.00	12.6	49,520	69,160	1.56	
HGW35HC																						105.8
QHW35CC	48	7.5	33.0	100	82	9.0	62	80.0	113.6	13.00	7.50	M10	12.0	10.1	18.0	13.0	8.50	6.5	60,520	63,840	1.56	
QHW35HC																						105.8
HGW45CC	60	9.5	37.5	120	100	10.0	80	97.0	139.4	13.00	10.00	M12	12.9	15.1	22.0	15.0	8.50	20.5	77,570	102,710	2.79	
HGW45HC																						128.8
QHW45CC	60	9.2	37.5	120	100	10.0	80	97.0	139.4	13.00	10.00	M12	12.9	15.1	22.0	15.0	8.50	10.0	89,210	94,810	2.79	
QHW45HC																						128.8
HGW55CC	70	13.0	43.5	140	116	12.0	95	117.7	166.7	17.35	11.00	M14	12.9	17.5	26.5	17.0	12.00	19.0	114,440	148,330	4.52	
HGW55HC								155.8	204.8	36.40									139,350	196,200	5.96	
HGW65CC	90	15.0	53.5	170	142	14.0	110	144.2	200.2	23.10	14.00	M16	12.9	25	37.5	23.0	15.00	15.0	163,630	215,330	9.17	
HGW65HC																						203.6

For dimensions of the rail see [chapter 3.1.10](#), for standard and optional lubrication adapters see [chapter 4.1](#).

Linear Guideways

HG/QH series

3.1.10 Dimensions of the HG rail

The HG rails are used for both the HG and QH blocks.

3.1.10.1 Dimensions of HGR_R




Table 3.9 Dimensions of rail HGR_R

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	D	h	d	P					
HGR15R	M4 × 16	15	15.0	7.5	5.3	4.5	60	4,000	3,900	6	54	1.45
HGR20R	M5 × 16	20	17.5	9.5	8.5	6.0	60	4,000	3,900	7	53	2.21
HGR25R	M6 × 20	23	22.0	11.0	9.0	7.0	60	4,000	3,900	8	52	3.21
HGR30R	M8 × 25	28	26.0	14.0	12.0	9.0	80	4,000	3,920	9	71	4.47
HGR35R	M8 × 25	34	29.0	14.0	12.0	9.0	80	4,000	3,920	9	71	6.30
HGR45R	M12 × 35	45	38.0	20.0	17.0	14.0	105	4,000	3,885	12	93	10.41
HGR55R	M14 × 45	53	44.0	23.0	20.0	16.0	120	4,000	3,840	14	106	15.08
HGR65R	M16 × 50	63	53.0	26.0	22.0	18.0	150	4,000	3,750	15	135	21.18

3.1.10.2 Dimensions of HGR_T




Table 3.10 Dimensions of rail HGR_T

Series/ size	Dimensions of rail [mm]					Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
	W_R	H_R	S	h	P					
HGR15T	15	15.0	M5	8	60	4,000	3,900	6	54	1.48
HGR20T	20	17.5	M6	10	60	4,000	3,900	7	53	2.29
HGR25T	23	22.0	M6	12	60	4,000	3,900	8	52	3.35
HGR30T	28	26.0	M8	15	80	4,000	3,920	9	71	4.67
HGR35T	34	29.0	M8	17	80	4,000	3,920	9	71	6.51
HGR45T	45	38.0	M12	24	105	4,000	3,885	12	93	10.87
HGR55T	53	44.0	M14	24	120	4,000	3,840	14	106	15.67
HGR65T	63	53.0	M20 ¹⁾	30	150	4,000	3,750	15	135	21.73

¹⁾ Deviating from DIN 645

Note:


1. The tolerance for E is +0.5 to -1 mm for standard rails and 0 to -0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

Linear Guideways

HG/QH series

3.1.10.3 Calculating the length of rails

HIWIN offers rails in customized lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2}$ min and $E_{1/2}$ max so that the mounting hole does not rupture.



F 3.2

$$L = (n - 1) \times P + E_1 + E_2$$

- L Total length of the rail [mm]
- n Number of mounting holes
- P Distance between two mounting holes [mm]
- $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

3.1.10.4 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.

Table 3.11 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
HG_15	M4 × 16	4	HG_35	M8 × 25	30
HG_20	M5 × 16	9	HG_35	M10	70
HG_25	M6 × 20	13	HG_45	M12 × 35	120
HG_30	M8 × 25	30	HG_55	M14 × 45	160
HG_30	M10	70	HG_65	M16 × 50	200

3.1.10.5 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail. Optional cover caps must be ordered separately.




Table 3.12 Cover caps for mounting holes of rails

Rail	Screw	Article number			Ø D [mm]	Height H [mm]
		Plastic	Brass	Steel		
HGR15R	M4	C4	C4-B	—	7.5	1.1
HGR20R	M5	C5	C5-B	C5-ST	9.5	2.2
HGR25R	M6	C6	C6-B	C6-ST	11.0	2.5
HGR30R	M8	C8	C8-B	C8-ST	14.0	3.3
HGR35R	M8	C8	C8-B	C8-ST	14.0	3.3
HGR45R	M12	C12	C12-B	C12-ST	20.0	4.6
HGR55R	M14	C14	C14-B	C14-ST	23.0	5.5
HGR65R	M16	C16	C16-B	C16-ST	26.0	5.5

Linear Guideways

HG/QH series

3.1.11 Sealing systems

Various sealing systems are available for HIWIN blocks. You will find an overview in [chapter 2.9](#). The table below shows the total length of the blocks with the different sealing systems. Sealing systems suitable for these sizes are available.




Table 3.13 Total length of blocks with different sealing systems

Series/ size	Total length L					
	SS	DD	ZZ	KK	SW	ZWX
HG_15C	61.4	68.0	69.0	75.6	63.2	—
QH_15C	61.4	68.0	68.4	75.0	—	—
HG_20S	56.5	59.5	57.5	62.5	57.5	61.3
HG_20C	77.5	82.5	82.5	87.5	78.5	82.3
QH_20C	76.7	81.7	81.9	86.9	—	—
HG_20H	92.2	97.5	97.2	102.2	93.2	97.0
QH_20H	91.4	96.4	96.6	101.6	—	—
HG_25C	84.0	89.0	89.0	94.0	85.0	91.8
QH_25C	83.4	88.4	89.4	94.4	—	—
HG_25H	104.6	109.6	109.6	114.6	105.6	112.4
QH_25H	104.4	109.0	110.0	115.0	—	—
HG_30C	97.4	104.8	105.4	112.8	99.0	105.8
QH_30C	97.4	104.8	104.8	112.2	—	—
HG_30H	120.4	127.8	128.4	135.8	122.0	128.8
QH_30H	120.4	127.8	127.8	135.2	—	—
HG_35C	112.4	119.8	120.4	127.8	115.2	122.4
QH_35C	113.6	118.6	119.0	124.0	—	—
HG_35H	138.2	145.6	146.2	153.6	141.0	148.2
QH_35H	139.4	144.4	144.8	149.8	—	—
HG_45C	139.4	149.4	150.0	160.0	140.0	144.8
QH_45C	139.4	146.6	147.2	154.4	—	—
HG_45H	171.2	181.2	181.8	191.8	171.8	176.6
QH_45H	171.2	178.4	179.0	186.2	—	—
HG_55C	166.7	177.1	177.1	187.5	163.7	172.9
HG_55H	204.8	215.2	215.2	225.5	201.8	211.0
HG_65C	200.2	209.2	208.2	217.2	196.2	203.4
HG_65H	259.6	268.6	267.6	276.6	255.6	262.8


Unit: mm

Linear Guideways

HG/QH series

3.1.11.1 Designation of sealing sets

The sealing sets are always supplied along with the assembly material and include the parts needed in addition to the standard seal.



3.1.12 Friction

The table shows the maximum frictional resistance of the individual end seal. Depending on sealing setup (SS, DD, ZZ, KK), the value may have to be multiplied. The values indicated apply to blocks on uncoated rails. Higher friction forces occur on coated rails.

Table 3.14 Frictional resistance of single-lipped seals

Series/size	Friction force [N]	Series/size	Friction force [N]
HG/QH_15	1.2	HG_45	3.9
HG/QH_20	1.6	QH_45	5.3
HG/QH_25	2.0	HG_55	4.7
HG/QH_30	2.7	HG_65	5.8
HG/QH_35	3.1		

Linear Guideways

HG/QH series

3.1.13 Lubrication unit E2

You will find more information about the lubrication unit in the general information in the lubrication unit E2 Section "2.6.3 Oil Lubrication unit E2".




Table 3.15 Dimensions of block with lubrication unit E2

Model	Dimensions of the block [mm]								Oil quantity [cm ³]	Mileage ²⁾ [km]
	W	H	T	V	L _{SS} ¹⁾	L _{ZZ} ¹⁾	L _{DD} ¹⁾	L _{KK} ¹⁾		
HG_15C	32.4	19.5	12.5	3.0	75.4	80.5	82.0	87.1	1.6	2,000
HG_20S	43.0	24.4	13.5	3.5	70.9	73.0	75.0	78.0	3.9	4,000
HG_20C	43.0	24.4	13.5	3.5	93.5	95.6	97.5	100.6	3.9	4,000
HG_20H	43.0	24.4	13.5	3.5	108.2	110.2	112.2	115.2	3.9	4,000
HG_25C	46.4	29.5	13.5	3.5	100.0	102.0	104.0	107.0	5.1	6,000
HG_25H	46.4	29.5	13.5	3.5	120.6	122.6	124.6	127.6	5.1	6,000
HG_30C	58.0	35.0	13.5	3.5	112.9	118.0	119.9	125.0	7.8	8,000
HG_30H	58.0	35.0	13.5	3.5	135.9	141.0	142.9	148.0	7.8	8,000
HG_35C	68.0	38.5	13.5	3.5	127.9	133.4	135.3	140.8	9.8	10,000
HG_35H	68.0	38.5	13.5	3.5	153.7	159.2	161.1	166.6	9.8	10,000
HG_45C	82.0	49.0	16.0	4.5	157.2	162.1	166.1	171.7	18.5	20,000
HG_45H	82.0	49.0	16.0	4.5	189.0	193.9	197.9	203.5	18.5	20,000
HG_55C	97.0	55.5	16.0	4.5	183.9	189.6	193.8	200.0	25.9	30,000
HG_55H	97.0	55.5	16.0	4.5	222.0	227.7	231.9	238.1	25.9	30,000
HG_65C	121.0	69.0	16.0	4.5	219.2	220.7	226.7	229.7	50.8	40,000
HG_65H	121.0	69.0	16.0	4.5	278.6	280.1	286.1	289.1	50.8	40,000

¹⁾ Total length depending on selected dust protection. SS = Standard dust protection


²⁾ Mileage at which the oil tank level should be checked at the very latest

Linear Guideways

HG/QH series

3.1.14 Tolerances depending on accuracy class

The HG and QH series are available in five accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.



3.1.14.1 Parallelism

Parallelism of stop surfaces D and B of block and rail and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.

Table 3.16 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class				
	C	H	P	SP	UP
– 100	12	7	3	2	2
100 – 200	14	9	4	2	2
200 – 300	15	10	5	3	2
300 – 500	17	12	6	3	2
500 – 700	20	13	7	4	2
700 – 900	22	15	8	5	3
900 – 1100	24	16	9	6	3
1100 – 1500	26	18	11	7	4
1500 – 1900	28	20	13	8	4
1900 – 2500	31	22	15	10	5
2500 – 3100	33	25	18	11	6
3100 – 3600	36	27	20	14	7
3600 – 4000	37	28	21	15	7

Unit: μm

Linear Guideways

HG/QH series

3.1.14.2 Accuracy – height and width

Height tolerance H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position.

Width tolerance N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.17 Height and width tolerances of non-interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
HG_15, 20 QH_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	0 – 0.03	0 – 0.03	0.006	0.006
	SP (Super precision)	0 – 0.015	0 – 0.015	0.004	0.004
	UP (Ultra precision)	0 – 0.008	0 – 0.008	0.003	0.003
HG_25, 30, 35 QH_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	0 – 0.04	0 – 0.04	0.007	0.007
	SP (Super precision)	0 – 0.02	0 – 0.02	0.005	0.005
	UP (Ultra precision)	0 – 0.01	0 – 0.01	0.003	0.003
HG_45, 55 QH_45	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	0 – 0.05	0 – 0.05	0.007	0.01
	SP (Super precision)	0 – 0.03	0 – 0.03	0.005	0.007
	UP (Ultra precision)	0 – 0.02	0 – 0.02	0.003	0.005
HG_65	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.07	± 0.07	0.02	0.025
	P (Precision)	0 – 0.07	0 – 0.07	0.01	0.015
	SP (Super precision)	0 – 0.05	0 – 0.05	0.007	0.01
	UP (Ultra precision)	0 – 0.03	0 – 0.03	0.005	0.007

Unit: mm

Linear Guideways

HG/QH series

Table 3.18 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
HG_15, 20 QH_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	± 0.015	± 0.015	0.006	0.006
HG_25, 30, 35 QH_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	± 0.02	± 0.02	0.007	0.007
HG_45, 55 QH_45	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	± 0.025	± 0.025	0.007	0.01
HG_65	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.07	± 0.07	0.02	0.025
	P (Precision)	± 0.035	± 0.035	0.01	0.015

Unit: mm

3.1.14.3 Permissible mounting surface tolerances

Once the requirements relating to the accuracy of the mounting surfaces are met, the good accuracy, rigidity and lifetime of the HG and QH series linear guideways are achieved.

Parallelism of the reference surface (P):




Table 3.19 Maximum tolerance for parallelism (P)

Series/size	Preload class		
	Z0	ZA	ZB
HG/QH_15	25	18	—
HG/QH_20	25	20	18
HG/QH_25	30	22	20
HG/QH_30	40	30	27
HG/QH_35	50	35	30
HG/QH_45	60	40	35
HG_55	70	50	45
HG_65	80	60	55

Unit: μm

Linear Guideways

HG/QH series

Table 3.20 Maximum tolerance for height of reference surface (S₁)

Series/size	Preload class		
	Z0	ZA	ZB
HG/QH_15	130	85	—
HG/QH_20	130	85	50
HG/QH_25	130	85	70
HG/QH_30	170	110	90
HG/QH_35	210	150	120
HG/QH_45	250	170	140
HG_55	300	210	170
HG_65	350	250	200

Unit: μm

3.1.15 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.21 Shoulder heights and fillets

Series/size	Max. edge radius r	Shoulder height of reference edge of rail E ₁	Shoulder height of reference edge of block E ₂	Clearance under block H ₁
HG_15	0.5	3.0	4.0	4.3
QH_15	0.5	3.0	4.0	4.0
HG/QH_20	0.5	3.5	5.0	4.6
HG/QH_25	1.0	5.0	5.0	5.5
HG/QH_30	1.0	5.0	5.0	6.0
HG/QH_35	1.0	6.0	6.0	7.5
HG/QH_45	1.0	8.0	8.0	9.5
HG_55	1.5	10.0	10.0	13.0
HG_65	1.5	10.0	10.0	15.0

Unit: mm

EG/QE series

The EG (standard) and QE (with Synchron-Motion™ technology) series with four ball tracks have a low installation height, making them ideally suited to applications with a low installation space.

01

Linear Guideways

EG/QE series

3.2 EG and QE series


3.2.1 Properties of the linear guideways, series EG and QE

The HIWIN linear guideways of the EG series with four ball tracks have a low installation height, making them ideally suited to applications with a low installation space. Despite this, the EG series has the same properties as the HG series – good loading capacity, low displacement forces and high efficiency. The ball retainers prevent the balls from falling out when the block is pulled off the rail during assembly.


The models of the QE series with SynchMotion™ technology offer all the advantages of the standard series EG. Controlled movement of the balls at a defined distance also results in improved synchronous performance, higher reliable travel speeds, extended lubrication intervals and less running noise. Since the installation dimensions of the QE blocks are identical to those of the EG blocks, they are also fitted on the EGR standard rail and can therefore be interchanged with ease.

3.2.2 Structure of the EG/QE series

- 4-row recirculation ball bearing guide
- 45° contact angle of ball tracks
- Ball retainers prevent the balls from falling out when the block is removed
- Various sealing variants depending on the field of application
- 6 options for connecting grease nipple or lubrication adapter
- SynchMotion™ technology (QE series)



Structure of the EG series



Structure of the QE series

Advantages:

- Zero play
- Interchangeable
- High accuracy
- High loading capacity in all loading directions
- Low friction losses even with preload thanks to optimized ball tracks and 2-point contact

Additional advantages of QE series:

- Improved synchronous performance
- Optimized for higher travel speeds
- Extended lubrication intervals
- Less running noise
- Higher dynamic load capacities

3.2.3 Order codes for the EG/QE series

For EG/QE linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. Block and rail can be ordered separately and fitted by the customer. Their accuracy extends to class P.


Given their stringent dimensional accuracy check, the interchangeable modules are a good choice for customers who do not use rails in pairs on one axis. Non-interchangeable linear guideways are always supplied preassembled. The order codes of the series include the dimensions, model, accuracy class, preload etc.

Linear Guideways

EG/QE series


Non-interchangeable models (custom-assembled)

○ Order code for the fully assembled linear guideway




Interchangeable models

○ Order code for EG/QE block



○ Order code for EG rail



Note:

¹⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails
By default multi-part rails are delivered with staggered butt joints.

²⁾ You will find an overview of the individual sealing systems in [chapter 2.9](#)



³⁾ Only available for EG

Linear Guideways EG/QE series

3.2.4 Block types

HIWIN provides square and flange blocks for its linear guideways. Given their low height and larger mounting surface, flange blocks are better suited to large loads.

Table 3.22 Block types

Type	Series/ size	Structure	Height [mm]	Rail length [mm]	Typical application
Square type	EGH-SA EGH-CA		24 – 48	100 – 4,000	<ul style="list-style-type: none"> ○ Machining centers ○ NC lathes ○ Grinding machines ○ Precision milling machines ○ High-performance cutting machines ○ Automation technology ○ Transport technology ○ Measuring technology ○ Machines and equipment requiring high positioning accuracy
Flange type	EGW-SC EGW-CC				

3.2.5 Rail types

In addition to rails with standard fastening from above, HIWIN also provides rails for fastening from below.


Table 3.23 Rail types

Fastening from above	Fastening from below
	
EGR_R	EGR_T

3.2.6 Preload

Definition

Every rail type can be preloaded based on the size of the balls. The curve shows that the rigidity doubles at higher preload. The EG/QE series offers three standard preload classes for various applications and conditions.



Linear Guideways

EG/QE series

Table 3.24 Preload ID

ID	Preload		Application	Sample applications
Z0	Light preload	$0 - 0.02 C_{dyn}$	Constant load direction, low impact, low accuracy needed	<ul style="list-style-type: none"> Transport technology Automatic packaging machines X-Y axis in industrial machines Welding machines
ZA	Medium preload	$0.03 - 0.05 C_{dyn}$	High accuracy needed	<ul style="list-style-type: none"> Machining centres Z axes for industrial machines Eroding machines NC lathes Precision X-Y tables Measuring technology
ZB	High preload	$0.06 - 0.08 C_{dyn}$	High rigidity needed, vibration and impact	<ul style="list-style-type: none"> Machining centres Grinding machines NC lathes Horizontal and vertical milling machines Z axis of machine tools High-performance cutting machines

3.2.7 Load ratings and torques




Table 3.25 Load ratings and torques for series EG/QE

Series/size	Dynamic load rating C_{dyn} [N] ¹⁾	Static load rating C_0 [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M_x	M_y	M_z	M_{0x}	M_{0y}	M_{0z}
EG_15S	5,350	9,400	45	22	22	80	40	40
QE_15S	8,560	8,790	68	29	29	70	30	30
EG_15C	7,830	16,190	62	48	48	130	100	100
QE_15C	12,530	15,280	98	73	73	120	90	90
EG_20S	7,230	12,740	73	34	34	130	60	60
QE_20S	11,570	12,180	123	47	47	130	50	50
EG_20C	10,310	21,130	107	78	78	220	160	160
QE_20C	16,500	20,210	171	122	122	210	150	150
EG_25S	11,400	19,500	134	70	70	230	120	120
QE_25S	18,240	18,900	212	96	96	220	100	100
EG_25C	16,270	32,400	190	160	160	380	320	320
QE_25C	26,030	31,490	305	239	239	370	290	290
EG_30S	16,420	28,100	233	122	122	400	210	210
QE_30S	26,270	27,820	377	169	169	400	180	180
EG_30C	23,700	47,460	339	274	274	680	550	550
QE_30C	37,920	46,630	544	414	414	670	510	510
EG_35S	22,660	37,380	339	187	187	560	310	310
QE_35S	36,390	36,430	609	330	330	610	330	330
EG_35C	33,350	64,840	504	354	354	980	690	690
QE_35C	51,180	59,280	863	648	648	1,000	750	750

¹⁾ Dynamic load rating for travel distance of 50,000 m

Linear Guideways EG/QE series

3.2.8 Rigidity

Rigidity depends on preload. Formula [F 3.3](#) can be used to determine deformation depending on rigidity.

F 3.3

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/ μm]

Table 3.26 Radial rigidity for series EG/QE

Load class	Series/ size	Rigidity depending on preload		
		Z0	ZA	ZB
Average load	EG_15S	105	126	141
	QE_15S	96	115	128
	EG_20S	126	151	168
	QE_20S	116	139	153
	EG_25S	156	187	209
	QE_25S	137	165	184
	EG_30S	184	221	246
	QE_30S	169	203	226
	EG_35S	221	265	295
	QE_35S	214	257	287
Heavy load	EG_15C	172	206	230
	QE_15C	157	187	209
	EG_20C	199	238	266
	QE_20C	183	219	245
	EG_25C	246	296	329
	QE_25C	219	263	293
	EG_30C	295	354	395
	QE_30C	271	326	363
	EG_35C	354	425	474
	QE_35C	333	399	445

Unit: N/ μm

Linear Guideways

EG/QE series

3.2.9 Dimensions of the EG/QE blocks

3.2.9.1 EGH/QEH




Table 3.27 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]														Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M × l	T	H ₂	H ₃	C _{dyn}	C ₀		
EGH15SA	24	4.5	9.5	34	26	4.0	—	23.1	40.1	14.80	3.50	5.7	M4 × 6	6.0	5.5	6.0	5,350	9,400	0.09	
EGH15CA							26	39.8	56.8	10.15							7,830	16,190	0.15	
QEH15SA	24	4.0	9.5	34	26	4.0	—	23.1	40.1	14.80	3.50	5.7	M4 × 6	6.0	5.5	6.0	8,560	8,790	0.09	
QEH15CA							26	39.8	56.8	10.15							12,530	15,280	0.15	
EGH20SA	28	6.0	11.0	42	32	5.0	—	29.0	50.0	18.75	4.15	12.0	M5 × 7	7.5	6.0	6.0	7,230	12,740	0.15	
EGH20CA							32	48.1	69.1	12.30							10,310	21,130	0.24	
QEH20SA	28	6.0	11.0	42	32	5.0	—	29.0	50.0	18.75	4.15	12.0	M5 × 7	7.5	6.0	6.5	11,570	12,180	0.15	
QEH20CA							32	48.1	69.1	12.30							16,500	20,210	0.23	
EGH25SA	33	7.0	12.5	48	35	6.5	—	35.5	59.1	21.90	4.55	12.0	M6 × 9	8.0	8.0	8.0	11,400	19,500	0.25	
EGH25CA							35	59.0	82.6	16.15							16,270	32,400	0.41	
QEH25SA	33	6.2	12.5	48	35	6.5	—	35.5	60.1	21.90	5.00	12.0	M6 × 9	8.0	8.0	8.0	18,240	18,900	0.24	
QEH25CA							35	59.0	83.6	16.15							26,030	31,490	0.40	
EGH30SA	42	10.0	16.0	60	40	10.0	—	41.5	69.5	26.75	6.00	12.0	M8 × 12	9.0	8.0	9.0	16,420	28,100	0.45	
EGH30CA							40	70.1	98.1	21.05							23,700	47,460	0.76	
QEH30SA	42	10.0	16.0	60	40	10.0	—	41.5	67.5	25.75	6.00	12.0	M8 × 12	9.0	8.0	9.0	26,270	27,820	0.44	
QEH30CA							40	70.1	96.1	20.05							37,920	46,630	0.75	
EGH35SA	48	11.0	18.0	70	50	10.0	—	45.0	75.0	28.50	7.00	12.0	M8 × 12	10.0	8.5	8.5	22,660	37,380	0.74	
EGH35CA							50	78.0	108.0	20.00							33,350	64,840	1.10	
QEH35SA	48	11.0	18.0	70	50	10.0	—	51.0	76.0	30.30	6.25	12.0	M8 × 12	10.0	8.5	8.5	36,390	36,430	0.58	
QEH35CA							50	83.0	108.0	21.30							51,180	59,280	0.90	

For dimensions of rail, see [chapter 3.2.10](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways EG/QE series

3.2.9.2 EGW/QEW




Table 3.28 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]															Load ratings [N]		Weigh [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M	T	T ₁	H ₂	H ₃	C _{dyn}	C ₀		
EGW15SC	24	4.5	18.5	52	41	5.5	—	23.1	40.1	14.80	3.50	5.7	M5	5.0	7	5.5	6.0	5,350	9,400	0.12	
EGW15CC							26	39.8	56.8	10.15								7,830	16,190	0.21	
QEW15SC	24	4.0	18.5	52	41	5.5	—	23.1	40.1	14.80	3.50	5.7	M5	5.0	—	5.5	6.0	8,560	8,790	0.12	
QEW15CC							26	39.8	56.8	10.15								12,530	15,280	0.21	
EGW20SC	28	6.0	19.5	59	49	5.0	—	29.0	50.0	18.75	4.15	12.0	M6	7.0	9	6.0	6.0	7,230	12,740	0.19	
EGW20CC							32	48.1	69.1	12.30								10,310	21,130	0.32	
QEW20SC	28	6.0	19.5	59	49	5.0	—	29.0	50.0	18.75	4.15	12.0	M6	7.0	—	6.0	6.5	11,570	12,180	0.19	
QEW20CC							32	48.1	69.1	12.30								16,500	20,210	0.31	
EGW25SC	33	7.0	25.0	73	60	6.5	—	35.5	59.1	21.90	4.55	12.0	M8	7.5	10	8.0	8.0	11,400	19,500	0.35	
EGW25CC							35	59.0	82.6	16.15								16,270	32,400	0.59	
QEW25SC	33	6.2	25.0	73	60	6.5	—	35.5	60.1	21.90	5.00	12.0	M8	7.5	—	8.0	8.0	18,240	18,900	0.34	
QEW25CC							35	59.0	83.6	16.15								26,030	31,90	0.58	
EGW30SC	42	10.0	31.0	90	72	9.0	—	41.5	69.5	26.75	6.00	12.0	M10	7.0	10	8.0	9.0	16,420	28,100	0.62	
EGW30CC							40	70.1	98.1	21.05								23,700	47,460	1.04	
QEW30SC	42	10.0	31.0	90	72	9.0	—	41.5	67.5	25.75	6.00	12.0	M10	7.0	—	8.0	9.0	26,270	27,820	0.61	
QEW30CC							40	70.1	96.1	20.05								37,920	46,630	1.03	
EGW35SC	48	11.0	33.0	100	82	9.0	—	45.0	75.0	28.50	7.00	12.0	M10	10.0	13	8.5	8.5	22,660	37,380	0.91	
EGW35CC							50	78.0	108.0	20.00								33,350	64,840	1.40	
QEW35SC	48	11.0	33.0	100	82	9.0	—	51.0	76.0	30.30	6.25	12.0	M10	10.0	13	8.5	8.5	36,390	36,430	0.77	
QEW35CC							50	83.0	108.0	21.30								51,180	59,280	1.19	

For dimensions of rail, see [chapter 3.2.10](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways

EG/QE series

3.2.10 Dimensions of the EG rail

The EG rails are used for both the EG and QE blocks.

3.2.10.1 Dimensions of EGR_R




Table 3.29 Dimensions of rail EGR_R

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	D	h	d	P					
EGR15R	M3 × 16	15	12.5	6.0	4.5	3.5	60	4,000	3,900	6	54	1.25
EGR20R	M5 × 16	20	15.5	9.5	8.5	6.0	60	4,000	3,900	7	53	2.08
EGR25R	M6 × 20	23	18.0	11.0	9.0	7.0	60	4,000	3,900	8	52	2.67
EGR30R	M6 × 25	28	23.0	11.0	9.0	7.0	80	4,000	3,920	9	71	4.35
EGR35R	M8 × 25	34	27.5	14.0	12.0	9.0	80	4,000	3,920	9	71	6.14

3.2.10.2 Dimensions of EGR_U (large mounting holes)




Table 3.30 Dimensions of rail EGR_U

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	D	h	d	P					
EGR15U	M4 × 16	15	12.5	7.5	5.3	4.5	60	4,000	3,900	6	54	1.23
EGR30U	M8 × 25	28	23.0	14.0	12.0	9.0	80	4,000	3,920	9	71	4.23

Note:

1. The tolerance for E is $+0.5$ to -1 mm for standard rails and 0 to -0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

Linear Guideways

EG/QE series

3.2.10.3 Dimensions of EGR_T (rail mounting from below)




Table 3.31 Dimensions of rail EGR_T


Series/ size	Dimensions of rail [mm]					Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
	W_R	H_R	S	h	P					
EGR15T	15	12.5	M5	7	60	4,000	3,900	6	54	1.26
EGR20T	20	15.5	M6	9	60	4,000	3,900	7	53	2.15
EGR25T	23	18.0	M6	10	60	4,000	3,900	8	52	2.79
EGR30T	28	23.0	M8	14	80	4,000	3,920	9	71	4.42
EGR35T	34	27.5	M8	17	80	4,000	3,920	9	71	6.34

Note:

1. The tolerance for E is +0.5 to -1 mm for standard rails and 0 to -0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

3.2.10.4 Calculating the length of rails

HIWIN offers rails in customised lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2}$ min and $E_{1/2}$ max so that the mounting hole does not rupture.



F 3.4

$$L = (n - 1) \times P + E_1 + E_2$$

- L Total length of the rail [mm]
n Number of mounting holes
P Distance between two mounting holes [mm]
 $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

3.2.10.5 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.

Table 3.32 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
EG_15	M3 × 16	2	EG_30	M6 × 25	13
EG_15U	M4 × 16	4	EG_30U	M8 × 25	30
EG_20	M5 × 16	9	EG_35	M8 × 25	30
EG_25	M6 × 20	13			

Linear Guideways

EG/QE series

3.2.10.6 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail. Optional cover caps must be ordered separately.



Table 3.33 Cover caps for mounting holes of rails

Rail	Screw	Article number			Ø D [mm]	Height H [mm]
		Plastic	Brass	Steel		
EGR15R	M3	C3	C3-B	—	6.0	1.2
EGR20R	M5	C5	C5-B	C5-ST	9.5	2.2
EGR25R	M6	C6	C6-B	C6-ST	11.0	2.5
EGR30R	M6	C6	C6-B	C6-ST	11.0	2.5
EGR35R	M8	C8	C8-B	C8-ST	14.0	3.3
EGR15U	M4	C4	C4-B	—	7.5	1.1
EGR30U	M8	C8	C8-B	C8-ST	14.0	3.3

Linear Guideways

EG/QE series

3.2.11 Sealing systems

Various sealing systems are available for HIWIN blocks. You will find an overview in [chapter 2.9](#). The table below shows the total length of the blocks with the different sealing systems. Sealing systems suitable for these sizes are available.





Table 3.34 Total length of blocks with different sealing systems

Series/ size	Total length L			
	SS	DD	ZZ	KK
EG_15S	40.1	44.1	41.7	45.7
QE_15S	40.1	44.1	42.1	46.1
EG_15C	56.8	60.8	58.4	62.4
QE_15C	56.8	60.8	58.8	62.8
EG_20S	50.0	54.0	51.6	55.6
QE_20S	50.0	54.0	52.0	56.0
EG_20C	69.1	73.1	70.7	74.7
QE_20C	69.1	73.1	71.1	75.1
EG_25S	59.1	63.1	61.1	65.1
QE_25S	60.1	65.1	62.1	67.1
EG_25C	82.6	86.6	84.6	88.6
QE_25C	83.6	88.6	85.6	90.6
EG_30S	69.5	73.5	71.5	75.5
QE_30S	67.5	72.5	69.5	74.5
EG_30C	98.1	102.1	100.1	104.1
QE_30C	96.1	101.1	98.1	103.1
EG_35S	75.0	79.0	78.0	82.0
QE_35S	76.0	80.0	79.0	83.0
EG_35C	108.0	112.0	111.0	115.0
QE_35C	108.0	112.0	111.0	115.0

Unit: mm

3.2.11.1 Designation of sealing sets

The sealing sets are always supplied along with the assembly material and include the parts needed in addition to the standard seal.



Linear Guideways

EG/QE series

3.2.12 Friction

The table shows the maximum frictional resistance of the individual end seal.
Depending on sealing setup (SS, ZZ, DD, KK), the value may have to be multiplied. The values indicated apply to blocks on uncoated rails. Higher friction forces occur on coated rails.

Table 3.35 Frictional resistance of single-lipped seals

Series/size	Friction force [N]	Series/size	Friction force [N]
EG_15	1.0	QE_15	1.1
EG_20	1.0	QE_20	1.4
EG_25	1.0	QE_25	1.7
EG_30	1.5	QE_30	2.1
EG_35	2.0	QE_35	2.3

3.2.13 Lubrication unit E2

You will find more information about the lubrication unit in the general information in the lubrication unit E2 Section ["2.6.3 Oil lubrication unit E2"](#).




Table 3.36 Dimensions of block with lubrication unit E2

Model	Dimensions of the block [mm]								Oil quantity [cm ³]	Mileage ²⁾ [km]
	W	H	T	V	L _{SS} ¹⁾	L _{ZZ} ¹⁾	L _{DD} ¹⁾	L _{KK} ¹⁾		
EG_15S	33.3	18.7	11.5	3.0	54.6	56.2	58.6	60.2	1.7	2,000
EG_15C	33.3	18.7	11.5	3.0	71.3	72.9	75.3	76.9	1.7	2,000
EG_20S	41.3	20.9	13.0	3.0	66.0	67.6	70.0	71.6	2.9	3,000
EG_20C	41.3	20.9	13.0	3.0	85.1	86.7	89.1	90.7	2.9	3,000
EG_25S	47.3	24.9	13.0	3.0	75.1	77.1	79.1	81.1	4.8	5,000
EG_25C	47.3	24.9	13.0	3.0	98.6	100.6	102.6	104.6	4.8	5,000
EG_30S	59.3	31.0	13.0	3.0	85.5	87.5	89.5	91.5	8.9	9,000
EG_30C	59.3	31.0	13.0	3.0	114.1	116.1	118.1	120.1	8.9	9,000

¹⁾ Total length depending on selected dust protection. SS = Standard dust protection


²⁾ Mileage at which the oil tank level should be checked at the very latest

Linear Guideways

EG/QE series

3.2.14 Tolerances depending on accuracy class

The EG and QE series are available in five accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.



3.2.14.1 Parallelism

Parallelism of stop surfaces D and B of block and rail and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.

Table 3.37 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class				
	C	H	P	SP	UP
– 100	12	7	3	2	2
100 – 200	14	9	4	2	2
200 – 300	15	10	5	3	2
300 – 500	17	12	6	3	2
500 – 700	20	13	7	4	2
700 – 900	22	15	8	5	3
900 – 1100	24	16	9	6	3
1100 – 1500	26	18	11	7	4
1500 – 1900	28	20	13	8	4
1900 – 2500	31	22	15	10	5
2500 – 3100	33	25	18	11	6
3100 – 3600	36	27	20	14	7
3600 – 4000	37	28	21	15	7

Unit: μm

Linear Guideways

EG/QE series

3.2.14.2 Accuracy – height and width

Height tolerance H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position.

Width tolerance N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.38 Height and width tolerances of non-interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
EG_15, 20 QE_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	0 – 0.03	0 – 0.03	0.006	0.006
	SP (Super precision)	0 – 0.015	0 – 0.015	0.004	0.004
	UP (Ultra precision)	0 – 0.008	0 – 0.008	0.003	0.003
EG_25, 30, 35 QE_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	0 – 0.04	0 – 0.04	0.007	0.007
	SP (Super precision)	0 – 0.02	0 – 0.02	0.005	0.005
	UP (Ultra precision)	0 – 0.01	0 – 0.01	0.003	0.003

Unit: mm

Table 3.39 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
EG_15, 20 QE_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	± 0.015	± 0.015	0.006	0.006
EG_25, 30, 35 QE_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	± 0.02	± 0.02	0.007	0.007

Unit: mm

Linear Guideways

EG/QE series

3.2.14.3 Permissible mounting surface tolerances

Once the requirements relating to the accuracy of the mounting surfaces are met, the good accuracy, rigidity and lifetime of the EG and QE series linear guideways are achieved.

Parallelism of the reference surface (P):




Table 3.40 Maximum tolerance for parallelism (P)

Series/size	Preload class		
	Z0	ZA	ZB
EG/QE_15	25	18	—
EG/QE_20	25	20	18
EG/QE_25	30	22	20
EG/QE_30	40	30	27
EG/QE_35	50	35	30

Unit: μm

Table 3.41 Maximum height tolerance of reference surface (S_1)

Series/size	Preload class		
	Z0	ZA	ZB
EG/QE_15	130	85	—
EG/QE_20	130	85	50
EG/QE_25	130	85	70
EG/QE_30	170	110	90
EG/QE_35	210	150	120

Unit: μm

3.2.15 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.42 Shoulder heights and fillets

Series/size	Max. edge radius r_1	Max. edge radius r_2	Shoulder height of reference edge of rail E_1	Shoulder height of reference edge of block E_2	Clearance under block H_1
EG/QE_15	0.5	0.5	2.7	5.0	4.5
EG/QE_20	0.5	0.5	5.0	7.0	6.0
EG/QE_25	1.0	1.0	5.0	7.5	7.0
EG/QE_30	1.0	1.0	7.0	7.0	10.0
EG_35	1.0	1.0	7.5	9.5	11.0
QE_35	1.0	1.5	7.5	9.5	11.0

Unit: mm

CG series

The HIWIN linear guideways of the CG series guarantee high torque loading capacity, easy mounting, better protection against entry of dust and against wear of the end seal due to cover strip.

01

WWW.HIWIN.CZ

Linear Guideways

CG series

3.3 CG series

3.3.1 Properties of the linear guideways, series CG

The HIWIN linear guideways of the CG series with O-arrangement of the ball tracks guarantee high torque loading capacity, especially in the M_x direction. The modified track geometry ensures high load ratings. The new flexible end seal automatically adjusts itself to the rail contour and ensures a high, permanent dust protection. To protect the end seal against mechanical damage, the CG series is equipped with a sheet metal scraper in front of the end seal as standard.


3.3.2 Design of the CG series

Free of play 4-row recirculation ball bearing guide with best dust protection already in the standard version.

Optionally, a cover strip is available – the entry of dust and wear of the sealing lip are thus permanently reduced to a minimum. With the help of a mounting tool the cover strip is installed in a few easy steps.

For optimum lubricant distribution the block has an additional lubrication path which leads the lubricant into the middle of the carrying zone. This ensures long relubrication intervals and a significant advantage especially in short stroke applications.



Easy mounting, better protection against entry of dust and against wear of the end seal due to cover strip.



Optimized lubrication concept for long relubrication intervals and short stroke applications.



O-arrangement and optimized geometry of ball bearing guide for high torque loading capacity and high load ratings.



Advantages:

- Free of play
- Interchangeable
- High accuracy
- High torque loading capacity, especially rolling moment M_x
- Optional with cover strip

3.3.3 Order codes for the CG series

For CG linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. Block and rail can be ordered separately and fitted by the customer. Their accuracy extends to class P.


Given their stringent dimensional accuracy check, the interchangeable models are a good choice for customers who do not use rails in pairs on one axis. Non-interchangeable linear guideways are always supplied preassembled. The order codes of the series include the dimensions, model, accuracy class, preload etc.

Linear Guideways

CG series


Non-interchangeable models (custom-assembled)

○ Order code for the fully assembled linear guideway




Interchangeable models

○ Order code for CG block



○ Order code for CG rail



Note:

¹⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails.
By default multi-part rails are delivered with staggered butt joints.

²⁾ You will find an overview of the individual sealing systems in [chapter 2.9](#)



Linear Guideways

CG series

3.3.4 Block types


HIWIN provides square and flange blocks for its linear guideways. Given their low height and larger mounting surface, flange blocks are better suited to large loads.

Table 3.43 **Block types**

Type	Series/ size	Structure	Height [mm]	Rail length [mm]	Typical application
Square type	CGH-CA CGH-HA		28 – 70	250 – 4,000	<ul style="list-style-type: none"> Woodworking Machining centres NC lathes Grinding machines Precision milling machines High-performance cutting machines Automation technology Transport technology Measuring technology Machines and equipment requiring high positioning accuracy
Flange type	CGW-CA CGW-HA		24 – 60		

3.3.5 Rail types


Table 3.44 **Rail types**

Fastening from above

CGR_R

3.3.6 Preload

Definition

Every rail type can be preloaded based on the size of the balls. The curve shows that the rigidity doubles at higher preload. The CG series offers three standard preload classes for various applications and conditions.



Linear Guideways

CG series

Preload ID

Table 3.45 Preload ID

ID	Preload		Application	Sample applications
Z0	Light preload	0 – 0.02 C _{dyn}	Constant load direction, little vibration, lower accuracy needed	<ul style="list-style-type: none"> Transport technology Automatic packaging machines X-Y axis in industrial machines Welding machines
ZA	Medium preload	0.05 – 0.07 C _{dyn}	High accuracy needed	<ul style="list-style-type: none"> Machining centres Z axes for industrial machines Eroding machines NC lathes Precision X-Y tables Measuring technology
ZB	High preload	above 0.1 C _{dyn}	High rigidity needed, vibration and impact	<ul style="list-style-type: none"> Machining centres Grinding machines NC lathes Horizontal and vertical milling machines Z axis of machine tools High-performance cutting machines

3.3.7 Load ratings and torques




Table 3.46 Load ratings and torques for series CG

Series/size	Dynamic load rating C _{dyn} [N] ¹⁾	Static load rating C ₀ [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M _x	M _y	M _z	M _{rx}	M _{ry}	M _{rz}
CG_20C	23,700	30,510	287.4	217.5	217.5	370	280	280
CG_25C	34,960	43,940	477.4	389.9	389.9	600	490	490
CG_30C	46,000	55,190	791.8	583.4	583.4	950	700	700
CG_35C	61,170	79,300	1,334.5	840.8	840.8	1,730	1,090	1,090

¹⁾ Dynamic load rating for travel distance of 50,000 m

3.3.8 Rigidity

Rigidity depends on preload. Formula F 3.5 can be used to determine deformation depending on rigidity.

F 3.5

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/μm]

Table 3.47 Radial rigidity for series CG

Load class	Series/ size	Rigidity depending on preload		
		Z0	ZA	ZB
Heavy load	CG_20C	271	415	483
	CG_25C	338	440	574
	CG_30C	447	553	757
	CG_35C	468	610	800

Unit: N/μm

Linear Guideways

CG series

3.3.9 Dimensions of the CG blocks

3.3.9.1 CGH




Table 3.48 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]								T	Load ratings [N]	
	H	H ₁	N	W	B	B ₁	C	L ₁	L	G	M × l		C _{dyn}	C ₀
CGH15CA ¹⁾	28	4.1	9.5	34	26	4.0	26	39.2	58.2	6.0	M4 × 5	6.0	13,800	18,020
CGH15HA ¹⁾							26	53.6	72.6				17,600	25,530
CGH20CA	30	4.6	12.0	44	32	6.0	36	52.5	74.9	6.0	M5 × 6	8.0	23,700	30,510
CGH20HA ¹⁾							50	68.5	90.9				28,600	39,900
CGH25CA	40	6.1	12.5	48	35	6.5	35	61.0	84.0	12.0	M6 × 8	8.0	34,960	43,940
CGH25HA ¹⁾							50	78.6	104.6				42,180	57,460
CGH30CA	45	7.0	16.0	60	40	10.0	40	69.0	97.4	12.0	M8 × 10	9.5	46,000	55,190
CGH30HA ¹⁾							60	92.3	118.9				58,590	78,180
CGH35CA	55	7.6	18.0	70	50	10.0	50	79.0	111.4	12.0	M8 × 13	10.2	61,170	79,300
CGH35HA ¹⁾							72	105.0	137.4				77,900	112,340
CGH45CA ¹⁾	70	9.7	20.5	86	60	13.0	60	97.8	137.8	12.9	M10 × 17	16.0	97,630	133,000
CGH45HA ¹⁾							80	132.3	172.3				124,430	217,200

¹⁾ Availability on request

For dimensions of rail, see [chapter 3.3.10](#) for standard and optional lubrication adapter, see [chapter 4.1](#)

Linear Guideways

CG series

3.3.9.2 CGW




Table 3.49 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]										Load ratings [N]	
	H	H ₁	N	W	B	B ₁	C	C ₁	L ₁	L	G	M	T	C _{dyn}	C _n
CGW15CC ¹⁾	24	4.1	16.0	47	38	4.5	30	26	39.2	58.2	6.0	M5	6.0	13,800	18,020
CGW15HC ¹⁾									53.6	72.6				17,600	25,530
CGW20CC	30	4.6	21.5	63	53	5.0	40	35	52.5	74.9	6.0	M6	6.5	23,700	30,510
CGW20HC ¹⁾									68.5	90.9				28,600	39,900
CGW25CC	36	6.1	23.5	70	57	6.5	45	40	61.0	84.0	12.0	M8	7.0	34,960	43,940
CGW25HC ¹⁾									78.6	104.6				42,180	57,460
CGW30CC	42	7.0	31.0	90	72	9.0	52	44	69.0	97.4	12.0	M10	10.5	46,000	55,190
CGW30HC ¹⁾									92.3	118.9				58,590	78,180
CGW35CC	48	7.6	33.0	100	82	9.0	62	52	79.0	111.4	12.0	M10	10.1	61,170	79,300
CGW35HC ¹⁾									105.0	137.4				77,900	112,340
CGW45CC ¹⁾	60	9.7	37.5	120	100	10.0	80	60	97.8	137.8	12.9	M12	15.1	97,630	133,000
CGW45HC ¹⁾									132.3	172.3				124,430	217,200

¹⁾ Availability on request

For dimensions of rail, see [chapter 3.3.10](#) for standard and optional lubrication adapter, see [chapter 4.1](#)

Linear Guideways

CG series

3.3.10 Dimensions of the CG rail

3.3.10.1 Dimensions of rail CGR_R




Table 3.50 Dimensions of rail CGR_R

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]
		W_R	H_R	D	h	d	P				
CGR15R ¹⁾	M4 × 16	15	16.2	7.5	5.3	4.5	60	4,000	3,900	6	54
CGR20R	M5 × 20	20	20.6	9.5	8.5	6.0	60	4,000	3,900	7	53
CGR25R	M6 × 22	23	24.3	11.0	9.0	7.0	60	4,000	3,900	8	52
CGR30R	M8 × 25	28	28.4	14.0	12.4	9.0	80	4,000	3,920	9	71
CGR35R	M8 × 30	34	31.9	14.0	12.0	9.0	80	4,000	3,920	9	71
CGR45R ¹⁾	M12 × 35	45	39.9	20.0	17.0	14.0	105	4,000	3,885	12	93


¹⁾ Availability on request

Note:

1. The tolerance for E is +0.5 to -1 mm for standard rails and 0 to -0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

3.3.10.2 Calculating the length of rails

HIWIN offers rails in customized lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2}$ min and $E_{1/2}$ max so that the mounting hole does not rupture.


F 3.6

$$L = (n - 1) \times P + E_1 + E_2$$

- L** Total length of the rail [mm]
n Number of mounting holes
P Distance between two mounting holes [mm]
 $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

Linear Guideways

CG series

3.3.10.3 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.

Table 3.51 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
CG_15	M4 × 16	4	CG_30	M10	70
CG_20	M5 × 16	9	CG_35	M8 × 25	30
CG_25	M6 × 20	13	CG_35	M10	70
CG_30	M8 × 25	30	CG_45	M12 × 35	120

3.3.10.4 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail. Optional cover caps must be ordered separately.



Table 3.52 Cover caps for mounting holes of rails

Rail	Screw	Article number			Ø D [mm]	Height H [mm]
		Plastic	Brass	Steel		
CGR15R	M4	5-001342	5-001344	—	7.5	1.1
CGR20R	M5	5-001348	5-001350	5-001352	9.5	2.2
CGR25R	M6	5-001353	5-001355	5-001357	11.0	2.5
CGR30R	M8	5-001358	5-001360	5-001362	14.0	3.3
CGR35R	M8	5-001358	5-001360	5-001362	14.0	3.3
CGR45R	M12	5-001322	5-001324	5-001327	20.0	4.6

3.3.11 Sealing systems

Various sealing systems are available for HIWIN blocks. You will find an overview in chapter 2.9. The table below shows the total length of the blocks with the different sealing systems. Sealing systems suitable for these sizes are available.




Table 3.53 Total length of blocks with different sealing systems

Series/size	Total length L			
	SS	ZZ	SW	ZWX
CG_20C	74.9	77.9	77.7	80.7
CG_25C	84.0	87.0	86.8	89.8
CG_30C	97.4	100.4	100.2	103.2
CG_35C	111.4	114.4	114.2	117.2


Unit: mm

Linear Guideways

CG series

3.3.12 Tolerances depending on accuracy class

The CG series is available in five accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.



3.3.12.1 Parallelism

Parallelism of stop surfaces D and B of block and rail and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.

Table 3.54 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class				
	C	H	P	SP	UP
– 100	12	7	3	2	2
100 – 200	14	9	4	2	2
200 – 300	15	10	5	3	2
300 – 500	17	12	6	3	2
500 – 700	20	13	7	4	2
700 – 900	22	15	8	5	3
900 – 1100	24	16	9	6	3
1100 – 1500	26	18	11	7	4
1500 – 1900	28	20	13	8	4
1900 – 2500	31	22	15	10	5
2500 – 3100	33	25	18	11	6
3100 – 3600	36	27	20	14	7
3600 – 4000	37	28	21	15	7

Unit: μm

Linear Guideways

CG series

3.3.12.2 Accuracy – height and width

Height tolerance of H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position.

Width tolerance of N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.55 Height and width tolerances of non-interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
CG_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	0 – 0.03	0 – 0.03	0.006	0.006
	SP (Super precision)	0 – 0.015	0 – 0.015	0.004	0.004
	UP (Ultra precision)	0 – 0.008	0 – 0.008	0.003	0.003
CG_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	0 – 0.04	0 – 0.04	0.007	0.007
	SP (Super precision)	0 – 0.02	0 – 0.02	0.005	0.005
	UP (Ultra precision)	0 – 0.01	0 – 0.01	0.003	0.003
CG_45	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	0 – 0.05	0 – 0.05	0.007	0.01
	SP (Super precision)	0 – 0.03	0 – 0.03	0.005	0.007
	UP (Ultra precision)	0 – 0.02	0 – 0.02	0.003	0.005

Unit: mm

Table 3.56 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
CG_15, 20	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	± 0.015	± 0.015	0.006	0.006
CG_25, 30, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	± 0.02	± 0.02	0.007	0.007
CG_45	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	± 0.025	± 0.025	0.007	0.01

Unit: mm

Linear Guideways

CG series

3.3.12.3 Permissible mounting surface tolerances

Once the requirements relating to the accuracy of the mounting surfaces are met, the good accuracy, rigidity and lifetime of the CG series linear guideways are achieved.

Tolerance for the parallelism of the reference surface (P)




Table 3.57 Maximum tolerance for parallelism (P)

Series/size	Preload class		
	Z0	ZA	ZB
CG_20	11	7	5
CG_25	12	8	6
CG_30	14	9	7
CG_35	15	11	8

Unit: μm

Tolerance for the height of the reference surface (S_1)

F 3.7

$$S_1 = a \times K - T_H$$

S_1 Max. height tolerance [mm]
 a Distance between rails [mm]
 K Coefficient of the height tolerance
 T_H Tolerance of height H acc. to Table 3.55 and Table 3.56

Table 3.58 Coefficient of height tolerance (K)

Series/size	Preload class		
	Z0	ZA	ZB
CG_15 – CG_45	2.8×10^{-4}	1.7×10^{-4}	1.2×10^{-4}


Linear Guideways

CG series

Height tolerance of the block mounting surface

- The height tolerance of the reference surface in the parallel use of two or more blocks (S_2)

Accuracy requirement for all block-mounting reference surfaces




F 3.8 $S_2 = b \times K$

S_2 Max. height tolerance [mm]
 b Distance between blocks [mm]
 K Coefficient of the height tolerance

- The height tolerance of the reference surface in the parallel use of two or more blocks (S_3)

Accuracy requirement for all block-mounting reference surfaces



F 3.9 $S_3 = c \times K$

S_3 Max. height tolerance [mm]
 c Distance between blocks [mm]
 K Coefficient of the height tolerance

Table 3.59 Coefficient of height tolerance (K)

Series/size	Load type	
	CG_C	CG_H
CG_15 – CG_45	4.2×10^{-5}	3.0×10^{-5}

Linear Guideways

CG series

3.3.13 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.60 Shoulder heights and fillets

Series/size	Max. edge radius r	Shoulder height of reference edge of rail E_1	Shoulder height of reference edge of block E_2	Clearance under block H_1
CG_15	0.5	3.0	4.0	4.1
CG_20	0.5	3.5	5.0	4.6
CG_25	1.0	5.0	5.0	6.1
CG_30	1.0	5.0	5.0	7.0
CG_35	1.0	6.0	6.0	7.6
CG_45	1.0	8.0	8.0	9.7

Unit: mm

WE/QW series

The large rail width and low installation height of the WE (standard) and QW (with SynchMotion™ technology) series permit a compact design and high torque loading capacity.

01

Linear Guideways WE/QW series

3.4 WE/QW series

3.4.1 Properties of the linear guideway, series WE and QW

The HIWIN linear guideways of the WE series are based on proven HIWIN technology. Their large rail width and low installation height permit a compact design and high torque loading capacity.


3.4.2 Structure of the WE/QW series

- 4-row recirculation ball bearing guide
- 45° contact angle
- Ball retainers prevent the balls from falling out when the block is removed
- Low installation height
- Wide linear guideway for high torque loading capacity
- Large mounting surface on block
- SynchMotion™ technology (QW series)


Advantages:

- Compact and low-cost design thanks to high torque loading capacity
- High efficiency thanks to low friction losses



50% wider than standard series



- The block's large mounting surface supports the transfer of higher torques
- The 45° arrangement of ball tracks permits high loading from all directions




- Optimized geometry and high loading capacity thanks to FEM analysis of rail and block



The models of the QW series with SynchMotion™ technology offer all the advantages of the standard series WE. Controlled movement of the balls at a defined distance also results in improved synchronous performance, higher reliable travel speeds, extended lubrication intervals and less running noise. Since the installation dimensions of the QW blocks are identical to those of the WE blocks, they are also fitted on the WER standard rail and can therefore be interchanged with ease.



Design of the WE series



Design of the QW series

Linear Guideways

WE/QW series


3.4.3 Order codes for the WE/QW series

For WE/QW linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. Block and rail can therefore be ordered separately and fitted by the customer.

Their accuracy extends to class P. Given their stringent dimensional accuracy check, the interchangeable modules are a good choice for customers who do not use rails in pairs on one axis. Non-interchangeable linear guideways are always supplied preassembled. The order codes of the series include the dimensions, model, accuracy class, preload etc.


Non-interchangeable models (custom-assembled)

- Item number of the fully assembled linear guideway




Interchangeable models

- Order code for WE/QW block



- Order code for WE rail



Note:

¹⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails.

By default multi-part rails are delivered with staggered butt joints.



²⁾ You will find an overview of the individual sealing systems in [chapter 2.9](#)

Linear Guideways WE/QW series

3.4.4 Block types

HIWIN provides square and flange blocks for its linear guideways. Given their low height and larger mounting surface, flange blocks are better suited for large loads.


Table 3.61 Block types

Type	Series/ Size	Structure	Height [mm]	Rail length [mm]	Typical application
Square type	WEH-CA QWH-CA		17 – 50	100 – 4.000	<ul style="list-style-type: none"> Automation Handling industry Measuring and test technology Semiconductor industry Injection moulding machines Linear axes
Flange type	WEW-CC QWW-CC				

3.4.5 Preload

Definition

Every rail type can be preloaded based on the size of the balls. The curve shows that the rigidity doubles at higher preload. The WE series offers three standard preload classes for various applications and conditions.



Preload ID

Table 3.62 Preload ID

ID	Preload		Application	Sample applications
Z0	Light preload	$0 - 0.02 C_{dyn}$	Constant load direction, low impact, low accuracy needed	<ul style="list-style-type: none"> Transport technology Automatic packaging machines X-Y axis in industrial machines Welding machines
ZA	Medium preload	$0.03 - 0.05 C_{dyn}$	High accuracy needed	<ul style="list-style-type: none"> Machining centres Z axes for industrial machines Eroding machines NC lathes Precision X-Y tables Measuring technology
ZB	High preload	$0.06 - 0.08 C_{dyn}$	High rigidity needed, vibration and impact	<ul style="list-style-type: none"> Machining centres Grinding machines NC lathes Horizontal and vertical milling machines Z axis of machine tools High-performance cutting machines

Linear Guideways

WE/QW series

3.4.6 Load ratings and torques




Table 3.63 Load ratings and torques for series WE/QW

Series/ size	Dynamic load rating C_{dyn} [N] ¹⁾	Static load rating C_0 [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M_x	M_y	M_z	M_{0x}	M_{0y}	M_{0z}
WE_17C	5,230	9,640	82	34	34	150	62	62
WE_21C	7,210	13,700	122	53	53	230	100	100
QW_21C	9,000	12,100	156	67	67	210	90	90
WE_27C	12,400	21,600	242	98	98	420	170	170
QW_27C	16,000	22,200	303	144	144	420	200	200
WE_35C	29,800	49,400	893	405	405	1,480	670	670
QW_35C	36,800	49,200	1,129	486	486	1,510	650	650
WE_50C	61,520	97,000	2,556	1,244	1,244	4,030	1,960	1,960

¹⁾ Dynamic load rating for travel distance of 50,000 m

3.4.7 Rigidity

Rigidity depends on preload. Formula F 3.5 can be used to determine deformation depending on rigidity.

F 3.10

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/ μm]

Table 3.64 Radial rigidity for series WE

Load class	Series/ size	Rigidity depending on preload		
		Z0	ZA	ZB
Heavy load	WE_17C	128	166	189
	WE_21C	154	199	228
	QW_21C	140	176	200
	WE_27C	187	242	276
	QW_27C	183	229	260
	WE_35C	281	364	416
	QW_35C	277	348	395
	WE_50C	428	554	633

Unit: N/ μm

Linear Guideways WE/QW series

3.4.8 Dimensions of the WE/QW blocks

3.4.8.1 WEH/QWH




Table 3.65 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]														Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M × l	T	H ₂	H ₃	C _{dyn}	C ₀		
WEH17CA	17	2.5	8.5	50	29	10.5	15	35.0	50.6	—	3.10	4.9	M4 × 5	6.0	4.0	3.0	5,230	9,640	0.12	
WEH21CA	21	3.0	8.5	54	31	11.5	19	41.7	59.0	14.68	3.65	12.0	M5 × 6	8.0	4.5	4.2	7,210	13,700	0.20	
QWH21CA	21	3.0	8.5	54	31	11.5	19	41.7	59.0	14.68	3.65	12.0	M5 × 6	8.0	4.5	4.2	9,000	12,100	0.20	
WEH27CA	27	4.0	10.0	62	46	8.0	32	51.8	72.8	14.15	3.50	12.0	M6 × 6	10.0	6.0	5.0	12,400	21,600	0.35	
QWH27CA	27	4.0	10.0	62	46	8.0	32	56.6	73.2	15.45	3.15	12.0	M6 × 6	10.0	6.0	5.0	16,000	22,200	0.35	
WEH35CA	35	4.0	15.5	100	76	12.0	50	77.6	102.6	18.35	5.25	12.0	M8 × 8	13.0	8.0	6.5	29,800	49,400	1.10	
QWH35CA	35	4.0	15.5	100	76	12.0	50	73.0	107.0	21.5	5.50	12.0	M8 × 8	13.0	8.0	6.5	36,800	49,200	1.10	
WEH50CA	50	7.5	20.0	130	100	15.0	65	112.0	140.0	28.05	6.00	12.9	M10 × 15	19.5	12.0	10.5	61,520	97,000	3.16	

For dimensions of rail, see [chapter 3.4.9](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways WE/QW series

3.4.8.2 WEW




Table 3.66 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]															Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M	T	T ₁	H ₂	H ₃	C _{dyn}	C ₀		
WEW17CC	17	2.5	13.5	60	53	3.5	26	35.0	50.6	—	3.10	4.9	M4	5.3	6	4.0	3.0	5,230	9,640	0.13	
WEW21CC	21	3.0	15.5	68	60	4.0	29	41.7	59.0	9.68	3.65	12.0	M5	7.3	8	4.5	4.2	7,210	13,700	0.23	
QWW21CC	21	3.0	15.5	68	60	4.0	29	41.7	59.0	9.68	3.65	12.0	M5	7.3	8	4.5	4.2	9,000	12,100	0.23	
WEW27CC	27	4.0	19.0	80	70	5.0	40	51.8	72.8	10.15	3.50	12.0	M6	8.0	10	6.0	5.0	12,400	21,600	0.43	
QWW27CC	27	4.0	19.0	80	70	5.0	40	56.6	73.2	15.45	3.15	12.0	M6	8.0	10	6.0	5.0	16,000	22,200	0.43	
WEW35CC	35	4.0	25.5	120	107	6.5	60	77.6	102.6	13.35	5.25	12.0	M8	11.2	14	8.0	6.5	29,800	49,400	1.26	
QWW35CC	35	4.0	25.5	120	107	6.5	60	83.0	107.0	21.50	5.50	12.0	M8	11.2	14	8.0	6.5	36,800	49,200	1.26	
WEW50CC	50	7.5	36.0	162	144	9.0	80	112.0	140.0	20.55	6.00	12.9	M10	14.0	18	12.0	10.5	61,520	97,000	3.71	

For dimensions of rail, see [chapter 3.4.9](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways

WE/QW series

3.4.9 Dimensions of the WE rail

3.4.9.1 Dimensions of WER_R




Table 3.67 Dimensions of rail WER_R


Series/ size	Assembly screw for rail [mm]	Dimensions of the rail [mm]							Max. length [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	W_B	H_R	D	h	d	P				
WER17R	M4 × 12	33	18	9.3	7.5	5.3	4.5	40	4,000	6	34	2.2
WER21R	M4 × 12	37	22	11.0	7.5	5.3	4.5	50	4,000	6	44	3.0
WER27R	M4 × 16	42	24	15.0	7.5	5.3	4.5	60	4,000	6	54	4.7
WER35R	M6 × 20	69	40	19.0	11.0	9.0	7.0	80	4,000	8	72	9.7
WER50R	M8 × 25	90	60	24.0	14.0	12.0	9.0	80	4,000	9	71	14.6

Note:

1. The tolerance for E is +0.5 to – 1 mm for standard rails and 0 to –0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

3.4.9.2 Calculating the length of rails

HIWIN offers rails in customized lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2}$ min and $E_{1/2}$ max so that the mounting hole does not rupture.



F 3.11

$$L = (n - 1) \times P + E_1 + E_2$$

- L Total length of the rail [mm]
- n Number of mounting holes
- P Distance between two mounting holes [mm]
- $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

Linear Guideways

WE/QW series

3.4.9.3 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts compromises the function and precision of the linear guideways. The following tightening torques are recommended for the screw sizes.

Table 3.68 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
WE_17	M4	4	WE/QW_35	M6	13
WE/QW_21	M4	4	WE_50	M	30
WE/QW_27	M4	4			

3.4.9.4 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail. Optional cover caps must be ordered separately.




Table 3.69 Cover caps for mounting holes of rails

Rail	Screw	Article number			Ø D [mm]	Height H [mm]
		Plastic	Brass	Steel		
WER17R	M4	C4	C4-M	—	7.5	1.1
WER21R	M4	C4	C4-M	—	7.5	1.1
WER27R	M4	C4	C4-M	—	7.5	1.1
WER35R	M6	C6	C6-M	C6-ST	11.0	2.5
WER50R	M8	C8	C8-M	C8-ST	14.0	3.3

3.4.10 Sealing systems

Various sealing systems are available for HIWIN blocks. You will find an overview in chapter 2.9. The table below shows the total length of the blocks with the different sealing systems. Sealing systems suitable for these sizes are available.




Table 3.70 Total length of block with different sealing systems

Series/size	Total length L			
	SS	DD	ZZ	KK
WE_17C	50.6	53.8	52.6	55.8
WE/QW_21C	59.0	63.0	61.0	65.0
WE/QW_27C	72.8	76.8	74.8	78.8
WE/QW_35C	102.6	106.6	105.6	109.6
WE_50C	140.0	145.0	142.0	147.0


Unit: mm

Linear Guideways

WE/QW series

3.4.11 Designation of sealing sets

The sealing sets are always supplied along with the assembly material and include the parts needed in addition to the standard seal.



3.4.12 Friction

The table shows the maximum frictional resistance of the individual end seal. Depending on sealing setup (SS, ZZ, DD, KK), the value may have to be multiplied. The values indicated apply to blocks on uncoated rails. Higher friction forces occur on coated rails.

Table 3.71 Frictional resistance of single-lipped seals


Series/size	Friction force [N]	Series/size	Friction force [N]
WE_17	1,2	WE/QW_35	3,9
WE/QW_21	2,0	WE_50	3,9
WE/QW_27	2,9		

Linear Guideways

WE/QW series

3.4.13 Tolerances depending on accuracy class

The WE series are available in five accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.



3.4.14 Parallelism

Parallelism of stop surfaces D and B of block and rail and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.

Table 3.72 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class				
	C	H	P	SP	UP
– 100	12	7	3	2	2
100 – 200	14	9	4	2	2
200 – 300	15	10	5	3	2
300 – 500	17	12	6	3	2
500 – 700	20	13	7	4	2
700 – 900	22	15	8	5	3
900 – 1100	24	16	9	6	3
1100 – 1500	26	18	11	7	4
1500 – 1900	28	20	13	8	4
1900 – 2500	31	22	15	10	5
2500 – 3100	33	25	18	11	6
3100 – 3600	36	27	20	14	7
3600 – 4000	37	28	21	15	7

Unit: μm

Linear Guideways

WE/QW series

3.4.14.1 Accuracy – height and width

Height tolerance H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Width tolerance N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position.

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.73 Height and width tolerances of non-interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
WE_17, 21 QW_21	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	0 – 0.03	0 – 0.03	0.006	0.006
	SP (Super precision)	0 – 0.015	0 – 0.015	0.004	0.004
	UP (Ultra precision)	0 – 0.008	0 – 0.008	0.003	0.003
WE_27, 35 QW_27, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	0 – 0.04	0 – 0.04	0.007	0.007
	SP (Super precision)	0 – 0.02	0 – 0.02	0.005	0.005
	UP (Ultra precision)	0 – 0.01	0 – 0.01	0.003	0.003
WE_50	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.02	0.02
	P (Precision)	0 – 0.05	0 – 0.05	0.01	0.01
	SP (Super precision)	0 – 0.03	0 – 0.03	0.01	0.01
	UP (Ultra precision)	0 – 0.02	0 – 0.02	0.01	0.01

Unit: mm

Table 3.74 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
WE_17, 21 QW_21	C (Normal)	± 0.1	± 0.1	0.02	0.02
	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	± 0.015	± 0.015	0.006	0.006
WE_27, 35 QW_27, 35	C (Normal)	± 0.1	± 0.1	0.02	0.03
	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	± 0.02	± 0.02	0.007	0.007
WE_50	C (Normal)	± 0.1	± 0.1	0.03	0.03
	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	± 0.025	± 0.025	0.007	0.01

Unit: mm

Linear Guideways

WE/QW series

3.4.14.2 Permissible mounting surface tolerances

Once the requirements relating to the accuracy of the mounting surfaces are met, the good accuracy, rigidity and lifetime of the WE series linear guideways are achieved.

Parallelism of the reference surface (P):




Table 3.75 Maximum tolerance for parallelism (P)

Series/size	Preload class		
	Z0	ZA	ZB
WE_17	20	15	9
WE/QW_21	25	18	9
WE/QW_27	25	20	13
WE/QW_35	30	22	20
WE_50	40	30	27

Unit: μm

Table 3.76 Maximum tolerance for height of reference surface (S_1)

Series/size	Preload class		
	Z0	ZA	ZB
WE_17	65	20	—
WE/QW_21	130	85	45
WE/QW_27	130	85	45
WE/QW_35	130	85	70
WE_50	170	110	90

Unit: mm

3.4.15 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.77 Shoulder heights and fillets

Series/size	Max. edge radius r_1	Max. edge radius r_2	Shoulder height of reference edge of rail E_1	Shoulder height of reference edge of block E_2	Clearance under block H_1
WE_17	0.4	0.4	2.0	4.0	2.5
WE/QW_21	0.4	0.4	2.5	5.0	3.0
WE/QW_27	0.5	0.4	3.0	7.0	4.0
WE/QW_35	0.5	0.5	3.5	10.0	4.0
WE_50	0.8	0.8	6.0	10.0	7.5

Unit: mm

MG series

The compact and lightweight design of the MG series is particularly suited to use in small devices.

01

Linear Guideways

MG series


3.5 MG series

3.5.1 Properties of the linear guideway, series MGN

The HIWIN linear guideway of the MGN series is based on proven HIWIN technology. The Gothic arch contact design absorbs loads in all directions and is particularly rigid and precise. Given its compact and lightweight design, it is particularly suited to use in small devices.

3.5.3 Structure of the MGN series

- 2-row recirculation ball bearing guide
- Gothic arch contact design
- Stainless steel block
- Rails made from standard or stainless steel
- Compact and lightweight design
- Steel balls are secured in the block by retaining wire
- Grease nipple available for MGN15
- End seal
- Bottom seal (optional for sizes 12 and 15)
- Interchangeable models are available in defined accuracy classes




Structure of the MGN series

3.5.2 Properties of the linear guideway, series MGW

The HIWIN linear guideway of the MGW series is based on proven HIWIN technology. The Gothic arch contact design absorbs loads in all directions and is particularly rigid and precise. The MGW series has a wider rail than the MGN series so can absorb considerably higher load torques.

3.5.4 Structure of the MGW series

- 2-row recirculation ball bearing guide
- Gothic arch contact design
- Stainless steel block
- Rails made from standard or stainless steel
- Compact and lightweight design
- Steel balls are secured in the block by retaining wire
- Grease nipple available for MGW15
- End seal
- Bottom seal (optional for sizes 12 and 15)
- Interchangeable models are available in defined accuracy classes



Structure of the MGW series

3.5.5 Applications of the MG series

The MGN and MGW series can be used in many sectors, e.g. in the semiconductor industry, PCB population, medical technology, robot applications, measurement devices, office automation and other sectors needing miniature guides.

Linear Guideways

MG series


3.5.6 Order codes for the MG series

For MGN and MGW linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. Block and rail can therefore be ordered separately and fitted by the customer.

Given their stringent dimensional accuracy check, the interchangeable modules are a good choice for customers who do not use rails in pairs on one axis. The order codes include the dimensions, model, accuracy class, preload etc.


Non-interchangeable models (custom-assembled)

- Order code for the fully assembled linear guideway




Interchangeable models

- Order code for MG block



- Order code for MG rail



Note:

¹⁾ Bottom seal is available for MGN and MGW series in sizes 12 and 15.

²⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails.

By default multi-part rails are delivered with staggered butt joints.

³⁾ Not available for paired rails.

Linear Guideways

MG series

3.5.7 Preload

The MGN/MGW series offers three preload classes for various applications.

Table 3.78 Preload ID

ID	Preload	Accuracy class
ZF	Slight play: 4 – 10 µm	C, H
Z0	Zero-play, very slight preload	C – P
Z1	Slight preload: 0 – 0.02 C _{dyn}	C – P

3.5.8 Load ratings and torques




Table 3.79 Load ratings and torques for MG series

Series/size	Dynamic load rating C _{dyn} [N] ¹⁾	Static load rating C ₀ [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M _x	M _y	M _z	M _{0x}	M _{0y}	M _{0z}
MGN05C	540	840	1.3	0.8	0.8	2.0	1.3	1.3
MGN05H	667	1,089	2.5	2.2	2.2	2.6	2.3	2.3
MGN07C	980	1,245	3	2	2	4.7	2.8	2.8
MGN07H	1,370	1,960	5	3	3	7.6	4.8	4.8
MGN09C	1,860	2,550	8	5	5	11.8	7.4	7.4
MGN09H	2,550	4,020	12	12	12	19.6	18.6	18.6
MGN12C	2,840	3,920	18	10	10	25.5	13.7	13.7
MGN12H	3,720	5,880	24	23	23	38.2	36.3	36.3
MGN15C	4,610	5,590	37	18	18	45.1	21.6	21.6
MGN15H	6,370	9,110	52	41	41	73.5	57.8	57.8
MGW07C	1,370	2,060	10	4	4	15.7	7.1	7.1
MGW07H	1,770	3,140	13	8	8	23.5	15.5	15.5
MGW09C	2,750	4,120	27	12	12	40.1	18.0	18.0
MGW09H	3,430	5,890	32	20	20	54.5	34.0	34.0
MGW12C	3,920	5,590	50	19	19	70.3	27.8	27.8
MGW12H	5,100	8,240	64	36	36	102.7	57.4	57.4
MGW15C	6,770	9,220	149	42	42	199.3	56.7	56.7
MGW15H	8,930	13,380	196	80	80	299.0	122.6	122.6

¹⁾ Dynamic load rating for travel distance of 50,000 m

Linear Guideways

MG series

3.5.9 Rigidity

Rigidity depends on preload. Formula [F 3.7](#) can be used to determine deformation depending on rigidity.

F 3.12

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/ μm]

Table 3.80 Radial rigidity for series MGN

Load Class	Series/ size	Preload	
		Z0	Z1
Average load	MGN07C	26	33
	MGN09C	37	48
	MGN12C	44	56
	MGN15C	57	74
High load	MGN07H	39	51
	MGN09H	56	73
	MGN12H	63	81
	MGN15H	87	113

 Unit: N/ μm

Table 3.81 Radial rigidity for series MGW

Load Class	Series/ size	Preload	
		Z0	Z1
Average load	MGN07C	38	49
	MGN09C	55	71
	MGN12C	63	81
	MGN15C	78	101
High load	MGN07H	54	70
	MGN09H	74	95
	MGN12H	89	114
	MGN15H	113	145

 Unit: N/ μm


Linear Guideways

MG series


3.5.10 Dimensions of the MG block

3.5.10.1 MGN

MGN05



MGN07, MGN09, MGN12



MGN15




Table 3.82 Dimensions of the block



Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]										Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	G	G _n	M × l	H ₂	C _{dyn}	C ₀	
MGN05C	6	1.5	3.5	12	8	2.0	—	9.6	16	—	Ø0.8	M2 × 1.5	1.0	540	840	0.008
MGN05H							—	12.6	19					667	1,089	0.010
MGN07C	8	1.5	5.0	17	12	2.5	8	13.5	22.5	—	Ø1.2	M2 × 2.5	1.5	980	1,245	0.01
MGN07H							13	21.8	30.8					1,372	1,960	0.02
MGN09C	10	2.0	5.5	20	15	2.5	10	18.9	28.9	—	Ø1.4	M3 × 3	1.8	1,860	2,550	0.02
MGN09H							16	29.9	39.9					2,550	4,020	0.03
MGN12C	13	3.0	7.5	27	20	3.5	15	21.7	34.7	—	Ø2	M3 × 3.5	2.5	2,840	3,920	0.03
MGN12H							20	32.4	45.4					3,720	5,880	0.05
MGN15C	16	4.0	8.5	32	25	3.5	20	26.7	42.1	4.5	M3	M3 × 4	3.0	4,610	5,590	0.06
MGN15H							25	43.4	58.8					6,370	9,110	0.09

For dimensions of rail, see [chapter 3.5.11](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways MG series

3.5.10.2 MGW

MGW07, MGW09, MGW12



MGW15





Table 3.83 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]										Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	G	G _n	M × l	H ₂	C _{dyn}	C ₀	
MGW07C	9	1.9	5.5	25	19	3.0	10	21.0	31.2	—	Ø 1.2	M3 × 3	1.85	1,370	2,060	0.02
MGW07H							19	30.8	41.0					1,770	3,140	0.03
MGW09C	12	2.9	6.0	30	21	4.5	12	27.5	39.3	—	Ø 1.4	M3 × 3	2.40	2,750	4,120	0.04
MGW09H							24	38.5	50.7					3,430	5,890	0.06
MGW12C	14	3.4	8.0	40	28	6.0	15	31.3	46.1	—	Ø 2	M3 × 3,6	2.80	3,920	5,590	0.07
MGW12H							28	45.6	60.4					5,100	8,240	0.10
MGW15C	16	3.4	9.0	60	45	7.5	20	38.0	54.8	5.2	M3	M4 × 4,2	3.20	6,770	9,220	0.14
MGW15H							35	57.0	73.8					8,930	13,380	0.22

For dimensions of rail, see [chapter 3.5.11](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways

MG series

3.5.11 Dimensions of the MG rail

3.5.11.1 Dimensions of MGN_R




Table 3.84 Dimensions of rail MGN_R

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	D	h	d	P					
MGNR05R	M2 × 6	5	3.6	3.6	0.8	2.4	15	250	225	4	11	0.15
MGNR07R	M2 × 6	7	4.8	4.2	2.3	2.4	15	600	585	5	12	0.22
MGNR09R	M3 × 8	9	6.5	6.0	3.5	3.5	20	1,200	1,180	5	15	0.38
MGNR12R	M3 × 8	12	8.0	6.0	4.5	3.5	25	2,000	1,975	5	20	0.65
MGNR15R	M3 × 10	15	10.0	6.0	4.5	3.5	40	2,000	1,960	6	34	1.06

3.5.11.2 Dimensions of MGW_R




Table 3.85 Dimensions of rail MGW_R

Series/ size	Screws for rail [mm]	Dimensions of the rail [mm]							Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	W_B	D	h	d	P					
MGWR07R	M3 × 6	14	5.2	—	6.0	3.2	3.5	30	600	570	6	24	0.51
MGWR09R	M3 × 8	18	7.0	—	6.0	4.5	3.5	30	1,200	1,170	6	24	0.91
MGWR12R	M4 × 8	24	8.5	—	8.0	4.5	4.5	40	2,000	1,960	8	32	1.49
MGWR15R	M4 × 10	42	9.5	23	8.0	4.5	4.5	40	2,000	1,960	8	32	2.86

Note:


1. The tolerance for E is +0.5 to -1 mm for standard rails and 0 to -0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically

Linear Guideways

MG series

3.5.11.3 Calculating the length of rails

HIWIN offers rails in customized lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2 \text{ min}}$ and $E_{1/2 \text{ max}}$ so that the mounting hole does not rupture.



F 3.13

$$L = (n - 1) \times P + E_1 + E_2$$

- L Total length of the rail [mm]
- n Number of mounting holes
- P Distance between two mounting holes [mm]
- $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

3.5.11.4 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.

Table 3.86 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
MGN05	M2 × 6	0,6	—	—	—
MGN07	M2 × 6	0,6	MGW07	M3 × 6	2
MGN09	M3 × 8	2	MGW09	M3 × 8	2
MGN12	M3 × 8	2	MGW12	M4 × 8	4
MGN15	M3 × 10	2	MGW15	M4 × 10	4

3.5.11.5 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail




Table 3.87 Cover caps for mounting holes of rails

Rail	Screw	Article number		Ø D [mm]	Height H [mm]
		Plastic	Brass		
MGNR05R	—	—	—	—	—
MGNR07R	—	—	—	—	—
MGNR09R	M3	C3 ¹⁾	C3-M ¹⁾	6	1.1
MGNR12R	M3	C3	C3-M	6	1.1
MGNR15R	M3	C3	C3-M	6	1.1
MGWR07R	—	—	—	—	—
MGWR09R	M3	C3	C3-M	6	1.1
MGWR12R	M4	C4A	—	8	1.1
MGWR15R	M4	C4A	—	8	1.1

¹⁾ Only possible with cylinder head screws with a low head according to DIN 7984

Linear Guideways

MG series

3.5.12 Dust protection

The blocks of the MG series are equipped on both sides with an end seal to protect against dirt as standard. In addition seals for the bottom of the block can be ordered using the "+U" identifier in the order code. They are available as options for sizes 12 and 15. They cannot be fitted for sizes 7 and 9 due to the limited installation space H_1 . When fitting a bottom seal, the side mounting surface of the rail must not exceed H_1 .




Table 3.88 Installation space H_1

Series/size	Bottom seal	H_1	Series/size	Bottom seal	H_1
MGN05	—	—	—	—	—
MGN07	—	—	MGW07	—	—
MGN09	—	—	MGW09	—	—
MGN12	●	2.0	MGW12	●	2.6
MGN15	●	3.0	MGW15	●	2.6

3.5.13 Friction

The table shows the maximum frictional resistance of the seals of a block.

Table 3.89 Frictional resistance for standard block

Series/size	Friction force [N]	Series/size	Friction force [N]
MGN05	0.1	—	—
MGN07	0.1	MGW07	0.2
MGN09	0.1	MGW09	0.2
MGN12	0.2	MGW12	0.3
MGN15	0.2	MGW15	0.3

Linear Guideways

MG series

3.5.14 Tolerances depending on accuracy class

The MG series are available in three accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.

3.5.14.1 Parallelism

Parallelism of stop surfaces D and B of block and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.




Table 3.90 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class		
	C	H	P
– 50	12	6	2.0
50 – 80	13	7	3.0
80 – 125	14	8	3.5
125 – 200	15	9	4.0
200 – 250	16	10	5.0
250 – 315	17	11	5.0
315 – 400	18	11	6.0
400 – 500	19	12	6.0
500 – 630	20	13	7.0
630 – 800	22	14	8.0
800 – 1000	23	16	9.0
1000 – 1200	25	18	11.0

Unit: μm

3.5.14.2 Accuracy – height and width

Height tolerance H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Width tolerance N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.91 Height and width tolerances of non-interchangeable models

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
MGN05-MG_15	C (Normal)	± 0.04	± 0.04	0.03	0.3
	H (High)	± 0.02	± 0.025	0.015	0.02
	P (Precision)	± 0.01	± 0.015	0.007	0.01

Unit: mm

Linear Guideways

MG series

Table 3.92 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N	Height variance of H ¹⁾
MGN05-MG_15	C (Normal)	± 0.04	± 0.04	0.03	0.03	0.07
	H (High)	± 0.02	± 0.025	0.015	0.02	0.04
	P (Precision)	± 0.01	± 0.015	0.007	0.01	0.02

Unit: mm

¹⁾ Permissible deviation of height H between several blocks on a pair of rails

3.5.14.3 Permissible mounting surface tolerances

Once the requirements relating to the accuracy of the mounting surfaces are met, the good accuracy, rigidity and lifetime of the MG series linear guideways are achieved.

Parallelism of the reference surface (P):




Table 3.93 Maximum tolerance for parallelism (P)

Series/size	Preload class		
	ZF	Z0	Z1
MG_05	2	2	2
MG_07	3	3	3
MG_09	4	4	3
MG_12	9	9	5
MG_15	10	10	6

Unit: µm

Table 3.94 Maximum tolerance for height of reference surface (S_r)

Series/size	Preload class		
	ZF	Z0	Z1
MG_05	20	20	2
MG_07	25	25	3
MG_09	35	35	6
MG_12	50	50	12
MG_15	60	60	20

Unit: µm

Table 3.95 Requirements for the mounting surface

Series/size	Required evenness of the mounting surface
MG_05	0.015/200
MG_07	0.025/200
MG_09	0.035/200
MG_12	0.050/200
MG_15	0.060/200

Note: The values in the table are applicable to the preload classes ZF and Z0. For Z1 or if more than one rail is to be mounted on the same surface, the table values must be at least halved.

Linear Guideways

MG series

3.5.15 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.96 Shoulder heights and fillets

Series/size	Max. edge radius r_1	Max. edge radius r_2	Shoulder height of H_1	Shoulder height of H_2
MGN05	0.1	0.2	1.2	2
MGN07	0.2	0.2	1.2	3
MGN09	0.2	0.3	1.7	3
MGN12	0.3	0.4	1.7	4
MGN15	0.5	0.5	2.5	5
MGW07	0.2	0.2	1.7	3
MGW09	0.3	0.3	2.5	3
MGW12	0.4	0.4	3.0	4
MGW15	0.4	0.8	3.0	5

Unit: mm

RG/QR series

The RG (standard) and QR (with Synch-Motion™ technology) series use rollers as rolling elements and provides extremely good rigidity and very good loading capacity.

01

Linear Guideways

RG/QR series

3.6 RG and QR series


3.6.1 Properties of the linear guideways, series RG and QR

The HIWIN linear guideways of the RG series use rollers rather than balls as rolling elements. The RG series provides extremely good rigidity and very good loading capacity. It is designed with a 45° contact angle. Its linear contact surface greatly reduces deformation from the loading produced and therefore ensures very good rigidity and loading capacity in all 4 loading directions. The linear guides of the RG series are therefore ideal for use in high-precision manufacturing.

The models of the QR series with SynchMotion™ technology offer all the positive properties of the standard series RG. Controlled movement of the rollers at a defined distance also results in improved synchronous performance, higher reliable travel speeds, extended lubrication intervals and less running noise. Since the installation dimensions of the QR blocks are identical to those of the RG blocks, they are also fitted on the RGR standard rail and can therefore be interchanged with ease.

3.6.2 Structure of the RG/QR series


- 4-row recirculation roller bearing guide
- 45° contact angle
- Various sealing variants depending on the field of application
- 6 options for connecting grease nipple and lubrication adapter
- SynchMotion™ technology (QR series)



Structure of the RG series

Advantages:

- Zero play
- Interchangeable
- Very high load ratings
- Very high rigidity
- Low displacement forces even with high preload



Structure of the QR series

Additional advantages of QR series:

- Improved synchronous performance
- Optimized for higher travel speeds
- Extended lubrication intervals
- Less running noise
- Higher dynamic load capacities

3.6.3 Order codes for the RG/QR series


For RG/QR linear guideways, a distinction is made between interchangeable and non-interchangeable models. The dimensions of both models are the same. The main difference is that the block and rail in the interchangeable models can be freely interchanged. The order codes of the series include the dimensions, model, accuracy class, preload etc.

Linear Guideways

RG/QR series


Non-interchangeable models (custom-assembled)

○ Order code for the fully assembled linear guideway




Interchangeable models

○ Order code for RG/QR block



○ Order code for RG rail



Note:

¹⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails. No number is specified for individual rails.

By default multi-part rails are delivered with staggered butt joints.

²⁾ You will find an overview of the individual sealing systems on in [chapter 2.9](#)

³⁾ Only available for RG



Linear Guideways

RG/QR series

3.6.4 Block types

HIWIN provides square and flange blocks for the linear guideways. Given their low height and large mounting surface, flange blocks are suited to large loads.

Table 3.97 Block types

Type	Series/size	Structure	Height [mm]	Rail length [mm]	Typical application
Square type	RGH-CA RGH-HA		28 – 90	100 – 4.000	<ul style="list-style-type: none"> Automation technology Transport technology CNC machining centers High-performance cutting machines CNC grinding machines Injection moulding machines Portal milling machines Machines and systems requiring high rigidity Machines and systems requiring high load rating Spark erosion machines
Flange type	RGW-CC RGW-HC		24 – 90		

3.6.5 Rail types

In addition to rails with standard fastening from above, HIWIN also provides rails for fastening from below.

Table 3.98 Rail types

Fastening from above	Fastening from below
	
RGR_R	RGR_T


Linear Guideways

RG/QR series

3.6.6 Preload

Definition

Every rail type can be preloaded based on the size of the balls. The curve shows that the rigidity doubles at higher preload. The RG/QR series offers two standard preload classes for various applications and conditions.




Preload ID

Table 3.99 Preload ID

ID	Preload		Application
ZA	Medium preload	$0.07 - 0.09 C_{dyn}$	High precision needed
ZB	High preload	$0.12 - 0.14 C_{dyn}$	Very high rigidity required, with vibration and impact

The diagram shows the relationship between rigidity, frictional resistance and nominal lifetime. For smaller models, a preload of no more than ZA is recommended to avoid the lifetime being shortened as a result of preload.



Linear Guideways

RG/QR series

3.6.7 Load ratings and torques




Table 3.100 Load ratings and torques for series RG/QR

Series/size	Dynamic load rating C_{dyn} [N] ¹⁾	Static load rating C_0 [N]	Dynamic moment [Nm]			Static moment [Nm]		
			M_x	M_y	M_z	M_{0x}	M_{0y}	M_{0z}
RG_15C	11,300	24,000	147	82	82	311	173	173
RG_20C	21,300	46,700	296	210	210	647	460	460
RG_20H	26,900	63,000	373	358	358	872	837	837
RG_25C	27,700	57,100	367	293	293	758	605	605
QR_25C	38,500	54,400	511	444	444	722	627	627
RG_25H	33,900	73,400	450	457	457	975	991	991
QR_25H	44,700	65,300	594	621	621	867	907	907
RG_30C	39,100	82,100	688	504	504	1,445	1,060	1,060
QR_30C	51,500	73,000	906	667	667	1,284	945	945
RG_30H	48,100	105,000	845	784	784	1,846	1,712	1,712
QR_30H	64,700	95,800	1,138	1,101	1,101	1,685	1,630	1,630
RG_35C	57,900	105,200	1,194	792	792	2,170	1,440	1,440
QR_35C	77,000	94,700	1,590	1,083	1,083	1,955	1,331	1,331
RG_35H	73,100	142,000	1,508	1,338	1,338	2,930	2,600	2,600
QR_35H	95,700	126,300	1,975	1,770	1,770	2,606	2,335	2,335
RG_45C	92,600	178,800	2,340	1,579	1,579	4,520	3,050	3,050
QR_45C	123,200	156,400	3,119	2,101	2,101	3,959	2,666	2,666
RG_45H	116,000	230,900	3,180	2,748	2,748	6,330	5,470	5,470
QR_45H	150,800	208,600	3,816	3,394	3,394	5,278	4,694	4,694
RG_55C	130,500	252,000	4,148	2,796	2,796	8,010	5,400	5,400
RG_55H	167,800	348,000	5,376	4,942	4,942	11,150	10,250	10,250
RG_65C	213,000	411,600	8,383	5,997	5,997	16,200	11,590	11,590
RG_65H	275,300	572,700	10,839	10,657	10,657	22,550	22,170	22,170

¹⁾ Dynamic load rating for travel distance of 100,000 m

Linear Guideways

RG/QR series

3.6.8 Rigidity

Rigidity depends on preload. Formula [F 3.10](#) can be used to determine deformation depending on rigidity.

F 3.14

$$\delta = \frac{P}{k}$$

δ Deformation [μm]
 P Operating load [N]
 k Rigidity [N/ μm]

Table 3.101 Radial rigidity for series RG/QR

Load class	Series/ size	Rigidity depending on preload	
		ZA	ZB
Heavy load	RG_15C	504	520
	RG_20C	614	633
	RG_25C	717	740
	QR_25C	645	665
	RG_30C	849	876
	QR_30C	726	748
	RG_35C	1,002	1,035
	QR_35C	856	882
	RG_45C	1,505	1,554
	QR_45C	1,310	1,350
	RG_55C	1,591	1,643
	RG_65C	2,227	2,300
Super heavy load	RG_20H	823	848
	RG_25H	917	947
	QR_25H	770	790
	RG_30H	1,136	1,173
	QR_30H	950	980
	RG_35H	1,344	1,388
	QR_35H	1,140	1,170
	RG_45H	1,938	2,002
	QR_45H	1,660	1,720
	RG_55H	2,182	2,254
	RG_65H	3,077	3,178

Unit: N/ μm

Linear Guideways RG/QR series

3.6.9 Dimensions of the RG/QR blocks

3.6.9.1 RGH/QRH




Table 3.102 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]														Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	L ₁	L	K ₁	K ₂	G	M × l	T	H ₂	H ₃	C _{dyn}	C ₀		
RGH15CA	28	4.0	9.5	34	26	4.0	26	45.0	68.0	13.40	4.70	5.3	M4 × 8	6.0	7.6	10.1	11,300	24,000	0.20	
RGH20CA	34	5.0	12.0	44	32	6.0	36	57.5	86.0	15.80	6.00	5.3	M5 × 8	8.0	8.3	8.3	21,300	46,700	0.40	
RGH20HA							50	77.5	106.0	18.80							26,900	63,000	0.53	
RGH25CA	40	5.5	12.5	48	35	6.5	35	64.5	97.9	20.75	7.25	12.0	M6 × 8	9.5	10.2	10.0	27,700	57,100	0.61	
RGH25HA							50	81.0	114.4	21.50							33,900	73,400	0.75	
QRH25CA	40	5.5	12.5	48	35	6.5	35	66.0	9.9	20.75	7.25	12.0	M6 × 8	9.5	10.2	10.0	38,500	54,400	0.60	
QRH25HA							50	81.0	112.9	21.50							44,700	65,300	0.74	
RGH30CA	45	6.0	16.0	60	40	10.0	40	71.0	109.8	23.50	8.00	12.0	M8 × 10	9.5	9.5	10.3	39,100	82,100	0.90	
RGH30HA							60	93.0	131.8	24.50							48,100	105,000	1.16	
QRH30CA	45	6.0	16.0	60	40	10.0	40	71.0	109.8	23.50	8.00	12.0	M8 × 10	9.5	9.5	10.3	51,500	73,000	0.89	
QRH30HA							60	93.0	131.8	24.50							64,700	95,800	1.15	
RGH35CA	55	6.5	18.0	70	50	10.0	50	79.0	124.0	22.50	10.00	12.0	M8 × 12	12.0	16.0	19.6	57,900	105,200	1.57	
RGH35HA							72	106.5	151.5	25.25							73,100	142,000	2.06	
QRH35CA	55	6.5	18.0	70	50	10.0	50	79.0	124.0	22.50	10.00	12.0	M8 × 12	12.0	16.0	19.6	77,000	94,700	1.56	
QRH35HA							72	106.5	151.5	25.25							95,700	126,300	2.04	
RGH45CA	70	8.0	20.5	86	60	13.0	60	106.0	153.2	31.00	10.00	12.9	M10 × 17	16.0	20.0	24.0	92,600	178,800	3.18	
RGH45HA							80	139.8	187.0	37.90							116,000	230,900	4.13	
QRH45CA	70	8.0	20.5	86	60	13.0	60	106.0	153.2	31.00	10.00	12.9	M10 × 17	16.0	20.0	24.0	123,200	156,400	3.16	
QRH45HA							80	139.8	187.0	37.90							150,800	208,600	4.10	
RGH55CA	80	10.0	23.5	100	75	12.5	75	125.5	183.7	37.75	12.50	12.9	M12 × 18	17.5	22.0	27.5	130,500	252,000	4.89	
RGH55HA							95	173.8	232.0	51.90							167,800	348,000	6.68	
RGH65CA	90	12.0	31.5	126	76	25.0	70	160.0	232.0	60.80	15.80	12.9	M16 × 20	25.0	15.0	15.0	213,000	411,600	8.89	
RGH65HA							120	223.0	295.0	67.30							275,300	572,700	12.13	

For dimensions of rail, see [chapter 3.6.10](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways

RG/QR series

3.6.9.2 RGW/QRW




Table 3.103 Dimensions of the block

Series/ size	Installation dimensions [mm]			Dimensions of the block [mm]																Load ratings [N]		Weight [kg]
	H	H ₁	N	W	B	B ₁	C	C ₁	L ₁	L	K ₁	K ₂	G	M	T	T ₁	H ₂	H ₃	C _{dyn}	C ₀		
RGW15CC	24	4.0	16.0	47	38	4.5	30	26	45.0	68.0	11.40	4.70	5.3	M5	6.0	7	3.6	6.1	11,300	24,000	0.22	
RGW20CC	30	5.0	21.5	63	53	5.0	40	35	57.5	86.0	13.80	6.00	5.3	M6	8.0	10	4.3	4.3	21,300	46,700	0.47	
RGW20HC									77.5	106.0	23.80											
RGW25CC	36	5.5	23.5	70	57	6.5	45	40	64.5	97.9	15.75	7.25	12.0	M8	9.5	10	6.2	6.0	27,700	57,100	0.72	
RGW25HC									81.0	114.4	24.00											
QRW25CC	36	5.5	23.5	70	57	6.5	45	40	66.0	97.9	15.75	7.25	12.0	M8	9.5	10	6.2	6.0	38,500	54,400	0.71	
QRW25HC									81.0	112.9	24.00											
RGW30CC	42	6.0	31.0	90	72	9.0	52	44	71.0	109.8	17.50	8.00	12.0	M10	9.5	10	6.5	7.3	39,100	82,100	1.16	
RGW30HC									93.0	131.8	28.50											
QRW30CC	42	6.0	31.0	90	72	9.0	52	44	71.0	109.8	17.50	8.00	12.0	M10	9.5	10	6.5	7.3	51,500	73,000	1.15	
QRW30HC									93.0	131.8	28.50											
RGW35CC	48	6.5	33.0	100	82	9.0	62	52	79.0	124.0	16.50	10.00	12.0	M10	12.0	13	9.0	12.6	57,900	105,200	1.75	
RGW35HC									106.5	151.5	30.25											
QRW35CC	48	6.5	33.0	100	82	9.0	62	52	79.0	124.0	16.50	10.00	12.0	M10	12.0	13	9.0	12.6	77,000	94,700	1.74	
QRW35HC									106.5	151.5	30.25											
RGW45CC	60	8.0	37.5	120	100	10.0	80	60	106.0	153.2	21.00	10.00	12.9	M12	14.0	15	10.0	14.0	92,600	178,800	3.43	
RGW45HC									139.8	187.0	37.90											
QRW45CC	60	8.0	37.5	120	100	10.0	80	60	106.0	153.2	21.00	10.00	12.9	M12	14.0	15	10.0	14.0	123,200	156,400	3.41	
QRW45HC									139.8	187.0	37.90											
RGW55CC	70	10.0	43.5	140	116	12.0	95	70	125.5	183.7	27.75	12.50	12.9	M14	16.0	17	12.0	17.5	130,500	252,000	5.43	
RGW55HC									173.8	232.0	51.90											
RGW65CC	90	12.0	53.5	170	142	14.0	110	82	160.0	232.0	40.80	15.80	12.9	M16	22.0	23	15.0	15.0	213,000	411,600	11.63	
RGW65HC									223.0	295.0	72.30											

For dimensions of rail, see [chapter 3.6.10](#), for standard and optional lubrication adapter, see [chapter 4.1](#).

Linear Guideways

RG/QR series

3.6.10 Dimensions of the RG rail

The RG rails are used for both the RG and QR blocks.

3.6.10.1 Dimensions of RGR_R




Table 3.104 Dimensions of rail RGR_R

Series/ size	Assembly screw for rail [mm]	Dimensions of rail [mm]						Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
		W_R	H_R	D	h	d	P					
RGR15R	M4 × 16	15	16.5	7.5	5.7	4.5	30.0	4,000	3,960.0	6	24.0	1.70
RGR20R	M5 × 20	20	21.0	9.5	8.5	6.0	30.0	4,000	3,960.0	7	23.0	2.66
RGR25R	M6 × 20	23	23.6	11.0	9.0	7.0	30.0	4,000	3,960.0	8	22.0	3.08
RGR30R	M8 × 25	28	28.0	14.0	12.0	9.0	40.0	4,000	3,920.0	9	31.0	4.41
RGR35R	M8 × 25	34	30.2	14.0	12.0	9.0	40.0	4,000	3,920.0	9	31.0	6.06
RGR45R	M12 × 35	45	38.0	20.0	17.0	14.0	52.5	4,000	3,937.5	12	40.5	9.97
RGR55R	M14 × 45	53	44.0	23.0	20.0	16.0	60.0	4,000	3,900.0	14	46.0	13.98
RGR65R	M16 × 50	63	53.0	26.0	22.0	18.0	75.0	4,000	3,900.0	15	60.0	20.22

3.6.10.2 Dimensions RGR_T (rail mounting from below)




Table 3.105 Dimensions of rail RGR_T

Series/ size	Dimensions of rail [mm]					Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
	W_R	H_R	S	h	P					
RGR15T	15	16.5	M5	8.0	30.0	4,000	3,960.0	6	24.0	1.86
RGR20T	20	21.0	M6	10.0	30.0	4,000	3,960.0	7	23.0	2.76
RGR25T	23	23.6	M6	12.0	30.0	4,000	3,960.0	8	22.0	3.36
RGR30T	28	28.0	M8	15.0	40.0	4,000	3,920.0	9	31.0	4.82
RGR35T	34	30.2	M8	17.0	40.0	4,000	3,920.0	9	31.0	6.48
RGR45T	45	38.0	M12	24.0	52.5	4,000	3,937.5	12	40.5	10.83
RGR55T	53	44.0	M14	24.0	60.0	4,000	3,900.0	14	46.0	15.15
RGR65T	63	53.0	M20 ¹⁾	30.0	75.0	4,000	3,900.0	15	60.0	21.24

¹⁾ Deviating from DIN 645

Note:


1. The tolerance for E is +0.5 to - 1 mm for standard rails and 0 to - 0.3 mm for joints.
2. If the $E_{1/2}$ dimensions are not indicated, the maximum possible number of mounting holes will be determined under consideration of $E_{1/2}$ min.
3. The rails are shortened to the required length. If the $E_{1/2}$ dimensions are not indicated, these will be carried out symmetrically.

Linear Guideways

RG/QR series

3.6.10.3 Calculating the length of rails

HIWIN offers rails in customized lengths. To prevent the risk of the end of the rail becoming unstable, the value E must not exceed half of the distance between the mounting holes (P). At the same time, the value $E_{1/2}$ should be between $E_{1/2}$ min and $E_{1/2}$ max so that the mounting hole does not rupture.



F 3.15

$$L = (n - 1) \times P + E_1 + E_2$$

- L Total length of the rail [mm]
- n Number of mounting holes
- P Distance between two mounting holes [mm]
- $E_{1/2}$ Distance from the middle of the last mounting hole to the end of the rail [mm]

3.6.10.4 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway. The following tightening torques are recommended for the relevant screw sizes.

Table 3.106 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
RG_15	M4 × 16	4	RG_35	M8 × 25	31
RG_20	M5 × 20	9	RG_45	M12 × 35	120
RG_25	M6 × 20	14	RG_55	M14 × 45	160
RG_30	M8 × 25	31	RG_65	M16 × 50	200

3.6.10.5 Cover caps for mounting holes of rails

The cover caps are used to keep the mounting holes free of chips and dirt. The standard plastic caps are provided with each rail. Optional cover caps must be ordered separately.




Table 3.107 Cover caps for mounting holes of rails

Rail	Screw	Article number			Ø D [mm]	Height H [mm]
		Plastic	Brass	Steel		
RGR15R	M4	C4	C4-B	—	7.5	1.1
RGR20R	M5	C5	C5-B	C5-ST	9.5	2.2
RGR25R	M6	C6	C6-B	C6-ST	11.0	2.5
RGR30R	M8	C8	C8-B	C8-ST	14.0	3.3
RGR35R	M8	C8	C8-B	C8-ST	14.0	3.3
RGR45R	M12	C12	C12-B	C12-ST	20.0	4.6
RGR55R	M14	C14	C14-B	C14-ST	23.0	5.5
RGR65R	M16	C16	C16-B	C16-ST	26.0	5.5

Linear Guideways

RG/QR series

3.6.11 Sealing systems

Various sealing systems are available for HIWIN blocks. You will find an overview in chapter 2.9. The table below shows the total length of the blocks with the different sealing systems. Sealing systems suitable for these sizes are available.





Table 3.108 Total length of block with different sealing systems

Series/ size	Total length L					
	SS	DD	ZZ	KK	SW	ZWX
RG_15C	68.0	72.4	70.0	74.4	—	—
RG_20C	86.0	90.4	88.0	92.4	—	—
RG_20H	106.0	110.4	108.0	112.4	—	—
RG_25C	97.9	102.3	99.9	104.3	—	—
QR_25C	97.7	102.3	99.9	104.3	—	—
RG_25H	114.4	118.8	116.4	120.8	—	—
QR_25H	112.9	117.3	114.9	119.3	—	—
RG_30C	109.8	114.6	112.8	117.6	—	—
QR_30C	109.8	114.6	112.8	117.6	—	—
RG_30H	131.8	136.6	134.8	139.6	—	—
QR_30H	131.8	136.6	134.8	139.6	—	—
RG_35C	124.0	129.0	127.0	132.0	—	—
QR_35C	124.0	129.0	127.0	132.0	—	—
RG_35H	151.5	156.5	154.5	159.5	—	—
QR_35H	151.5	156.5	154.5	159.5	—	—
RG_45C	153.2	160.4	156.2	163.4	156.5	166.2
QR_45C	153.2	160.4	156.2	163.4	—	—
RG_45H	187.0	194.2	190.0	197.2	190.3	200.0
QR_45H	187.0	194.2	190.0	197.2	—	—
RG_55C	183.7	190.9	186.7	193.9	186.9	198.3
RG_55H	232.0	239.2	235.0	242.2	235.2	246.6
RG_65C	232.0	240.8	235.0	243.8	235.2	245.3
RG_65H	295.0	303.8	298.0	306.8	298.2	308.3

Unit: mm

3.6.11.1 Designation of seal sets

The sealing sets are always supplied along with the assembly material and include the parts needed in addition to the standard seal.



Series:

RG
QR

Size:

RG: 15, 20, 25, 30, 35, 45, 55, 65
QR: 25, 30, 35, 45

Dust protection ID:

SS: Standard seal
ZZ: End seal with scraper
DD: Double end seal
KK: Double end seal with scraper
SW: End seal with double sealing lip
ZWX: End seal with double sealing lip and scraper

Linear Guideways

RG/QR series

3.6.12 Friction

The table shows the maximum frictional resistance of the individual end seal.
Depending on sealing setup (SS, ZZ, DD, KK), the value may have to be multiplied. The values indicated apply to blocks on uncoated rails. Higher friction forces occur on coated rails.

Table 3.109 Frictional resistance of the single-lipped seals

Series/size	Friction force [N]	Series/size	Friction force [N]
RG_15	2.0	RG/QR_35	3.5
RG_20	2.5	RG/QR_45	4.2
RG/QR_25	2.8	RG_55	5.1
RG/QR_30	3.3	RG_65	6.7

3.6.13 Lubrication unit E2

You will find more information about the lubrication unit in the general information in Section "2.6.3 Oil lubrication unit E2".




Table 3.110 Dimensions of block with lubrication unit E2

Model	Dimensions of the block [mm]								Oil quantity [cm ³]	Mileage ²⁾ [km]
	W	H	T	V	L _{SS} ¹⁾	L _{ZZ} ¹⁾	L _{DD} ¹⁾	L _{KK} ¹⁾		
RG_25C	46.8	29.2	13.5	3.5	114.9	116.9	119.3	121.3	5.0	6,000
RG_25H	46.8	29.2	13.5	3.5	131.4	133.4	135.8	137.8	5.0	6,000
RG_30C	58.8	34.9	13.5	3.5	126.8	129.8	131.6	134.6	7.5	8,000
RG_30H	58.8	34.9	13.5	3.5	148.8	151.8	153.6	156.6	7.5	8,000
RG_35C	68.8	40.3	13.5	3.5	141.0	144.0	146.0	149.0	10.7	10,000
RG_35H	68.8	40.3	13.5	3.5	168.5	171.5	173.5	176.5	10.7	10,000
RG_45C	83.8	50.2	16.0	4.5	173.7	176.7	180.9	183.9	18.5	20,000
RG_45H	83.8	50.2	16.0	4.5	207.5	210.5	214.7	217.7	18.5	20,000
RG_55C	97.6	58.4	16.0	4.5	204.2	207.2	211.4	214.4	26.5	30,000
RG_55H	97.6	58.4	16.0	4.5	252.5	255.5	259.7	262.7	26.5	30,000
RG_65C	121.7	76.1	16.0	4.5	252.5	255.5	261.3	264.3	50.5	40,000
RG_65H	121.7	76.1	16.0	4.5	315.5	318.5	324.3	327.3	50.5	40,000

¹⁾ Total length depending on selected dust protection. SS = Standard dust protection


²⁾ Mileage at which the oil tank level should be checked at the very latest.

Linear Guideways

RG/QR series

3.6.14 Tolerances depending on accuracy class

The RG and QR series are available in four accuracy classes depending on parallelism between block and rail, height accuracy H and accuracy of width N. The choice of accuracy class is determined by the machine requirements.



3.6.14.1 Parallelism

Parallelism of stop surfaces D and B of block and rail and parallelism of top of block C to mounting surface A of rail. Ideal linear guideway installation is required, as is a measurement in the centre of the block.

Table 3.111 Tolerance of parallelism between block and rail

Rail length [mm]	Accuracy class			
	H	P	SP	UP
– 100	7	3	2	2
100 – 200	9	4	2	2
200 – 300	10	5	3	2
300 – 500	12	6	3	2
500 – 700	13	7	4	2
700 – 900	15	8	5	3
900 – 1100	16	9	6	3
1100 – 1500	18	11	7	4
1500 – 1900	20	13	8	4
1900 – 2500	22	15	10	5
2500 – 3100	25	18	11	6
3100 – 3600	27	20	14	7
3600 – 4000	28	21	15	7

Unit: μm

Linear Guideways

RG/QR series

3.6.14.2 Accuracy – height and width

Height tolerance H

Permissible absolute dimension variance of height H, measured between centre of screw-on surface C and underside of rail A, with block in any position on the rail.

Width tolerance N

Permissible absolute dimension variance of width N, measured between centre of screw-on surfaces D and B, with block in any position on the rail.

Height variance of H

Permissible variance of height H between several blocks on a rail, measured in the same rail position.

Width variance of N

Permissible variance of width N between several blocks on a rail, measured in the same rail position.

Table 3.112 Height and width tolerances of non-interchangeable models

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
RG_15, 20	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	0 – 0.03	0 – 0.03	0.006	0.006
	SP (Super precision)	0 – 0.015	0 – 0.015	0.004	0.004
	UP (Ultra precision)	0 – 0.008	0 – 0.008	0.003	0.003
RG_25, 30, 35 QR_25, 30, 35	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	0 – 0.04	0 – 0.04	0.007	0.007
	SP (Super precision)	0 – 0.02	0 – 0.02	0.005	0.005
	UP (Ultra precision)	0 – 0.01	0 – 0.01	0.003	0.003
RG_45, 55 QR_45	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	0 – 0.05	0 – 0.05	0.007	0.01
	SP (Super precision)	0 – 0.03	0 – 0.03	0.005	0.007
	UP (Ultra precision)	0 – 0.02	0 – 0.02	0.003	0.005
RG_65	H (High)	± 0.07	± 0.07	0.02	0.025
	P (Precision)	0 – 0.07	0 – 0.07	0.01	0.015
	SP (Super precision)	0 – 0.05	0 – 0.05	0.007	0.01
	UP (Ultra precision)	0 – 0.03	0 – 0.03	0.005	0.007

Unit: mm


Table 3.113 Height and width tolerances of interchangeable types

Series/size	Accuracy class	Height tolerance of H	Width tolerance of N	Height variance of H	Width variance of N
RG_15, 20	H (High)	± 0.03	± 0.03	0.01	0.01
	P (Precision)	± 0.015	± 0.015	0.006	0.006
RG_25, 30, 35 QR_25, 30, 35	H (High)	± 0.04	± 0.04	0.015	0.015
	P (Precision)	± 0.02	± 0.02	0.007	0.007
RG_45, 55 QR_45	H (High)	± 0.05	± 0.05	0.015	0.02
	P (Precision)	± 0.025	± 0.025	0.007	0.01
RG_65	H (High)	± 0.07	± 0.07	0.02	0.025
	P (Precision)	± 0.035	± 0.035	0.01	0.015

Unit: mm

3.6.14.3 Permissible mounting surface tolerances

Tolerance for the parallelism of the reference surface (P)



Series/size	Preload class		
	Z0	ZA	ZB
RG_15	5	3	3
RG_20	8	6	4
RG/QR_25	9	7	5
RG/QR_30	11	8	6
RG/QR_35	14	10	7
RG/QR_45	17	13	9
RG_55	21	14	11
RG_65	27	18	14

Tolerance for the height of the reference surface (S_1)

F 3.16 $S_1 = a \times K$

Table 3.115 **Coefficient of height tolerance (K)**


Series/size	Preload class		
	Z0	ZA	ZB
RG 15 – 65/QR 25 – 45	2.2×10^{-4}	1.7×10^{-4}	1.2×10^{-4}

Linear Guideways

RG/QR series

Height tolerance of the block mounting surface

- The height tolerance of the reference surface in the parallel use of two or more blocks (S_2)




F 3.17

$$S_2 = b \times 4,2 \times 10^{-5}$$

S_2 Max. height tolerance [mm]
b Distance between blocks [mm]

- The height tolerance of the reference surface in the parallel use of two or more blocks (S_3)



F 3.18

$$S_3 = c \times 4,2 \times 10^{-5}$$

S_3 Max. height tolerance [mm]
c Distance between blocks [mm]

Linear Guideways

RG/QR series

3.6.15 Shoulder heights and fillets

Imprecise shoulder heights and fillets of mounting surfaces compromise precision and may lead to conflicts with the block or rail profiles. The following shoulder heights and edge profiles must be observed in order to avoid assembly problems.




Table 3.116 Shoulder heights and fillets

Series/size	Max. edge radius r_1	Max. edge radius r_2	Shoulder height of reference edge of rail E_1	Shoulder height of reference edge of block E_2	Clearance under block H_1
RG_15	0.5	0.5	4.0	4.0	4.0
RG_20	0.5	0.5	5.0	5.0	5.0
RG/QR_25	1.0	1.0	5.0	5.0	5.5
RG/QR_30	1.0	1.0	5.0	5.0	6.0
RG/QR_35	1.0	1.0	6.0	6.0	6.5
RG/QR_45	1.0	1.0	7.0	8.0	8.0
RG_55	1.5	1.5	9.0	10.0	10.0
RG_65	1.5	1.5	10.0	10.0	12.0

Unit: mm

PG series

The PG series are a special type of the HG/QH series with the integrated, magnetic positioning measurement system MAGIC.

01

Linear Guideways

PG series

3.7 PG series

3.7.1 Properties of the linear guideways, series PG

The HIWIN linear guideways of the PG series are a special type of the HG/QH series with the integrated, magnetic positioning measurement system MAGIC. The positioning measurement systems of the MAGIC series are optimised for measuring the distances travelled in linear movements and particularly on linear motor axes. The measuring system consists of a magnetic measuring gauge on a stainless steel carrier tape and a sensing unit. The robust housing with excellent electrical shielding and real-time signal output make the HIWIN MAGIC series the positioning measurement system of choice for demanding applications.


In the PG series, the stylus is fitted directly on the HG/QH series block. The magnetic tape is integrated in an additional groove in the HGR rail. The MAGIC positioning measurement system is also available as a model not dependent on the rail. The customer can specify where the magnetic tape and stylus are positioned. For details, please refer to the catalogue "Electric drive technology – linear motors, torque motors, positioning measurement systems".

3.7.2 Structure of the PG series

- HG/QH series block
- HG series rail with additional groove for measuring scale
- Encoder can be fitted on HG-20, HG-25, QH-20 and QH-25 size blocks
- Assembly direction: Looking towards the reference edge of the block, the encoder is fitted on the left as standard. The encoder cable is also on the side of the reference edge

Advantages:


- Zero contact measurement with $1 V_{pp}$ or digital output
- Digital resolution of $1 \mu m$
- Encoder and housing are not sensitive to dust, humidity, oil and chips
- Encoder with metal housing and IP67 protection mode
- Simple assembly
- Signal output in real time
- Special housing for EMC optimization




Linear Guideways

PG series

3.7.3 Order codes for the PG series



Continuation of order codes for PG series



Note:

¹⁾ Not the same design as the HGR25R standard rail without groove. M5 assembly screw rather than M6.

²⁾ For the PG series, the total number of blocks per axis is specified (all blocks of the ordered article).

³⁾ The figure 2 is also a quantity, i.e. one item of the above-mentioned article consists of a pair of rails.

No number is specified for individual rails. By default multi-part rails are delivered with staggered butt joints.

⁴⁾ If nothing is specified, the block is supplied with standard dust protection (standard end seal and bottom seal).

For an overview of the various sealing systems, see [chapter 2.9](#).

⁵⁾ With open ends, the 5000 cable length should be selected as standard.

⁶⁾ The display must be ordered separately.

⁷⁾ See Section [3.7.6](#)

Linear Guideways

PG series

3.7.4 Dimensions of the PG blocks

The following figure shows a HGH20CA/HGH25CA block. It is also possible to use the modules with HG20, HG25, QH20 and QH25 block sizes. The overall dimensions then change accordingly. The dimensions of all block sizes are shown in [Table 3.114](#).




Table 3.117 Dimensions of the block

Series/size	L [mm]	L1 [mm]	B [mm]	B1 [mm]	H [mm]	H1 [mm]
HG_20C	118.0	41.5	44	43.0	30	4.6
HG_20H	132.7	41.5	44	43.0	30	4.6
HG_25C	124.5	41.5	48	46.4	40	5.5
HG_25H	145.1	41.5	48	46.4	40	5.5
QH_20C	117.2	41.5	44	43.0	30	4.6
QH_20H	131.9	41.5	44	43.0	30	4.6
QH_25C	123.9	41.5	48	46.4	40	5.5
QH_25H	144.5	41.5	48	46.4	40	5.5

Unit: mm

3.7.5 Dimensions of the PG rails

3.7.5.1 Rail with groove, mounting from above




Table 3.118 Dimensions of HGR_R G1

Series/ size	Dimensions of rail [mm]						Max. length [mm]	Max. length E ₁ = E ₂ [mm]	E _{1/2} min [mm]	E _{1/2} max [mm]	Weight [kg/m]
	W _R	H _R	D	h	d	P					
HGR20R G1	20	17.5	9.5	8.5	6.0	60	4,000	3,900	7	53	2.05
HGR25R G1C	23	22.0	9.5	8.5	6.0	60	4,000	3,900	7	53	3.05

Linear Guideways

PG series

3.7.5.2 Rail with groove, mounting from below




Table 3.119 Dimensions of HGR_T G1

Series/ size	Dimensions of rail [mm]					Max. length [mm]	Max. length $E_1 = E_2$ [mm]	$E_{1/2}$ min [mm]	$E_{1/2}$ max [mm]	Weight [kg/m]
	W_R	H_R	S	h	P					
HGR20T G1	20	17.5	M6	10	60	4,000	3,900	7	53	2.13

3.7.5.3 Tightening torques for mounting bolts

Insufficient tightening of the mounting bolts strongly compromises the precision of the linear guideway; the following tightening torques are therefore recommended for the relevant screw sizes.


Table 3.120 Tightening torques of the mounting bolts according to ISO 4762-12.9

Series/size	Screw size	Torque [Nm]	Series/size	Screw size	Torque [Nm]
HGR20R G1	M5 × 16	9	HGR25R G1C	M5 × 20	9
HGR20T G1	M6	13			

3.7.6 Orientation of the HIWIN MAGIC-PG encoder

According to the order code (section 3.7.3) the HIWIN MAGIC-PG encoder is available in the orientations 1 to 4 as shown below. Without a statement about the required orientation the encoder is delivered by default (orientation 1).

For more than one block on a rail or on a rail pair, the encoder is assembled on block 1, rail 1, as shown below. If a non-standard orientation is needed, this has to be defined in the MAGIC-PG project planning sheet (www.hiwin.cz).



Linear Guideways

PG series

3.7.7 Specifications of the positioning measurement system HIWIN MAGIC and HIWIN MAGIC-PG

Table 3.121 Electrical and mechanical properties of HIWIN MAGIC and HIWIN MAGIC-PG

	1 V _{pp} (analogue)	TTL (digital)
Electrical properties		
Output signal specification	sin/cos, 1 V _{pp} (0.85 V _{pp} – 1.2 V _{pp})	Quadrature signal acc. to RS 422
Resolution	Infinite, signal period 1 mm	1 µm
Repetition accuracy bidirectional	0.003 mm	0.002 m
Absolute accuracy	± 20 µm/m	
Reference signal ¹⁾	Periodic index impulse at a distance of 1 mm	
Phase angle	90° ± 0,1° el	90°
DC component	2.5 V ± 0.3 V	—
Distortion factor	Typ. < 0.1 %	—
Operating voltage	5 V ± 5 %	
Power consumption	Typ. 35 mA, max. 70 mA	Typ. 70 mA, max. 120 mA
Max. measurement speed	10 m/s	5 m/s
EMC class	3, according to IEC 801	
Mechanical properties		
Housing material	Aluminium alloy, encoder bottom made of stainless steel	
Dimensions of MAGIC encoder	L × B × H: 45 × 12 × 14 mm	
Standard cable length ²⁾	5 m	
Min. bending radius cable	40 mm	
Protection class	IP67	
Operating temperature	0 °C to +50 °C	
Weight of MAGIC encoder	80 g	
Weight of MAGIC-PG encoder	80 g	
MAGIC-PG suitable for blocks	HG-20, HG-25, QH-20, QH-25	

¹⁾ Can be used with proximity switch

²⁾ For the use in drag chains we recommend our pre-assembled encoder cable with a pre-mounted round connector M17 (coupling, female) on one side, which matches the optional round plug connector M17 (male) of the encoder. For details, please contact your HIWIN technician.

Table 3.122 Properties of the magnetic scale


Properties	Magnetic scale (including stainless steel protective cover tape)
Accuracy class ¹⁾	± 20 µm/m
Linear expansion coefficient	11.5 × 10 ⁻⁶ m/K
Period	1 mm
Thickness magnetic scale	1.70 ± 0.10 mm
Thickness magnetic scale + protective cover tape	1.85 ± 0.15 mm
Width	10.05 ± 0.10 mm
Maximum length	24 m
Magnetic remanence	> 240 mT
Pole pitch (distance north/south pole)	1 mm
Single reference marks	Optional
Material	Elastomers, nitrile and EPDM
Temperature range	0 °C to +50 °C
Weight	70 g/m

¹⁾ at 20 °C

Linear Guideways

PG series

Separate magnetic scale (left) without protective cover tape and integrated into a profile rail (right) with stainless steel protective cover tape



3.7.8 Connection for MAGIC positioning measurement system

3.7.8.1 Cable assignment (analogue and digital variant)

A high-quality, 8-core cable

(1 each of V1+, V1-, V2+, V2- and V0+, V0- (or A, \bar{A} , B, \bar{B} und Z, \bar{Z} for the digital variant) suitable for cable track is used twisted in pairs.

In drag lines, we generally recommend our pre-assembled extension cables, which are designed especially for use in such lines. The extension cables are supplied with a round plug connector on one end (female coupling) or customized.


3.7.8.2 MAGIC measurement system formats and outputs (analogue)

Signal format of sine/cosine 1 V_{pp} output


The electrical signals after the differential input of the subsequent electronics. The

HIWIN MAGIC sine/cosine 1 V_{pp} interface is strictly oriented towards the Siemens specification. The period length of the sine output signal is 1 mm. The period length of the reference signal is 1 mm.

Electrical signals after the differential input of the downstream electronic components (analogue version)



Recommended subsequent electronics circuit for sine/cosine 1 V_{pp} output




Linear Guideways

PG series


TTL-output (digital)

The signals on A and B channels have a 90° phase shift (according to RS422 specification in DIN 66259). Recommended terminal resistance $Z = 120 \Omega$. Output signals: A, \bar{A} , B, \bar{B} and Z, \bar{Z} . Individual reference pulse (optional) and definition of a minimum pulse duration are possible as an option.

Signals of the MAGIC encoder (TTL version)



Recommended subsequent electronics circuit for TTL output



Accessories

01

Linear Guideways Accessories

4. Accessories

4.1 Lubrication adapters

A grease nipple is attached to the front side of the block as standard **(1)**. The lubrication connection on the opposite side is sealed with a plug screw. Alternatively, lubrication can also be carried out through one of the four laterally provided connections on the recirculation unit **(2)** or from above **(3)**. Grease nipples, lubrication adapters or push-on connectors can be used for lubrication.




Table 4.1 Overview block type/thread size

Block type	Thread size front/side
HG_15	M4
HG_20, HG_25, HG_30, HG_35	M6 × 0.75
HG_45, HG_55, HG_65	1/8 PT
QH_15	M4
QH_20, QH_25, QH_30, QH_35	M6 × 0.75
QH_45	1/8 PT
EG_15	M4
EG_20, EG_25, EG_30, EG_35	M6 × 0.75
QE_15	M4
QE_20, QE_25, QE_30, QE_35	M6 × 0.75
WE_17	M3
WE_21, WE_27, WE_35, QW_21, QW_27, QW_35	M6 × 0.75
WE_50	1/8 PT
MG_15	M3
RG_15, RG_20	M4
RG_25, RG_30, RG_35	M6 × 0.75
RG_45, RG_55, RG_65	1/8 PT
QR_25, QR_30, QR_35	M6 × 0.75
QR_45	1/8 PT

Linear Guideways

Accessories

4.1.1 Grease nipples and lubrication fittings

Table 4.2 Grease nipples M3 × 0.5P






	
Art.No.: 20-000275 (Standard)	Art.No.: 20-000370 (Option)

Table 4.3 Grease nipples and lubrication fittings M4 × 0.7P

 <p>Technical drawing of the grease nipple showing dimensions: M6 × 0.75P, 7, 10, 8, 4, M4 × 0.7P, 16.5, Ø5.</p>	
LF-64 Art.No.: 20-000019	
	
Art.No.: 20-000272 (Standard)	Art.No.: 20-000325 (Option)

The stated article numbers apply to the standard dust protection. Article numbers for optional dust protection available on request.

Linear Guideways Accessories

Table 4.4 Grease nipples and lubrication fittings M6 × 0.75P

SF-76 Art.No.: 20-000006	LF-76 Art.No.: 20-000007	SF-86 Art.No.: 20-000008	LF-86 Art.No.: 20-000009
Art.No.: 20-000273 (Option)	Art.No.: 20-000283 (Option)	Art.No.: 20-000290 (Standard)	

Table 4.5 Grease nipples and lubrication fittings 1/8 PT

SF-78 Art.No.: 20-000010	LF-78 Art.No.: 20-000011	SF-88 Art.No.: 20-000012	LF-88 Art.No.: 20-000013
Art.No.: 20-000280 (Option)	Art.No.: 20-000292 (Standard)		

The stated article numbers apply to the standard dust protection. Article numbers for optional dust protection available on request.

Linear Guideways

Accessories

4.1.2 Push-in fittings

Table 4.6 Push-in fittings




Table 4.7 Dimensions of push-in fittings

Type	Article number	G	Ø D	Shape	H	L	L1	L2
TCS-44	8-12-0186	M4 × 0.7	4	Straight	4	20.5	—	—
TCS-46	8-12-0127	M6 × 0.75	4	Straight	5	23.5	—	—
TCS-66	20-000463	M6 × 0.75	6	Straight	4	22.5	—	—
TCL-46	8-12-0128	M6 × 0.75	4	Angled	5	—	15.5	18
TCL-66	8-12-0138	M6 × 0.75	6	Angled	5	—	15.5	21
TCS-4G	8-12-0131	G 1/8	4	Straight	6	20.0	—	—
TCS-6G	8-12-0136	G 1/8	6	Straight	6	24.0	—	—
TCL-4G	8-12-0130	G 1/8	4	Angled	6	—	20.0	20
TCL-6G	8-12-0137	G 1/8	6	Angled	6	—	20.0	21

The stated article numbers apply to the standard dust protection. Article numbers for optional dust protection available on request.

Linear Guideways

Accessories

4.2 HIWIN grease guns and lubricants

Table 4.8 HIWIN grease guns

Grease gun	Lubrication adapter and set of nozzles GNZ-05-BOX	Direct filling	Cartridge
GN-080M	without	●	70 g
GN-080M	with	●	70 g
GN-400C	without	●	400 g
GN-400C	with	●	400 g

Table 4.9 HIWIN greases G

Grease type	Area of application	Article number		
		70 g cartridge	400 g cartridge	1 kg container ¹⁾
G01	Heavy-duty applications	G01-0070	G01-0400	G01-1000
G02	Clean room applications	G02-0070	G02-0400	G02-1000
G03	Clean room applications High speed	G03-0070	G03-0400	G03-1000
G04	High speed	G04-0070	G04-0400	G04-1000
G05	Standard grease	G05-0070	G05-0400	G05-1000

¹⁾ Delivery time on request

Table 4.10 HIWIN grease PLO

Grease type	Area of application	Article number	
		400 g cartridge	1 kg container
PLO-05	Standard grease	PLO-05-400	PLO-05-1000

Table 4.11 HIWIN oils

Description	Scope of delivery	Comment
SHC 636	1-litre bottle	Oil for filling the E2 lubrication tank

You will also find details about the HIWIN lubricants and lubrication of the linear guideways on www.hiwin.cz.



Linear Guideways

Notes

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Notes

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal grey lines across the entire width of the page, providing a guide for handwriting or typing. The background is a solid off-white color.

Linear Guideways

Notes

[illegible]

Notes

[illegible]



HIWIN S.R.O.

MEDKOVA 888/11
627 00 BRNO
CZECH REPUBLIC
TEL.: +420 548 528 238
FAX.: +420 548 220 223
EMAIL: INFO@HIWIN.CZ

WWW.HIWIN.CZ

HIWIN S.R.O.

MLÁDEŽNÍČKA 2101
01701 POVÁŽSKÁ BYSTRICA
SLOVAKIA
TEL.: +421 424 434 777
FAX.: +421 424 262 306
EMAIL: INFO@HIWIN.SK

WWW.HIWIN.SK

HIWIN BULGARIA OOD

VIDRICA 7
1532 SOFIA-KAZICHENE
BULGARIA
TEL.: +359-2 974 5659
FAX.: +359-2 974 5659
EMAIL: INFO@HIWIN.BG

WWW.HIWIN.BG

Technical data subject to change without notice

© Hiwin s.r.o. 2017 II.